LIMITED TO STOCK ON HAND IN BREA, CA



DTC PIVOT POINT C80 SERIES SOFT CLOSE QUICK DOWEL HINGES

- Soft Close
- · Quick Dowel Attachment
- Cup Depth 11.5mm
- Door Thickness 16-26mm
- Possible Tab Distance 3-6mm



\$1.39 DTCC80A675T8F C80

• 110 Degree Opening



\$1.69

DTC80H675T8 C80

• 135 Degree Opening



\$2.49

DTC80A605T8F C80

155 BI-Fold Degree Opening

 Cam Adjustment +/- 2mm



\$0.39 DTC89H10JQ

• 00mm Face Frame Mounting Plate



\$0.44

DTC89H30JQ

• 03MM Face Frame Mounting Plate



\$0.49 DTC89H60JQ

• 06MM Face Frame Mountin Plate

DTC SD20 SOFT CLOSE FULL EXTENSION UNDERMOUNT SLIDES



- 12mm-16mm Drawer Thickness
- 100,000 Cycle Tested

Includes:

- 0DS03-A-2D Front Locking Device
- · Height and Side to Side Adjustment

Item #	Description	LP2287 Price per Pair
DTCSD20229H	09" Soft Close Full Extension Undermount Slide 2D Front Locking Device	\$8.69
DTCSD20305H	12" Soft Close Full Extension Undermount Slide 2D Front Locking Device	\$8.39
DTCSD20381H	15" Soft Close Full Extension Undermount Slide 2D Front Locking Device	\$8.39
DTCSD20457H	18" Sof Close Full Extension Undermoutn Slide 2D Front Locking Device	\$8.69
DTCSD20533H	21" Soft Close Full Extension Undermount Slide 2D Front Locking Device	\$9.09

Offer valid: 8/19 - 9/30/2025. Please reference promo code LP2287 when placing an order with Customer Service. For online orders, enter promo code LP2287 in the promo code field of the shopping cart.

Würth Louis and Company (800) 422-4389 www.wurthlac.com

OPT-OUT INFORMATION: You may request Würth Louis and Company not to send any future advertisements to a telephone facsimile machine or machines. Failure to comply with such a request in the form prescribed by law, within the shortest time prescribed by law not to exceed 30 days, is unlawful. If you wish to discontinue future fax advertisements from Würth Louis and Company, Please send your request by Email to: creditdepartment@wurthlac.com, or by Fax to: 800-944-7494 or by Calling: 800-422-4389 option 2. Your request should specify the telephone numbers or numbers of each telephone facsimile machine to which the request relates.