

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 02/12/2024

Reviewed on 11/17/2022

### 1 Identification

- **Product identifier**
- **Trade name:** LP 289/99
- **Application of the substance / the mixture** Antistatic coolant
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Riepe GmbH & Co. KG  
Theodor Rosenbaum Str. 28-30  
32257 Bünde - Deutschland  
Tel.: +49 (0) 5223 - 687407-0  
Fax: +49 (0) 5223 - 687407-50  
E-Mail: info@riepe.eu
- **Information department:**  
Tel.: +49 (0) 5223 - 687407-0  
E-mail: info@riepe.eu
- **Emergency telephone number:**  
Advice center for poisoning, Mainz  
Tel. 0 61 31 / 19 240

Emergency Phone: 1-800-424-9300  
CHEMTREC 24 Hrs

Information Phone #: 336-884-1846  
ADWOOD CORPORATION - NC

### 2 Hazard(s) identification

- **Classification of the substance or mixture**  
Flammable Liquids 3 H226 Flammable liquid and vapor.  
Eye Irritation 2A H319 Causes serious eye irritation.  
Carcinogenicity 1A H350 May cause cancer.
- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**  
ethanol
- **Hazard statements**  
Flammable liquid and vapor.  
Causes serious eye irritation.  
May cause cancer.
- **Precautionary statements**  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Wear protective gloves / eye protection / face protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 02/12/2024

Reviewed on 11/17/2022

Trade name: LP 289/99

(Contd. of page 1)

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**- Classification system:**

**- NFPA ratings (scale 0 - 4)**

Health = 2

Fire = 3

Reactivity = 0

**- HMIS-ratings (scale 0 - 4)**

Health = \*2

Fire = 3

Reactivity = 0

**- Other hazards**

**- Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

**- Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with harmless additions

**- Dangerous components:**

64-17-5	ethanol	50-100%
67-63-0	propan-2-ol	2.5-10%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### 4 First-aid measures

**- Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

**- After skin contact:**

Remove contaminated clothing immediately. Wash affected areas with plenty of water und soap. If irritation continues, contact a doctor.

- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

**- After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting.

If symptoms persist consult doctor.

**- Information for doctor:**

**- Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**- Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Fire-fighting measures

**- Extinguishing media**

**- Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 3)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 02/12/2024

Reviewed on 11/17/2022

Trade name: LP 289/99

(Contd. of page 2)

- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
Can form explosive gas-air mixtures. In case of incomplete combustion carbon monoxide can arise. Fumes are heavier than air and distributed over ground. Inflammation is possible from a far distance.
- **Advice for firefighters**
- **Protective equipment:**  
See section 8.  
Wear self-contained respiratory protective device.
- **Additional information**  
Endangered containers in the surrounding area should be cooled with a water-hose.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment and keep unprotected persons away.  
Extinguish naked flames. Remove flammable sources. No smoking. Avoid sparks. Avoid contact with skin, eyes and clothing. Avoid inhalation of fumes. Air contaminated rooms thoroughly. Protect against electrostatic sparks.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
In case of release of larger quantities, inform competent authorities.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

#### - PAC-1:

64-17-5	ethanol	1,800 ppm
67-63-0	propan-2-ol	400 ppm
78-93-3	2-Butanone	200 ppm
102-71-6	Triethanolamine	15 mg/m <sup>3</sup>
124-68-5	2-amino-2-methylpropanol	17 mg/m <sup>3</sup>
141-43-5	2-aminoethanol	6 ppm
29385-43-1	methyl-1H-benzotriazole	2 mg/m <sup>3</sup>

#### - PAC-2:

64-17-5	ethanol	3300* ppm
67-63-0	propan-2-ol	2000* ppm
78-93-3	2-Butanone	2700* ppm
102-71-6	Triethanolamine	240 mg/m <sup>3</sup>
124-68-5	2-amino-2-methylpropanol	190 mg/m <sup>3</sup>
141-43-5	2-aminoethanol	170 ppm
29385-43-1	methyl-1H-benzotriazole	22 mg/m <sup>3</sup>

#### - PAC-3:

64-17-5	ethanol	15000* ppm
---------	---------	------------

(Contd. on page 4)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 02/12/2024

Reviewed on 11/17/2022

Trade name: LP 289/99

		(Contd. of page 3)
67-63-0	propan-2-ol	12000** ppm
78-93-3	2-Butanone	4000* ppm
102-71-6	Triethanolamine	1,500 mg/m <sup>3</sup>
124-68-5	2-amino-2-methylpropanol	570 mg/m <sup>3</sup>
141-43-5	2-aminoethanol	1,000 ppm
29385-43-1	methyl-1H-benzotriazole	130 mg/m <sup>3</sup>

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Store in cool, dry place in tightly closed receptacles.  
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**  
Protect against direct sunlight, other sources of heat and ignition.  
Store in cool, dry conditions in well sealed receptacles.
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storage and handling of water hazardous substances  
Store in a cool location.  
Store in the original container if possible
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:**  
Pay attention to regulations/technical rules for the storage of combustible liquids.
- **Storage class:** 3(VCI - Concept, 2007)
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:**  
Raumlüftung bzw. Absaugung. Maßnahmen gegen elektrostatische Aufladung.
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

#### 64-17-5 ethanol

PEL	Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm
TLV	Short-term value: 1000 ppm
	A3

#### 67-63-0 propan-2-ol

PEL	Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
REL	Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
TLV	Short-term value: 400 ppm Long-term value: 200 ppm
	BEI, A4

(Contd. on page 5)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 02/12/2024

Reviewed on 11/17/2022

Trade name: LP 289/99

(Contd. of page 4)

### - Ingredients with biological limit values:

#### 67-63-0 propan-2-ol

BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----	---

- **Additional information:** The lists that were valid during the creation were used as basis.

#### - Exposure controls

##### - Personal protective equipment:

##### - General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.  
Gases, fumes and aerosols should not be inhaled.

- **Breathing equipment:** Use suitable respiratory protective device in case of insufficient ventilation.

##### - Recommended filter device for short term use:

Filter AX  
(EN 14387)

##### - Protection of hands:

Solvent resistant gloves  
(EN 374)

##### - Material of gloves

Butylrubber, BR, recommended thickness of the material:  $\geq 0.7$  mm, penetration time:  $\geq 480$  min.  
Fluorocarbon rubber (Viton), recommended thickness of the material:  $\geq 0.7$  mm, penetration time:  $\geq 480$  min.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- **Penetration time of glove material** Change gloves if notice sign of disenchantment.

##### - Eye protection:

Tightly sealed goggles  
(EN 166)

##### - Body protection:

Standard protective clothing. Chemical resistant safety-shoes or boots. If skin contact is possible, wear impenetrable protective clothing against this solvent.  
(EN 368)

## \* 9 Physical and chemical properties

### - Information on basic physical and chemical properties

#### - General Information

##### - Appearance:

Form:	Fluid
Color:	Blue

- Odor: Alcohol-like

- Odor threshold: Not determined.

- pH-value at 20 °C (68 °F): 10.3

- Melting point/Melting range: Undetermined.

- Boiling point/Boiling range: Undetermined.

(Contd. on page 6)

— USA —

## Safety Data Sheet

acc. to OSHA HCS

Printing date 02/12/2024

Reviewed on 11/17/2022

Trade name: LP 289/99

(Contd. of page 5)

- <b>Flash point:</b>	24 °C (75.2 °F)
- <b>Flammability (solid, gaseous):</b>	Flammable.
- <b>Auto igniting:</b>	425 °C (797 °F)
- <b>Decomposition temperature:</b>	Not determined.
- <b>Ignition temperature:</b>	Product is not selfigniting.
- <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
- <b>Explosion limits:</b>	
<b>Lower:</b>	4.8 Vol % (determined (EN 1839))
<b>Upper:</b>	15 Vol % (ethanol)
- <b>Vapor pressure at 20 °C (68 °F):</b>	57 hPa (42.8 mm Hg)
- <b>Vapor pressure at 50 °C (122 °F):</b>	280 hPa (210 mm Hg)
- <b>Density at 20 °C (68 °F):</b>	0.87 g/cm <sup>3</sup> (7.26 lbs/gal)
- <b>Relative density</b>	Not determined.
- <b>Vapor density</b>	Not determined.
- <b>Evaporation rate</b>	Not determined.
- <b>Solubility in / Miscibility with Water:</b>	Fully miscible.
- <b>Partition coefficient (n-octanol/water):</b>	Not determined.
- <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
- <b>Solvent content:</b>	
<b>VOC content:</b>	45.0 %
- <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** strong oxidizing agents
- **Hazardous decomposition products:** Formation of carbon monoxide and carbon dioxide in case of fire.

USA  
(Contd. on page 7)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 02/12/2024

Reviewed on 11/17/2022

Trade name: LP 289/99

(Contd. of page 6)

### 11 Toxicological information

#### - Information on toxicological effects

##### - Acute toxicity:

##### - LD/LC50 values that are relevant for classification:

###### 64-17-5 ethanol

Oral	LD50	10,470 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC 50 / 4 h	>50 mg/l (rat) (OECD 403) >20 mg/l (mouse)

###### 67-63-0 propan-2-ol

Oral	LD50	5,840 mg/kg (rat) (OECD 401) 4,570 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit) 13,400 mg/kg (rab)
Inhalative	LC 50 / 4 h	30 mg/l (rat)

##### - Primary irritant effect:

- **on the skin:** No irritant effect.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

##### - Additional toxicological information:

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

##### - Carcinogenic categories

##### - IARC (International Agency for Research on Cancer)

64-17-5	ethanol	1
67-63-0	propan-2-ol	3
102-71-6	Triethanolamine	3

##### - NTP (National Toxicology Program)

None of the ingredients is listed.

##### - OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### \*12 Ecological information

#### - Toxicity

##### - Aquatic toxicity:

###### 64-17-5 ethanol

LC 50 / 48 h	8,140 mg/l (Leuciscus idus)
EC 50 / 48 h	>10,000 mg/l (Daphnia magna)
EC 50 / 72 h	275 mg/l (Chlorella vulgaris) (OECD 201)

###### 67-63-0 propan-2-ol

LC 50 / 96 h	>10,000 mg/l (Pimephales promelas) (OECD 203 (Acute toxicity - fish))
LC 50 / 48 h	>100 mg/l (Leuciscus idus)

(Contd. on page 8)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 02/12/2024

Reviewed on 11/17/2022

Trade name: LP 289/99

(Contd. of page 7)

EC 50 / 48 h	>100 mg/l (Daphnia magna)
EC 50 / 16 h	1,050 mg/l (Pseudomonas putida) (DIN 38412 T.8)
EC 50 / 72 h	>100 mg/l (Scenedesmus subspicatus)

**- Persistence and degradability**

Easily biodegradable

**64-17-5 ethanol**

Biodegradability &gt;70 % /5d (OECD 301 D)

**67-63-0 propan-2-ol**

Biodegradability 49 % /BOD/ThBOD

Biodegradability 53 % /5 d, BSB5/CS (92/69/EG (L383) C.5 \* Abbaubarkeit)

CSB 2.23 mg O2/g (Methode : Verordnung (EC) Nr. 440/2008, Anhang, C.)

BSB5 1.72 mg O2/g (Methode : Verordnung (EC) Nr. 440/2008, Anhang, C.)

The product is readily biodegradable.

**- Behavior in environmental systems:**

**- Bioaccumulative potential** No further relevant information available.

**- Mobility in soil** No further relevant information available.

**- Ecotoxic effects:**

**- Bacteria inhibition EC 20 (mg/l according to ISO 8192 B):**

**64-17-5 ethanol**

EC 50 (static) &gt;100 mg/l (Chlorella pyrenoidosa) (OECD 201)

**- Additional ecological information:**

**- General notes:**

Do not allow to enter drainage system, surface or ground water

Water hazard class 1 (Self-assessment): slightly hazardous for water

**- Results of PBT and vPvB assessment**

**- PBT:** Not applicable.

**- vPvB:** Not applicable.

**- Other adverse effects** No further relevant information available.

### \*13 Disposal considerations

**- Waste treatment methods**

The note below refers to the product left as it is and not to further processed products. When mixed with other products, other disposal routes may be required; in case of doubt, consult the supplier of the product or the local authority.

**- Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

If possible, send to be recycled, otherwise burn or deposit in a certified facility.

**- Waste disposal key:**

Since 01/01/99 the waste code numbers have not only been product-related but are also essentially application-related. The valid waste code number of the application can be obtained from the European waste catalogue.

**- Uncleaned packagings:** Disposal must be made according to official regulations.

**- Recommendation:**

**Rented packaging:** After optimal emptying, close immediately and return to the supplier without cleaning.

Care should be taken that no other materials get into the packaging.

**Other containers:** After complete emptying and cleaning, send to be reconditioned or recycled.

(Contd. on page 9)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 02/12/2024

Reviewed on 11/17/2022

Trade name: LP 289/99

(Contd. of page 8)

Caution: Leftovers in the containers may cause the risk of explosion.  
Uncleaned containers should not be perforated, cut or welded.

### 14 Transport information

- UN-Number	UN1987
- DOT, ADR/RID/ADN, IMDG, IATA	UN1987
- UN proper shipping name	Alcohols, n.o.s. (Isopropanol, Ethanol)
- DOT	1987 ALCOHOLS, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL), ETHANOL (ETHYL ALCOHOL))
- ADR/RID/ADN	1987 ALCOHOLS, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL), ETHANOL (ETHYL ALCOHOL))
- IMDG	ALCOHOLS, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL), ETHANOL (ETHYL ALCOHOL))
- IATA	ALCOHOLS, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL), ETHANOL)
- Transport hazard class(es)	
- DOT, IMDG, IATA	3 Flammable liquids
- Class	3
- Label	3
- ADR/RID/ADN	
- Class	3 (F1) Flammable liquids
- Label	3
- Packing group	III
- DOT, ADR/RID/ADN, IMDG, IATA	III
- Environmental hazards:	Not applicable.
- Marine pollutant:	No
- Special precautions for user	Warning: Flammable liquids
- Hazard identification number (Kemler code):	30
- EMS Number:	F-E, S-D
- Stowage Category	A
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
- Transport/Additional information:	
- ADR/RID/ADN	
- Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
- IMDG	
- Limited quantities (LQ)	5L
- Excepted quantities (EQ)	Código E4 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 10)

USA

## Safety Data Sheet

acc. to OSHA HCS

Printing date 02/12/2024

Reviewed on 11/17/2022

Trade name: LP 289/99

(Contd. of page 9)

<b>- UN "Model Regulation":</b>	UN 1987 ALCOHOLS, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL), ETHANOL (ETHYL ALCOHOL)), 3, III
---------------------------------	---

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Sara**

- **Section 313 (Specific toxic chemical listings):**

Substance is listed:

67-63-0 propan-2-ol

- **TSCA (Toxic Substances Control Act):**

64-17-5	ethanol
7732-18-5	water, distilled, conductivity or of similar purity
67-63-0	propan-2-ol
78-93-3	2-Butanone
102-71-6	Triethanolamine
124-68-5	2-amino-2-methylpropanol
141-43-5	2-aminoethanol
29385-43-1	methyl-1H-benzotriazole

- **Hazardous Air Pollutants**

None of the ingredients is listed.

- **National regulations:**

- **Information about limitation of use:**

Employment restrictions concerning young persons must be observed.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Registration-Number**

- **Relevant phrases**

Complete wording of hazard statements and risk phrases (H-phrases) mentioned in section 3. These phrases refer to the constituents. The labelling for this product is stated in section 2.

- **Department issuing SDS:** See section 1.3: Informing area

- **Contact:**

- **Date of preparation / last revision** 02/12/2024

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

LEV: Local Exhaust Ventilation

RPE: Respiratory Protective Equipment

RCR: Risk Characterisation Ratio (RCR= PEC/PNEC)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 11)

— USA —

## Safety Data Sheet

acc. to OSHA HCS

Printing date 02/12/2024

Reviewed on 11/17/2022

---

**Trade name: LP 289/99**

---

(Contd. of page 10)

*IATA: International Air Transport Association**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**TRGS: Technische Regeln für Gefahrstoffe (Technical Rules for Dangerous Substances, BAuA, Germany)**VOC: Volatile Organic Compounds (USA, EU)**ISO: International Organisation for Standardisation**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**vPvB: very Persistent and very Bioaccumulative**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**BEI: Biological Exposure Limit**Flammable Liquids 3: Flammable liquids – Category 3**Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A**Carcinogenicity 1A: Carcinogenicity – Category 1A***- \* Data compared to the previous version altered.**

---

USA

---