

D405ANC

1-AXIS SLIDING TABLE SAW





- · Programmable rip fence with maximum cutting width of 51" by means of a precision ball screw
- Motorized blade rise/fall
- · Motorized blade tilting with electronic angle display on control panel
- · Overhead control panel can be adjusted for operator convenience
- · Convenient external manual scoring adjustment
- · 7.5 HP main motor with 1HP scoring motor
- (3) saw blade speeds for optimum cutting results in various materials
- · Precision anodized aluminum sliding table with prismatic rollers running on precision ground steel guides
- · Aluminum extruded crosscut fence with (2) flip stops with convenient angle adjustment for mitre cuts
- · Solid cast iron main table which is ground and polished
- Heavy-duty outrigger for strong support of work-piece during cutting operations
- · Overhead CE blade guard with dust port
- · Complete with eccentric clamp and wedge for solid wood cutting

SPECIFICATIONS

Cast iron fixed table dimension	21.6" x 35.3"
Sliding table dimension	126" x 15 ½"
Extension table (rear)	37 ½" x 35 ¼"
Extension table (front)	32.7" x 12.6"
Max. main saw blade diameter	355mm (14")
Main saw bore	30 mm
Max. cutting height at 90° (355mm)	4.13"
Max. cutting height at 45° (355mm)	2.76"
Main saw motor	7.5 HP
Main blade speed	3000/ 4000/ 5000 RPM
Scoring saw blade	120 mm
Scoring saw blade bore	20 mm
Scoring blade motor	1 HP
Scoring blade speed	8000 RPM
Max rip cutting width	51.2"
Cutting width adjustment	NC control
Blade tilting adjustment	Motorized (0°~45°)
Main saw height adjustment	Motorized
Dust collection system	4.72" / 4" (120/ 102 mm)
Machine weight	1740 lbs.
Machine shipping dimension	83" x 45 ½" x 44" (1782 lbs)
Sliding table shipping dimension	137" x 19 ½" x 14 ½" (432 lbs)

















T: 1.888.982.2683 F: 604.540.1780



