




D405M

SLIDING TABLE SAW



FEATURES

- 7.5 HP main motor with 1HP scoring motor
- 8 foot precision anodized aluminum sliding table with prismatic rollers running on precision ground steel guides
- Solid cast iron main table which is ground and polished
- Heavy-duty outrigger for strong support of work-piece during cutting operations
- Solid rip fence with manual fine adjustment and locking lever
- Manual saw blade rise/fall & tilting, conveniently located on the operator side of the machine
- Pointer indicator for accurately displaying blade angle
- Aluminum extruded crosscut fence with two flip stops with dual metric and inch rulers
- Eccentric hold down clamp, table return handle, and wedge for solid wood ripping included
- Optional overhead saw blade guard with built in dust port included (CE-type)

SPECIFICATIONS

	D405M-8	D405M-10
Cast iron fixed table dimension	21.6" x 35.3"	
Sliding table dimension	102.4" x 14 3/4"	126" x 15.5"
Max rip cutting width	51.2"	
Main saw blade diameter (max.)	400mm (15.75")	
Main saw bore	30 mm	
Max. cutting height at 90°	4.13"	
Max. cutting height at 45°	2 3/4"	
Main saw motor	7 1/2 HP	
Main blade speed	3000/ 4000/ 5000 RPM	
Scoring saw blade	120 mm	
Scoring saw blade bore	20 mm	
Scoring blade motor	1 HP	
Scoring blade speed	8000 RPM	
Blade tilting adjustment	0°~45°	