

UA 920 SEALANT



Titebond® UA 920 is a urethane acrylic elastomeric formula that does it all. It has excellent adhesion and flexibility, making it the professional's ideal choice for all interior and exterior construction, home remodeling and repair projects. It is mildew resistant, non-yellowing and reduces dirt pickup. UA 920 forms an airtight, water resistant seal on most common building materials, including concrete, fiber cement, metal, wood and vinyl siding and trim. It offers a quick grab, is easy to tool and finish and remains flexible.

Ready to Use

No mixing or primer required;
reduces labor and installation cost

Ultra Low VOC

VOC-compliant in all 50 states

Joint Movement Capability \pm 25%

Remains flexible

Weather Resistant

Produces long-lasting weather-tight seals

Paintable

May be painted with premium grade water-based
paints 2-4 hours after application

Wide Temperature Application Range

40°F – 120°F

Ideal Applications Include:

- Interior/exterior joint sealing
- General home remodeling projects

MULTI-PURPOSE

UA 920 SEALANT

SPECIFICATIONS

Complies with the following requirements:

- ASTM C920 Grade NS Class 25 and ASTM C834 Type OP for white and colors (Type C for Clear) Grade -18°C
- Federal specification TT-S-00230C Type II Class A
- ASTM C1382
- AAMA 808.3

PHYSICAL AND CHEMICAL CHARACTERISTICS

Type: Urethane/Modified Acrylic Blend (Siliconized)

Non-reactive VOC:

White, Clear & Colors:

<50 g/L (< 1.5% wt.)

Solids:

White & Colors:

69%

Clear:

61%

Tooling time: 15-20 minutes

Paintable: 2 hours

Full cure: 3-7 days*

Tack-free time: 2-3 hours

Weight per gallon:

White & Colors: 9.68 lbs.

Clear: 8.68 lbs.

Freeze thaw stability: Stable

Flashpoint: Solvent free/Not applicable

Application temperature: 40°F – 120°F

Joint movement capability: ± 25%

Storage life: 24 months in tightly closed containers between 50°F to 80°F

Coverage: 10.1 fl. oz. = 31 linear ft. at a 1/4" bead

Clean-up: Soap and water

* Cure will be affected by joint size, configuration and environmental conditions.

50 Year Limited Warranty: If not satisfied with product performance when used as directed, return container and proof of purchase to Franklin International, Inc. for replacement of product. Liability is limited to product replacement only.

APPLICATION

Titebond® UA 920 comes ready to use. Apply by professional cartridge gun. Extrude sealant into openings, gaps or holes surrounding the application. Fill joint opening to maximum capacity and repeat as necessary. Always apply sealant in a bead form. If joint depth exceeds 1/4", use backing material. To ensure neat sealant lines, mask areas adjacent to joints. Once sealant is dry to the touch and does not transfer, remove masking tape. Painting may occur 2-4 hours after application with a premium grade water-based (latex-based) paint. For other paint types, a compatibility test is recommended. It is the sole responsibility of the user to thoroughly test any proposed use with all substrates to determine project suitability.

LIMITATIONS

Do not apply if rain is expected within 12 hours. Air, sealant and surface temperature should be above 40°F. Allow at least 2 hours of drying time before painting with acrylic or elastomeric coatings. If joint depth exceeds 1/4", use backing material. Not designed for continuous submersion or use below the waterline. Do not use for aquariums. For questions, please call our Help Line at 1.800.347.4583 or visit us at Titebond.com.

NOTE: Titebond UA 920 Clear (8741) will be white during application but will dry clear within 7-14 days, depending on temperature, humidity and bead size.

CAUTION STATEMENT

WARNING: EYE, SKIN AND RESPIRATORY IRRITANT. The white and color options contains acrylic polymer, limestone, titanium dioxide and ethylene glycol. The clear option contains acrylic polymer, mineral spirits and ethylene glycol. Long term exposure to ingredients in this product can increase the risk of certain cancers. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate personal protective equipment.

FIRST AID: If swallowed, do not induce vomiting; contact physician. If eye contact occurs, flush eyes with water for 15 minutes; contact physician. Wash skin contact areas with soap and water; contact physician if irritation persists. For additional information, refer to Safety Data Sheet. **KEEP OUT OF THE REACH OF CHILDREN.**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Part Number	Size/Color	Weight	UPC	Units Per Package	Units Per Pallet
8701	10.1 oz. Cartridge/White 4 colors available	15.54 lbs.	037083087017	12	108

Franklin International

Sales: 1.800.669.4583 / Technical: 1.800.347.4583

©2019 00863-3627LN FF1022

TITEBOND.COM

