



DP-1000E Belt Driven Drill Press

Product Images



Additional Information

Stock Number	BA9-1022128
Base Dimensions (In.)	23" x 16"
Base Size (In.)	23" x 16"
Certification	CE
Chuck Size (In.)	B-16 1-16mm Keyless Chuck, MT2 to B16 Arbor, Drift Key
Column Diameter (In.)	3-1/8
Drilling Capacity Mild Steel (In.)	1"
Input Power	110 Volt
Model Number	DP-1000E
Motor (HP)	1/2 HP
Number of Spindle Speeds	5
Product Lease Price	53
Prop 65	Cancer and Reproductive Harm
Quill Diameter (In.)	2"
Range of Spindle Speeds (RPM)	250, 700, 1150, 1900, & 2900
Shipping Dimensions (L x W x H) (In.)	60x44x21
Speeds	250, 700, 1150, 1900, & 2900
Spindle Distance to Table (Max.) (In.)	5-1/2" Min. To 35-1/2" Max.
Spindle Taper	MT2
Spindle Travel (In.)	3
Swing (In.)	15-1/2"
Table Material	Cast Iron
Table Size (In.)	12-1/2" x 12-1/2"
Table T-Slot (In.)	1/2"

Table Tilt (Deg.)	360°
Weight (Lbs.)	290
Distance From Spindle To Base (In.)	47-1/2"
Shipping Weight (Lbs.)	290

