



GH-26120ZH, 4-1/8" Spindle Bore Geared Head Lathe

Product Images



Short Description

GH-26120ZH, 4-1/8" Spindle Bore Geared Head Lathe

Additional Information

Stock Number	JT9-321890
Bed Gap (In.)	8
Carriage Travel (In.)	108-1/4
Compound Slide Travel (In.)	5-1/2
Coolant Pump Motor	1/8
Diametral Pitch Threads Number	22.0000
Drive	Geared Head
Gross Weight (Lbs)	9471
Length of Gap (In.)	8
Max Tool Size (In.)	1-1/4 x 1-1/4
Model Number	GH-26120ZH
Modular Pitch Threads Number	18.0000
Modular Pitch Threads Range	0.5-7
Motor (HP)	10 HP, 230/460, 3 Ph
Motor Power (HP)	10
Motor Voltage (V.)	230/460
Net Weight (Lbs.)	9362
Number of Inch Threads	48.0000
Number of Longitudinal and Cross Feed Rates	65
Number of Metric Threads	22.0000
Number of Spindle Speeds	12
Overall Dimensions (L x W x H) (In.)	178 x 43 x 57
Overall Height (In.)	57
Prewired Voltage (V.)	176 x 43 x 57

Prop 65	Cancer and Reproductive Harm
Range of Cross Feeds (IPR)	.0040 - .0404
Range of Inch Threads (TPI)	2 - 30
Range of Longitudinal Feeds (IPR)	.0023 - .0937
Range of Metric Threads	1 - 14
Range of Spindle Speeds (RPM)	36 - 1,600
Shipping Dimensions (L x W x H) (In.)	178 x 43 x 57
Size	26 x 120
Spindle Bore (In.)	4-1/8
Spindle Mount	D1-8
Spindle Speeds	12
Spindle Taper	MT5
Spindle Taper with Sleeve	MT-5
Steady Rest Capacity (In.)	Small 25/32 - 4-29/32, Large 3-15/16 - 9-7/16
Style (Type)	Engine - Large Spindle Bore
Swing Over Bed (In.)	26
Swing Over Cross Slide (In.)	16-1/2
Swing Through Gap (In.)	34
Tailstock Spindle Travel (In.)	6
Taper in Tailstock Spindle	MT-5
Weight (Lbs.)	9362
Width of Bed (In.)	16
Wiring Remarks	Additional Fee required to rewire to 460V

