

1 Identification

- **Product identifier**
 - *Product number* CQT10
 - *Trade name:* **DRY GLAZE WHITE**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flammable Liquids 2 H225 Highly flammable liquid and vapor.
Eye Irritation 2A H319 Causes serious eye irritation.
- **Label elements**
 - *GHS label elements*
The product is classified and labeled according to the Globally Harmonized System (GHS).
 - *Hazard pictograms*




GHS02 GHS07
 - *Signal word* Danger
 - *Hazard statements*
H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
 - *Precautionary statements*
 - P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 - P241 Use explosion-proof electrical/ventilating/lighting/equipment.
 - P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 - P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P403+P235 Store in a well-ventilated place. Keep cool.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
 - *Additional information:*
2.5 % of the mixture consists of component(s) of unknown toxicity.
- **Classification system:**
 - *NFPA ratings (scale 0 - 4)*



Product number CQT10
Trade name: DRY GLAZE WHITE

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

64-17-5	ethanol	50-74.99%
	<ul style="list-style-type: none">  Flammable Liquids 2, H225  Eye Irritation 2A, H319 	
107-21-1	ethanediol	5-9.99%
	<ul style="list-style-type: none">  Acute Toxicity - Oral 4, H302 	
67-64-1	acetone	2.5-4.99%
	<ul style="list-style-type: none">  Flammable Liquids 2, H225  Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336 	
67-63-0	propan-2-ol	0.5-1%
	<ul style="list-style-type: none">  Flammable Liquids 2, H225  Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336 	
78-93-3	butanone	0.5-1%
	<ul style="list-style-type: none">  Flammable Liquids 2, H225  Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336 	

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately rinse with water.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

For symptoms and effects caused by substances, refer to Section 11.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

US

(Contd. on page 3)

Product number CQT10
Trade name: DRY GLAZE WHITE

(Contd. of page 2)

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

64-17-5	ethanol	1,800 ppm
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	30 mg/m
107-21-1	ethanediol	30 ppm
67-64-1	acetone	200 ppm
1344-28-1	aluminium oxide	15 mg/m
67-63-0	propan-2-ol	400 ppm
78-93-3	butanone	200 ppm

· PAC-2:

64-17-5	ethanol	3300* ppm
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	330 mg/m
107-21-1	ethanediol	150 ppm

(Contd. on page 4)

Product number CQT10
Trade name: DRY GLAZE WHITE

(Contd. of page 3)

67-64-1	acetone	3200* ppm
1344-28-1	aluminium oxide	170 mg/m
67-63-0	propan-2-ol	2000* ppm
78-93-3	butanone	2700* ppm

· PAC-3:

64-17-5	ethanol	15000* ppm
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2,000 mg/m
107-21-1	ethanediol	900 ppm
67-64-1	acetone	5700* ppm
1344-28-1	aluminium oxide	990 mg/m
67-63-0	propan-2-ol	12000** ppm
78-93-3	butanone	4000* ppm

7 Handling and storage

· **Handling:**· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **Conditions for safe storage, including any incompatibilities**· **Storage:**· **Requirements to be met by storerooms and receptacles:**

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

· **Information about storage in one common storage facility:** Not required.· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.· **Control parameters**· **Components with limit values that require monitoring at the workplace:****64-17-5 ethanol**

PEL Long-term value: 1900 mg/m , 1000 ppm

REL Long-term value: 1900 mg/m , 1000 ppm

TLV Short-term value: 1000 ppm

A3

(Contd. on page 5)

Product number CQT10
Trade name: DRY GLAZE WHITE

(Contd. of page 4)

107-21-1 ethanediol

TLV Short-term value: 10** mg/m , 50* ppm
 Long-term value: 25* ppm
 *vapor fraction:**inh. fraction, aerosol only, A4
 WEEL I (2)

67-64-1 acetone

PEL Long-term value: 2400 mg/m , 1000 ppm
 REL Long-term value: 590 mg/m , 250 ppm
 TLV Short-term value: 500 ppm
 Long-term value: 250 ppm
 A4, BEI

67-63-0 propan-2-ol

PEL Long-term value: 980 mg/m , 400 ppm
 REL Short-term value: 1225 mg/m , 500 ppm
 Long-term value: 980 mg/m , 400 ppm
 TLV Short-term value: 400 ppm
 Long-term value: 200 ppm
 BEI, A4

78-93-3 butanone

PEL Long-term value: 590 mg/m , 200 ppm
 REL Short-term value: 885 mg/m , 300 ppm
 Long-term value: 590 mg/m , 200 ppm
 TLV Short-term value: 300 ppm
 Long-term value: 200 ppm
 BEI

· Ingredients with biological limit values:**67-64-1 acetone**

BEI 25 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Acetone (nonspecific)

67-63-0 propan-2-ol

BEI 40 mg/L
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Acetone (background, nonspecific)

78-93-3 butanone

BEI 2 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Methyl ethyl ketone (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· Exposure controls**· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes and skin.

(Contd. on page 6)

Product number CQT10
Trade name: DRY GLAZE WHITE

(Contd. of page 5)

- **Breathing equipment:**
Use suitable respiratory protective device in case of insufficient ventilation.
- **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

- **Form:** Fluid
- **Color:** According to product specification
- **Odor:** Characteristic
- **Odor threshold:** Not determined.

· **pH-value:** Mixture is non-polar/aprotic.

· Change in condition

- **Melting point/Melting range:** Undetermined.
- **Boiling point/Boiling range:** 56 °C (132.8 °F)

· **Flash point:** -17 °C (1.4 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 410 °C (770 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

- **Lower:** 2.6 Vol %
- **Upper:** 53 Vol %

(Contd. on page 7)

Product number CQT10
Trade name: DRY GLAZE WHITE

(Contd. of page 6)

· Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)
· Density (+/- 0,03) at 20 °C (68 °F):	1.091 g/cm (9.104 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not determined.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic at 20 °C (68 °F):	40 s (ISO 4 mm)
· Oxidising properties:	N.A.
· Solvent content:	
· Water:	2.4 %
· VOC content:	60.95 % 664.9 g/l / 5.55 lb/gal
· Solids content:	33.5 %
· Other information (HAPS)	
107-21-1 ethanediol	5-9.99%
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:**
in case of possible formation of combustion:
Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral	LD50	3,763 mg/kg (mouse)
------	------	---------------------

64-17-5 ethanol

Oral	LD50	10,470 mg/kg (mouse)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	124.7 mg/l (mouse)

(Contd. on page 8)

Product number CQT10
Trade name: DRY GLAZE WHITE

(Contd. of page 7)

107-21-1 ethanediol

Oral	LD50	301 mg/kg (mouse)
	LD50.	7,712 mg/kg (mouse)
Dermal	LD50	3,501 mg/kg (mouse)
		9,530 mg/kg (rabbit)
Inhalative	LC50/6 h	2.6 ppm (mouse)

67-64-1 acetone

Oral	LD50	5,800 mg/kg (mouse)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	76 mg/l (mouse)

67-63-0 propan-2-ol

Oral	LD50	4,710 mg/kg (mouse)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	72.6 mg/l (mouse)

78-93-3 butanone

Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	21 mg/l (mouse)

· **Primary irritant effect:**

- *on the skin:* No irritant effect.
- *on the eye:* Irritating effect.

· **Sensitization:** No sensitizing effects known.· **Additional toxicological information:****Irritant**

Causes serious eye irritation.

2.5 % of the mixture consists of component(s) of unknown toxicity.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

· **Carcinogenic categories****Titanium dioxide**

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

· **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

64-17-5	ethanol	1 in alcoholic beverages
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2B - DUST

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

US

(Contd. on page 9)

Product number CQT10
Trade name: DRY GLAZE WHITE

(Contd. of page 8)

12 Ecological information

· Toxicity

· Aquatic toxicity:

64-17-5 ethanol

EC50	5,012 mg/l (daphnia) (48 h)
LC50 (96h)	15.3 mg/l (Fish)

107-21-1 ethanediol

EC50	101 mg/l (daphnia) (48h)
LC50 (96h)	72,860 mg/l (Fish)

67-64-1 acetone

EC50	8,800 mg/l (daphnia)
LC50 (96h)	5,540 mg/l (Fish)

67-63-0 propan-2-ol

EC50	1,001 mg/l (algae) (72 h)
	10,000 mg/l (daphnia) (24 h)
LC50 (96h)	9,640 mg/l (Fish)

78-93-3 butanone

EC50	2,029 mg/l (algae) (96 h)
	308 mg/l (daphnia) (48 h)
LC50 (96h)	2,993 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

· Behavior in environmental systems:

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· Uncleaned packagings:

- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

US

(Contd. on page 10)

Product number CQT10
Trade name: DRY GLAZE WHITE

(Contd. of page 9)

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA · Note 	UN1263 Check viscosity and flash point at section 9
<ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG, IATA 	Paint PAINT
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT 	 <ul style="list-style-type: none"> · Class · Label · Class · Label
<ul style="list-style-type: none"> · IMDG, IATA 	 <ul style="list-style-type: none"> · Class · Label
<ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA 	II
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	No
<ul style="list-style-type: none"> · Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category 	Warning: Flammable liquids 33 F-E, S-E B
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<ul style="list-style-type: none"> · UN "Model Regulation": 	UN 1263 PAINT, 3, II

US

(Contd. on page 11)

Product number CQT10
Trade name: DRY GLAZE WHITE

(Contd. of page 10)

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

- Various regulations
- SARA

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

107-21-1	ethanediol	5-9.99%
1344-28-1	aluminium oxide	1-2.49%
67-63-0	propan-2-ol	0.5-1%

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

107-21-1	ethanediol
----------	------------

· **Proposition 65**

· **Chemicals known to cause cancer:**

Titanium dioxide only in bound form

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	only for Dust	25-29.99%
------------	---	---------------	-----------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

107-21-1	ethanediol	5-9.99%
----------	------------	---------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I	2.5-4.99%
78-93-3	butanone	I	0.5-1%

· **TLV (Threshold Limit Value)**

64-17-5	ethanol	A3
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	A4
107-21-1	ethanediol	A4
67-64-1	acetone	A4
1344-28-1	aluminium oxide	A4
67-63-0	propan-2-ol	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	25-29.99%
------------	---	-----------

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

(Contd. on page 12)

Product number CQT10
Trade name: DRY GLAZE WHITE

(Contd. of page 11)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
 - **Date of preparation / last revision** 06/10/2022 / 106
 - **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - NIOSH: National Institute for Occupational Safety
 - OSHA: Occupational Safety & Health
 - TLV: Threshold Limit Value
 - PEL: Permissible Exposure Limit
 - REL: Recommended Exposure Limit
 - BEI: Biological Exposure Limit
 - Flammable Liquids 2: Flammable liquids . Category 2
 - Acute Toxicity - Oral 4: Acute toxicity . Category 4
 - Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A
 - Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) . Category 3
 - **Sources**
 - REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments
 - Agency ECHA web site
 - INRS Fiche Toxicologique
 - IARC International agency for research on cancer
- *** Data compared to the previous version altered.**