



1 Identification

- **Product identifier**
 - Product number HBT7A01
 - Trade name: **WB WHITE SEALER**
 - Application of the substance / the mixture For professional use
- **Details of the supplier of the safety data sheet**
 - Manufacturer/Supplier:
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
 - Information department:
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - Emergency telephone number:
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.


2 Hazard(s) identification

- **Classification of the substance or mixture**
Carc. 1A H350 May cause cancer. Route of exposure: Inhalation.
 - **Label elements**
 - GHS label elements
The product is classified and labeled according to the Globally Harmonized System (GHS).
 - Hazard pictograms
- 

GHS08
- Signal word Danger
 - Hazard-determining components of labeling:
Quartz (SiO₂)
 - Hazard statements
H350 May cause cancer. Route of exposure: Inhalation.
 - Precautionary statements
 - P201 Obtain special instructions before use.
 - P202 Do not handle until all safety precautions have been read and understood.
 - P280 Wear protective gloves/protective clothing/eye protection/face protection.
 - P308+P313 IF exposed or concerned: Get medical advice/attention.
 - P405 Store locked up.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
 - **Classification system:**
 - NFPA ratings (scale 0 - 4)
- 

Health = 0

Fire = 1

Reactivity = 0
- HMIS-ratings (scale 0 - 4)
- 

Health = *0

Fire = 1

Reactivity = 0

Product number HBT7A01
Trade name: WB WHITE SEALER

(Contd. of page 1)

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

111-76-2	2-butoxyethanol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319 Flam. Liq. 4, H227	2.5-4.99%
57-55-6	propane-1,2-diol	0.5-1%
34590-94-8	Dipropylene glycol monomethyl ether Flam. Liq. 4, H227	<1%
112-34-5	2-(2-butoxyethoxy)ethanol ⚠ Eye Irrit. 2A, H319	<0.5%
14808-60-7	Quartz (SiO ₂) ⚠ Carc. 1A, H350	≥0.1-<0.5%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

For symptoms and effects caused by substances, refer to Section 11.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:**

Do not use a jet water stream as it may scatter and spread fire.

· **Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

(Contd. on page 3)

Product number HBT7A01

Trade name: WB WHITE SEALER

(Contd. of page 2)

· **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

471-34-1	calcium carbonate	45 mg/m
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	30 mg/m
111-76-2	2-butoxyethanol	60 ppm
57-55-6	propane-1,2-diol	30 mg/m
34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
14808-60-7	Quartz (SiO ₂)	0.075 mg/m

· **PAC-2:**

471-34-1	calcium carbonate	210 mg/m
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	330 mg/m
111-76-2	2-butoxyethanol	120 ppm
57-55-6	propane-1,2-diol	1,300 mg/m
34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
14808-60-7	Quartz (SiO ₂)	33 mg/m

· **PAC-3:**

471-34-1	calcium carbonate	1,300 mg/m
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2,000 mg/m
111-76-2	2-butoxyethanol	700 ppm
57-55-6	propane-1,2-diol	7,900 mg/m
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
14808-60-7	Quartz (SiO ₂)	200 mg/m

US

(Contd. on page 4)

Product number HBT7A01
Trade name: WB WHITE SEALER

(Contd. of page 3)

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Keep respiratory protective device available.

· Information about protection against explosions and fires:

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep receptacle tightly sealed.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol

PEL Long-term value: 240 mg/m , 50 ppm
Skin

REL Long-term value: 24 mg/m , 5 ppm
Skin

TLV Long-term value: 20 ppm
BEI, A3

57-55-6 propane-1,2-diol

WEEL Long-term value: 10 mg/m

34590-94-8 Dipropylene glycol monomethyl ether

PEL Long-term value: 600 mg/m , 100 ppm
Skin

REL Short-term value: 900 mg/m , 150 ppm
Long-term value: 600 mg/m , 100 ppm
Skin

TLV Long-term value: NIC-50 ppm
(Skin)

112-34-5 2-(2-butoxyethoxy)ethanol

TLV Long-term value: 10* ppm
*Inhalable fraction and vapor

(Contd. on page 5)

Product number HBT7A01
Trade name: WB WHITE SEALER

(Contd. of page 4)

14808-60-7 Quartz (SiO₂)

PEL	Long-term value: 0.05* mg/m *resp. dust; 30mg/m ³ /SiO ₂ +2
REL	Long-term value: 0.05* mg/m *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m *respirable particulate matter, A2

Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)
-----	--

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Store protective clothing separately.

Breathing equipment:

Not required.
Short term filter device:



Suitable respiratory protective device recommended.

Filter A

Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Product number HBT7A01
Trade name: WB WHITE SEALER

(Contd. of page 5)

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:

Fluid

· Color:

According to product specification

· Odor:

Characteristic

· Odor threshold:

Not determined.

· pH-value:

Mixture is non-polar/aprotic.

· Change in condition

· Melting point/Melting range:

Undetermined.

· Boiling point/Boiling range:

100 °C (212 °F)

· Flash point:

100 °C (212 °F)

· Flammability (solid, gaseous):

Not applicable.

· Ignition temperature:

240 °C (464 °F)

· Decomposition temperature:

Not determined.

· Auto igniting:

Product is not selfigniting.

· Danger of explosion:

Product does not present an explosion hazard.

· Explosion limits:

· Lower:

1.1 Vol %

· Upper:

10.6 Vol %

· Vapor pressure at 20 °C (68 °F):

1.2 hPa (0.9 mm Hg)

· Density (+/- 0,03) at 20 °C (68 °F):

1.598 g/cm (13.335 lbs/gal)

· Relative density

Not determined.

· Vapor density

Not determined.

· Evaporation rate

Not determined.

· Solubility in / Miscibility with

· Water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water):

Not determined.

· Viscosity:

· Dynamic:

Not determined.

· Kinematic at 20 °C (68 °F):

60 s (ISO 6 mm)

· Oxidising properties:

N.A.

· Solvent content:

· Water:

31.6 %

· VOC content:

3.84 %

61.4 g/l / 0.51 lb/gal

· Solids content:

64.7 %

(Contd. on page 7)

Product number HBT7A01
Trade name: WB WHITE SEALER

(Contd. of page 6)

· **Other information (HAPS)**

112-34-5 2-(2-butoxyethoxy)ethanol

<0.5%

· **Other information**

No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	58,730 mg/kg (mouse)
Dermal	LD50	43,651 mg/kg (rab)
Inhalative	LC50/4 h	437 mg/l (mouse)

111-76-2 2-butoxyethanol

Oral	LD50	1,480 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (mouse)

57-55-6 propane-1,2-diol

Oral	LD50	20,000 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)

34590-94-8 Dipropylene glycol monomethyl ether

Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	19,020 mg/kg (rabbit)

112-34-5 2-(2-butoxyethoxy)ethanol

Oral	LD50	6,600 mg/kg (mouse)
Dermal	LD50	2,764 mg/kg (rabbit)

· **Primary irritant effect:**

- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Safety data sheet available on request.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

(Contd. on page 8)

Product number HBT7A01

Trade name: WB WHITE SEALER

(Contd. of page 7)

· **Carcinogenic categories**

Titanium dioxide

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

Quartz

No significant exposure to quartz is thought to occur during the use of products in which quartz is bound to other materials, such as resin, and for quantities present in the formula

· **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2B - DUST
14808-60-7	Quartz (SiO ₂)	1

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	≥0.1-<0.5%
------------	----------------------------	------------

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

111-76-2 2-butoxyethanol

EC50 101 mg/l (daphnia) (24 h)

LC50 (96h) 101 mg/l (Fish)

57-55-6 propane-1,2-diol

EC50 19,000 mg/l (algae) (48 h)

18,340 mg/l (daphnia) (48 h)

LC50 (96h) 40,613 mg/l (Fish)

34590-94-8 Dipropylene glycol monomethyl ether

EC50 970 mg/l (algae) (72 h)

1,919 mg/l (daphnia) (48 h)

LC50 (96h) 1,001 mg/l (Fish)

112-34-5 2-(2-butoxyethoxy)ethanol

EC50 1,001 mg/l (daphnia) (48 h)

LC50 (96h) 1,300 mg/l (Leuciscus idus melanotus)

· **Persistence and degradability** No further relevant information available.

· **Substances Easily biodegradable**

111-76-2 2-butoxyethanol .

57-55-6 propane-1,2-diol .

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

(Contd. on page 9)

Product number HBT7A01
Trade name: WB WHITE SEALER

(Contd. of page 8)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· DOT, ADN, IMDG, IATA

Not applicable

· **Note**

Check the viscosity at section 9

· **UN proper shipping name**

· DOT, ADN, IMDG, IATA

Not applicable

· **Transport hazard class(es)**

· DOT, ADR, ADN, IMDG, IATA

· **Class**

Not applicable

· **Packing group**

· DOT, IMDG, IATA

Not applicable

· **Environmental hazards:**

· **Marine pollutant:**

No

· **Special precautions for user**

Not applicable.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **UN "Model Regulation":**

Not applicable

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Various regulations**

· SARA

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

111-76-2 2-butoxyethanol

2.5-4.99%

(Contd. on page 10)

Product number HBT7A01
Trade name: WB WHITE SEALER

(Contd. of page 9)

112-34-5	2-(2-butoxyethoxy)ethanol	<0.5%
----------	---------------------------	-------

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

Titanium dioxide only in bound form

Quartz (SiO₂) only in bound form

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	only for Dust	5-9.99%
14808-60-7	Quartz (SiO ₂)	*	≥0.1-<0.5%

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

111-76-2	2-butoxyethanol	NL	2.5-4.99%
----------	-----------------	----	-----------

· **TLV (Threshold Limit Value)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	A4
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
111-76-2	2-butoxyethanol	A3
14808-60-7	Quartz (SiO ₂)	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	5-9.99%
14808-60-7	Quartz (SiO ₂)	≥0.1-<0.5%

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** IVM Chemicals Srl

· **Contact:** See emergency phone

· **Date of preparation / last revision** 08/30/2021 / 57

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/30/2021

Version number 58

Reviewed on 07/30/2021

Product number HBT7A01**Trade name: WB WHITE SEALER**

(Contd. of page 10)

ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit
 Flam. Liq. 4: Flammable liquids . Category 4
 Acute Tox. 4: Acute toxicity . Category 4
 Skin Irrit. 2: Skin corrosion/irritation . Category 2
 Eye Irrit. 2A: Serious eye damage/eye irritation . Category 2A
 Carc. 1A: Carcinogenicity . Category 1A

• **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site
 INRS Fiche Toxicologique
 IARC International agency for research on cancer

• *** Data compared to the previous version altered.**

US