

## 1 Identification

- **Product identifier**
  - Product number HKA111
  - Trade name: **CLEAR WB CONVERTER 70SH**
    - Application of the substance / the mixture For professional use
- **Details of the supplier of the safety data sheet**
  - **Manufacturer/Supplier:**  
IVM Chemicals srl  
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
  - **Information department:**  
Environmental Health and safety office  
hseoffice@ivmchemicals.com
  - **Emergency telephone number:**  
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

## 2 Hazard(s) identification


- **Classification of the substance or mixture**  
The product is not classified, according to the Globally Harmonized System (GHS).

- **Label elements**

- GHS label elements Not applicable
  - Hazard pictograms Not applicable
  - Signal word Not applicable
  - Hazard statements Not applicable

- **Classification system:**

- NFPA ratings (scale 0 - 4)



Health = 0  
 Fire = 0  
 Reactivity = 0

- HMIS-ratings (scale 0 - 4)




HEALTH 0 Health = 0  
 FIRE 0 Fire = 0  
 REACTIVITY 0 Reactivity = 0

## 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- Description: Mixture: consisting of the following components.

- **Dangerous components:**

111-76-2	2-butoxyethanol  Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319 Flam. Liq. 4, H227	1-2.49%
34590-94-8	Dipropylene glycol monomethyl ether Flam. Liq. 4, H227	1-<5%

(Contd. on page 2)

**Product number HKA111**

**Trade name: CLEAR WB CONVERTER 70SH**

		(Contd. of page 1)
112-34-5	2-(2-butoxyethoxy)ethanol ⚠ Eye Irrit. 2A, H319	<0.5%
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) ⚠ Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330 ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318 ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) ⚠ Skin Sens. 1A, H317	≥0.00025-<0.0015%

#### 4 First-aid measures

· **Description of first aid measures**

· **General information:**

No special measures required.  
personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

For symptoms and effects caused by substances, refer to Section 11.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

#### 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

· **For safety reasons unsuitable extinguishing agents:**

Do not use a jet water stream as it may scatter and spread fire.

· **Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· **Protective equipment:** No special measures required.

#### 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures** Not required.

· **Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)

**Product number HKA111****Trade name: CLEAR WB CONVERTER 70SH**

(Contd. of page 2)

Dispose contaminated material as waste according to Section 13.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

· PAC-1:		
111-76-2	2-butoxyethanol	60 ppm
34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
25322-69-4	Propane-1,2-diol, propoxylated	30 mg/m
108-01-0	2-dimethylaminoethanol	3.7 ppm
68439-49-6	c16-18 alcohols ethoxylated	3.8 mg/m
68439-49-6	c16-18 alcohols ethoxylated	3.8 mg/m
124-68-5	2-amino-2-methylpropanol	17 mg/m
· PAC-2:		
111-76-2	2-butoxyethanol	120 ppm
34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
25322-69-4	Propane-1,2-diol, propoxylated	330 mg/m
108-01-0	2-dimethylaminoethanol	40 ppm
68439-49-6	c16-18 alcohols ethoxylated	42 mg/m
68439-49-6	c16-18 alcohols ethoxylated	42 mg/m
124-68-5	2-amino-2-methylpropanol	190 mg/m
· PAC-3:		
111-76-2	2-butoxyethanol	700 ppm
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
25322-69-4	Propane-1,2-diol, propoxylated	2,000 mg/m
108-01-0	2-dimethylaminoethanol	72 ppm
68439-49-6	c16-18 alcohols ethoxylated	250 mg/m
68439-49-6	c16-18 alcohols ethoxylated	250 mg/m
124-68-5	2-amino-2-methylpropanol	570 mg/m

## 7 Handling and storage

- **Handling:**

- *Precautions for safe handling* No special measures required.

- *Information about protection against explosions and fires:* No special measures required.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- *Requirements to be met by storerooms and receptacles:*

- Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

- In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- Take on temperature greater than 5 ° C

(Contd. on page 4)

**Product number HKA111**
**Trade name: CLEAR WB CONVERTER 70SH**

(Contd. of page 3)

- *Information about storage in one common storage facility: Not required.*
- *Further information about storage conditions: None.*
- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
  - *Components with limit values that require monitoring at the workplace:*  
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
 At this time, the remaining constituent has no known exposure limits.

### 111-76-2 2-butoxyethanol

PEL	Long-term value: 240 mg/m , 50 ppm Skin
REL	Long-term value: 24 mg/m , 5 ppm Skin
TLV	Long-term value: 20 ppm BEI, A3

### 34590-94-8 Dipropylene glycol monomethyl ether

PEL	Long-term value: 600 mg/m , 100 ppm Skin
REL	Short-term value: 900 mg/m , 150 ppm Long-term value: 600 mg/m , 100 ppm Skin
TLV	Long-term value: NIC-50 ppm (Skin)

### 112-34-5 2-(2-butoxyethoxy)ethanol

TLV	Long-term value: 10* ppm *Inhalable fraction and vapor
-----	---

#### · *Ingredients with biological limit values:*

### 111-76-2 2-butoxyethanol

BEI	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)
-----	--

- *Additional information:* The lists that were valid during the creation were used as basis.

#### · **Exposure controls**

##### · *Personal protective equipment:*

- **General protective and hygienic measures:**  
*The usual precautionary measures for handling chemicals should be followed.*
- **Breathing equipment:** Not required.
- **Protection of hands:**  
*Due to missing tests no recommendation to the glove material can be given for the product.  
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  
 The glove material has to be impermeable and resistant to the product .*
- **Material of gloves**  
*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be*

(Contd. on page 5)

**Product number HKA111****Trade name: CLEAR WB CONVERTER 70SH**

(Contd. of page 4)

calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Goggles recommended during refilling.

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · General Information

##### · Appearance:

- **Form:** Fluid
- **Color:** According to product specification
- **Odor:** Characteristic
- **Odor threshold:** Not determined.

· **pH-value:** Mixture is non-polar/aprotic.

#### · Change in condition

- **Melting point/Melting range:** Undetermined.
- **Boiling point/Boiling range:** 100 °C (212 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 240 °C (464 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

#### · Explosion limits:

- **Lower:** 1.1 Vol %
- **Upper:** 14 Vol %

· **Vapor pressure at 20 °C (68 °F):** 1.2 hPa (0.9 mm Hg)

· **Density (+/- 0,03) at 20 °C (68 °F):** 1.027 g/cm (8.57 lbs/gal)

- **Relative density** Not determined.
- **Vapor density** Not determined.
- **Evaporation rate** Not determined.

#### · Solubility in / Miscibility with

· **Water:** Fully miscible.

· **Partition coefficient (n-octanol/water):** Not determined.

#### · Viscosity:

- **Dynamic:** Not determined.
- **Kinematic at 20 °C (68 °F):** 45 s (ISO 6 mm)
- **Oxidising properties:** N.A.

#### · Solvent content:

- **Water:** 59.9 %
- **VOC content:** 5.46 %  
56.1 g/l / 0.47 lb/gal

· **Solids content:** 34.5 %

(Contd. on page 6)

**Product number HKA111**
**Trade name: CLEAR WB CONVERTER 70SH**

(Contd. of page 5)

**· Other information (HAPS)**

112-34-5	2-(2-butoxyethoxy)ethanol	<0.5%
----------	---------------------------	-------

· Other information	No further relevant information available.
---------------------	--

## 10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
  - **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

**· Information on toxicological effects**
**· Acute toxicity:**
**· LD/LC50 values that are relevant for classification:**
**ATE (Acute Toxicity Estimate)**

Oral	LD50	33,387 mg/kg
Dermal	LD50	47,826 mg/kg (rab)
Inhalative	LC50/4 h	478 mg/l (mouse)

**111-76-2 2-butoxyethanol**

Oral	LD50	1,480 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (mouse)

**34590-94-8 Dipropylene glycol monomethyl ether**

Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	19,020 mg/kg (rabbit)

**112-34-5 2-(2-butoxyethoxy)ethanol**

Oral	LD50	6,600 mg/kg (mouse)
Dermal	LD50	2,764 mg/kg (rabbit)

**108-01-0 2-dimethylaminoethanol**

Oral	LD50	1,183 mg/kg (mouse)
Dermal	LD50	1,219 mg/kg (rabbit)
Inhalative	LC50/4 h	6.1 mg/l (mouse)

**· Primary irritant effect:**

- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.

**· Sensitization:** No sensitizing effects known.

**· Additional toxicological information:**

The product is not subject to classification according to internally approved calculation methods for preparations:

(Contd. on page 7)

**Product number HKA111****Trade name: CLEAR WB CONVERTER 70SH**

(Contd. of page 6)

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

Contains a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1), 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Safety data sheet available on request.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

**111-76-2 2-butoxyethanol**

EC50 101 mg/l (daphnia) (24 h)

LC50 (96h) 101 mg/l (Fish)

**34590-94-8 Dipropylene glycol monomethyl ether**

EC50 970 mg/l (algae) (72 h)

1,919 mg/l (daphnia) (48 h)

LC50 (96h) 1,001 mg/l (Fish)

**112-34-5 2-(2-butoxyethoxy)ethanol**

EC50 1,001 mg/l (daphnia) (48 h)

LC50 (96h) 1,300 mg/l (Leuciscus idus melanotus)

**108-01-0 2-dimethylaminoethanol**

EC50 66.1 mg/l (algae) (72 h)

98.4 mg/l (daphnia) (48 h)

**55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)**

EC50 0.027 mg/l (algae) (72 h)

0.16 mg/l (daphnia) (48 h)

LC50 (96h) 0.19 mg/l (Fish)

- **Persistence and degradability** No further relevant information available.

- **Substances Easily biodegradable**

111-76-2 2-butoxyethanol .

34590-94-8 Dipropylene glycol monomethyl ether .

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

(Contd. on page 8)

**Product number HKA111**  
**Trade name: CLEAR WB CONVERTER 70SH**

(Contd. of page 7)

- **Additional ecological information:**
  - **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
  - **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
  - **Recommendation:**  
Hand over to hazardous waste disposers.  
Dispose of contents and container in accordance with local state and federal regulations.
- **Uncleaned packagings:**
  - **Recommendation:** Disposal must be made according to official regulations.
  - **Recommended cleansing agent:** Water, if necessary with cleansing agents.

### 14 Transport information

- **UN-Number**
  - DOT, ADN, IMDG, IATA Not applicable
  - Note Check the viscosity at section 9
- **UN proper shipping name**
  - DOT, ADN, IMDG, IATA Not applicable
- **Transport hazard class(es)**
  - DOT, ADR, ADN, IMDG, IATA
  - Class Not applicable
- **Packing group**
  - DOT, IMDG, IATA Not applicable
- **Environmental hazards:**
  - Marine pollutant: No
- **Special precautions for user** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **UN "Model Regulation":** Not applicable

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
  - Various regulations
    - SARA
  - Section 355 (extremely hazardous substances):  
None of the ingredients is listed.

(Contd. on page 9)



**Product number HKA111****Trade name: CLEAR WB CONVERTER 70SH**

(Contd. of page 8)

· **Section 313 (Specific toxic chemical listings) :**

111-76-2	2-butoxyethanol	1-2.49%
112-34-5	2-(2-butoxyethoxy)ethanol	<0.5%

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

111-76-2	2-butoxyethanol	NL	1-2.49%
----------	-----------------	----	---------

· **TLV (Threshold Limit Value)**

111-76-2	2-butoxyethanol	A3
----------	-----------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
- **Date of preparation / last revision** 08/30/2021 / 7

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 BEI: Biological Exposure Limit  
 Flam. Liq. 4: Flammable liquids . Category 4  
 Acute Tox. 3: Acute toxicity . Category 3

(Contd. on page 10)

**Product number HKA111****Trade name: CLEAR WB CONVERTER 70SH**

(Contd. of page 9)

*Acute Tox. 4: Acute toxicity . Category 4**Acute Tox. 2: Acute toxicity . Category 2**Skin Corr. 1B: Skin corrosion/irritation . Category 1B**Skin Irrit. 2: Skin corrosion/irritation . Category 2**Eye Dam. 1: Serious eye damage/eye irritation . Category 1**Eye Irrit. 2A: Serious eye damage/eye irritation . Category 2A**Skin Sens. 1A: Skin sensitisation . Category 1A**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard . Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard . Category 1***• Sources****REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments**

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

**• \* Data compared to the previous version altered.**

US