

1 Identification

- **Product identifier**
 - *Product number* KGA2
 - *Trade name:* **PU CLEAR CONV 50SH**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Flam. Liq. 2 H225 Highly flammable liquid and vapor.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Carc. 1A H350 May cause cancer.
Repr. 2 H361 Suspected of damaging fertility or the unborn child.
STOT SE 3 H336 May cause drowsiness or dizziness.
STOT RE 2 H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.

- **Label elements**

- *GHS label elements*

The product is classified and labeled according to the Globally Harmonized System (GHS).

 - *Hazard pictograms*



GHS02 GHS07 GHS08

- *Signal word* Danger
- *Hazard-determining components of labeling:*

isobutyl acetate
xylene
ethylbenzene
toluene
- *Hazard statements*

H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H350 May cause cancer.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.

(Contd. on page 2)

Product number KGA2
Trade name: PU CLEAR CONV 50SH

(Contd. of page 1)

Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



HMIS-ratings (scale 0 - 4)



3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture: consisting of the following components.

Dangerous components:

110-19-0	isobutyl acetate Flam. Liq. 2, H225 STOT SE 3, H336	25-29.99%
1330-20-7	xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	10-12.49%
123-86-4	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	2.5-4.99%
100-41-4	ethylbenzene Flam. Liq. 2, H225 Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H332 Aquatic Chronic 3, H412	2.5-4.99%
141-78-6	ethyl acetate Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336	2.5-4.99%
108-88-3	toluene Flam. Liq. 2, H225 Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H336 Aquatic Chronic 3, H412	1-2.49%

(Contd. on page 3)

Product number KGA2
Trade name: PU CLEAR CONV 50SH

		(Contd. of page 2)
64-17-5	ethanol ⚠ Flam. Liq. 2, H225 ☠ Carc. 1A, H350 ⚠ Eye Irrit. 2A, H319	0.5-1%
78-93-3	butanone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	0.5-1%
108-10-1	4-methylpentan-2-one ⚠ Flam. Liq. 2, H225 ☠ Carc. 2, H351 ⚠ Acute Tox. 4, H332; Eye Irrit. 2A, H319; STOT SE 3, H335	0.5-1%
108-94-1	cyclohexanone ⚠ Flam. Liq. 3, H226 ☠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	≥0.5-<1%
67-63-0	propan-2-ol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	<0.5%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary).

Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Do not induce vomiting; immediately call for medical help.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

(Contd. on page 4)

Product number KGA2
Trade name: PU CLEAR CONV 50SH

(Contd. of page 3)

- **For safety reasons unsuitable extinguishing agents:**
 Do not use a jet water stream as it may scatter and spread fire.
- **Special hazards arising from the substance or mixture**
 During heating or in case of fire poisonous gases are produced.
 In case of fire, the following can be released:
 Nitrogen oxides (NO_x)
 Carbon monoxide (CO)
- **Advice for firefighters**
 Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.
- **Protective equipment:**
 Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
 Ensure adequate ventilation
 Keep away from ignition sources
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to Section 13.
 Ensure adequate ventilation.
- **Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:		
110-19-0	isobutyl acetate	450 ppm
1330-20-7	xylene	130 ppm
123-86-4	n-butyl acetate	5 ppm
100-41-4	ethylbenzene	33 ppm
141-78-6	ethyl acetate	1,200 ppm
108-88-3	toluene	67 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m
64-17-5	ethanol	1,800 ppm
78-93-3	butanone	200 ppm
108-10-1	4-methylpentan-2-one	75 ppm
108-94-1	cyclohexanone	60 ppm
9002-88-4	Polyethylene low density	16 mg/m
67-63-0	propan-2-ol	400 ppm
· PAC-2:		
110-19-0	isobutyl acetate	1300* ppm
1330-20-7	xylene	920* ppm

(Contd. on page 5)

Product number KGA2
Trade name: PU CLEAR CONV 50SH

(Contd. of page 4)		
123-86-4	n-butyl acetate	200 ppm
100-41-4	ethylbenzene	1100* ppm
141-78-6	ethyl acetate	1,700 ppm
108-88-3	toluene	560 ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m
64-17-5	ethanol	3300* ppm
78-93-3	butanone	2700* ppm
108-10-1	4-methylpentan-2-one	500 ppm
108-94-1	cyclohexanone	830 ppm
9002-88-4	Polyethylene low density	170 mg/m
67-63-0	propan-2-ol	2000* ppm

· **PAC-3:**

110-19-0	isobutyl acetate	7500** ppm
1330-20-7	xylene	2500* ppm
123-86-4	n-butyl acetate	3000* ppm
100-41-4	ethylbenzene	1800* ppm
141-78-6	ethyl acetate	10000** ppm
108-88-3	toluene	3700* ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m
64-17-5	ethanol	15000* ppm
78-93-3	butanone	4000* ppm
108-10-1	4-methylpentan-2-one	3000* ppm
108-94-1	cyclohexanone	5000* ppm
9002-88-4	Polyethylene low density	1,000 mg/m
67-63-0	propan-2-ol	12000** ppm

7 Handling and storage

· **Handling:**

- **Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
 Use explosion-proof apparatus / fittings and spark-proof tools.

- **Information about protection against explosions and fires:**

- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

- Store in a cool, well-ventilated area, away from heat and sources of ignition
- Provide solvent resistant, sealed floor.
- Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.
- In cases where there is no reported expiration date, it means that the product must be used

(Contd. on page 6)

Product number KGA2
Trade name: PU CLEAR CONV 50SH

(Contd. of page 5)

- within 8 months.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

110-19-0 isobutyl acetate

PEL	Long-term value: 700 mg/m , 150 ppm
REL	Long-term value: 700 mg/m , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

1330-20-7 xylene

PEL	Long-term value: 435 mg/m , 100 ppm
REL	Short-term value: 655 mg/m , 150 ppm Long-term value: 435 mg/m , 100 ppm
TLV	Short-term value: (150) ppm Long-term value: (100) NIC-20 ppm BEI, A4

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m , 150 ppm
REL	Short-term value: 950 mg/m , 200 ppm Long-term value: 710 mg/m , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m , 100 ppm
REL	Short-term value: 545 mg/m , 125 ppm Long-term value: 435 mg/m , 100 ppm
TLV	Long-term value: 20 NIC-20 ppm BEI, A3, NIC: OTO, BEI, A3

141-78-6 ethyl acetate

PEL	Long-term value: 1400 mg/m , 400 ppm
REL	Long-term value: 1400 mg/m , 400 ppm
TLV	Long-term value: 400 ppm

108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m , 150 ppm Long-term value: 375 mg/m , 100 ppm

(Contd. on page 7)

Product number KGA2
Trade name: PU CLEAR CONV 50SH

(Contd. of page 6)

TLV Long-term value: 20 ppm
 BEI, OTO, A4

64-17-5 ethanol

PEL Long-term value: 1900 mg/m , 1000 ppm
 REL Long-term value: 1900 mg/m , 1000 ppm
 TLV Short-term value: 1000 ppm
 A3

78-93-3 butanone

PEL Long-term value: 590 mg/m , 200 ppm
 REL Short-term value: 885 mg/m , 300 ppm
 Long-term value: 590 mg/m , 200 ppm
 TLV Short-term value: 300 ppm
 Long-term value: 200 ppm
 BEI

108-10-1 4-methylpentan-2-one

PEL Long-term value: 410 mg/m , 100 ppm
 REL Short-term value: 300 mg/m , 75 ppm
 Long-term value: 205 mg/m , 50 ppm
 TLV Short-term value: 75 ppm
 Long-term value: 20 ppm
 BEI, A3

108-94-1 cyclohexanone

PEL Long-term value: 200 mg/m , 50 ppm
 REL Long-term value: 100 mg/m , 25 ppm
 Skin
 TLV Short-term value: 50 ppm
 Long-term value: 20 ppm
 Skin, BEI, A3

67-63-0 propan-2-ol

PEL Long-term value: 980 mg/m , 400 ppm
 REL Short-term value: 1225 mg/m , 500 ppm
 Long-term value: 980 mg/m , 400 ppm
 TLV Short-term value: 400 ppm
 Long-term value: 200 ppm
 BEI, A4

Ingredients with biological limit values:**1330-20-7 xylene**

BEI 1.5 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

(Contd. on page 8)

Product number KGA2
Trade name: PU CLEAR CONV 50SH

(Contd. of page 7)

108-88-3 toluene

BEI 0.02 mg/L
 Medium: blood
 Time: prior to last shift of workweek
 Parameter: Toluene

0.03 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Toluene

0.3 mg/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: o-Cresol with hydrolysis (background)

78-93-3 butanone

BEI 2 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Methyl ethyl ketone (nonspecific)

108-10-1 4-methylpentan-2-one

BEI 1 mg/L
 Medium: urine
 Time: end of shift
 Parameter: MIBK

108-94-1 cyclohexanone

BEI 80 mg/L
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: 1,2-Cyclohexanediol (with hydrolysis, nonspecific, nonquantitative)

8 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Cyclohexanol (with hydrolysis, nonspecific, nonquantitative)

67-63-0 propan-2-ol

BEI 40 mg/L
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Acetone (background, nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.
- Pregnant women should strictly avoid inhalation or skin contact.

(Contd. on page 9)

US

Product number KGA2
Trade name: PU CLEAR CONV 50SH

(Contd. of page 8)

- **Breathing equipment:**
Short term filter device:



Suitable respiratory protective device recommended.

Filter A

- **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· **Form:**

Fluid

· **Color:**

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Mixture is non-polar/aprotic.

· Change in condition

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

77 °C (170.6 °F)

· **Flash point:**

-4 °C (24.8 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

>370 °C (>698 °F)

· **Decomposition temperature:**

Not determined.

(Contd. on page 10)

Product number KGA2
Trade name: PU CLEAR CONV 50SH

(Contd. of page 9)

· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· Explosion limits:		
· Lower:	1 Vol %	
· Upper:	11.5 Vol %	
· Vapor pressure at 20 °C (68 °F):	97 hPa (72.8 mm Hg)	
· Density (+/- 0,03) at 20 °C (68 °F):	0.975 g/cm (8.136 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water):	Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	101 s (ISO 6 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· Water:	0.0 %	
· VOC content:	53.81 %	
	524.7 g/l / 4.38 lb/gal	
· Solids content:	46.2 %	
· Other information (HAPS)		
1330-20-7	xylene	10-12.49%
100-41-4	ethylbenzene	2.5-4.99%
108-88-3	toluene	1-2.49%
108-10-1	4-methylpentan-2-one	0.5-1%
· Other information	No further relevant information available.	

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
 No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
 Reacts with oxidizing agents.
 Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:**
 in case of possible formation of combustion:
 Carbon monoxide and carbon dioxide

US

(Contd. on page 11)

Product number KGA2
Trade name: PU CLEAR CONV 50SH

(Contd. of page 10)

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Dermal	LD50	9,096 mg/kg (rabbit)
Inhalative	LC50/4 h	79.1 mg/l (mouse)

110-19-0 isobutyl acetate

Oral	LD50	13,400 mg/kg (mouse)
Dermal	LD50	17,401 mg/kg (rabbit)
Inhalative	LC50/4 h	31 mg/l (mouse)

1330-20-7 xylene

Oral	LD50.	3,523 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rabbit) (ATE value)
	LD50.	12,126 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (mouse) (ATE value)
	LC50/4h.	27.571 mg/l (mouse)

123-86-4 n-butyl acetate

Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.1 mg/l (mouse)

100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (mouse)
Dermal	LD50	15,486 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/l (mouse)

141-78-6 ethyl acetate

Oral	LD50	4,934 mg/kg (rabbit)
Dermal	LD50	20,001 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (mouse)
	LC0	22.6 ppm (mouse)

108-88-3 toluene

Oral	LD50	5,000 mg/kg (mouse)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	25.7 mg/l (mouse)

64-17-5 ethanol

Oral	LD50	10,470 mg/kg (mouse)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	124.7 mg/l (mouse)

78-93-3 butanone

Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	21 mg/l (mouse)

(Contd. on page 12)

Product number KGA2
Trade name: PU CLEAR CONV 50SH

(Contd. of page 11)

108-10-1 4-methylpentan-2-one

Oral	LD50	2,080 mg/kg (mouse)
Dermal	LD50	16,000 mg/kg (rab)
Inhalative	LC50/4 h	16.6 mg/l (mouse)

108-94-1 cyclohexanone

Oral	LD50	1,890 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rabbit)
Inhalative	LC50/4 h	6.3 mg/l (mouse)

67-63-0 propan-2-ol

Oral	LD50	4,710 mg/kg (mouse)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	72.6 mg/l (mouse)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

Irritant

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.

Contains Fatty acids, tallow, oleylamine compounds. May produce an allergic reaction.

- **Carcinogenic categories**

Ethylbenzene

From IARC MONOGRAPHS VOLUME 77/2000

Human carcinogenicity data

Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

Evaluation

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

- **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

100-41-4	ethylbenzene	2B
64-17-5	ethanol	1
108-10-1	4-methylpentan-2-one	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

US

(Contd. on page 13)

Product number KGA2
Trade name: PU CLEAR CONV 50SH

(Contd. of page 12)

12 Ecological information

· Toxicity

· Aquatic toxicity:	
110-19-0 isobutyl acetate	
EC50	370 mg/l (algae) (72 h) 25 mg/l (daphnia)
LC50 (96h)	17 mg/l (Fish)
1330-20-7 xylene	
EC50	2.2 mg/l (algae) (72h)
LC50 48h	1 mg/l (daphnia)
LC50 (96h)	2.6 mg/l (Fish)
123-86-4 n-butyl acetate	
EC50	397 mg/l (algae) (72 h) 44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)
100-41-4 ethylbenzene	
EC50	438 mg/l (algae) (72h) 1.8 mg/l (daphnia) (48 h)
LC50 (96h)	12.1 mg/l (Fish)
141-78-6 ethyl acetate	
EC50	165 mg/l (daphnia) (48 h)
LC50 (96h)	230 mg/l (Fish)
108-88-3 toluene	
EC50	134 mg/l (algae) (96 h) 3.78 mg/l (daphnia) (48 h)
LC50 (96h)	5.5 mg/l (Fish)
64-17-5 ethanol	
EC50	5,012 mg/l (daphnia) (48 h)
LC50 (96h)	15.3 mg/l (Fish)
78-93-3 butanone	
EC50	2,029 mg/l (algae) (96 h) 308 mg/l (daphnia) (48 h)
LC50 (96h)	2,993 mg/l (Fish)
108-10-1 4-methylpentan-2-one	
EC50	201 mg/l (daphnia) (48 h)
LC50 (96h)	180 mg/l (Fish)
108-94-1 cyclohexanone	
EC50	101 mg/l (algae) (72 h) 101 mg/l (daphnia)
LC50 (96h)	527 mg/l (Fish)
67-63-0 propan-2-ol	
EC50	1,001 mg/l (algae) (72 h) 10,000 mg/l (daphnia) (24 h)

(Contd. on page 14)

Product number KGA2
Trade name: PU CLEAR CONV 50SH

(Contd. of page 13)

LC50 (96h)	9,640 mg/l (Fish)
------------	-------------------

- **Persistence and degradability** No further relevant information available.

- **Substances Easily biodegradable**

110-19-0	isobutyl acetate	.
1330-20-7	xylene	.
123-86-4	n-butyl acetate	.
100-41-4	ethylbenzene	.
141-78-6	ethyl acetate	.
108-88-3	toluene	.
64-17-5	ethanol	.
78-93-3	butanone	.
108-10-1	4-methylpentan-2-one	.

- **Behavior in environmental systems:**
 - **Bioaccumulative potential** No further relevant information available.
 - **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
 - **General notes:**
 - Water hazard class 2 (Self-assessment): hazardous for water
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 - **Recommendation:**
 - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 - Hand over to hazardous waste disposers.
 - Dispose of contents and container in accordance with local state and federal regulations.
- **Uncleaned packagings:**
 - **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|----------------------------------|----------------------------------|
| · UN-Number | |
| · DOT, IMDG, IATA | UN1263 |
| · Note | Check the viscosity at section 9 |
| · UN proper shipping name | |
| · DOT | Paint |
| · IMDG, IATA | PAINT |

(Contd. on page 15)

US

Product number KGA2
Trade name: PU CLEAR CONV 50SH

(Contd. of page 14)

· **Transport hazard class(es)**

· **DOT**



- **Class** 3 Flammable liquids
- **Label** 3
- **Class** 3 Flammable liquids
- **Label** 3

· **IMDG, IATA**



- **Class** 3 Flammable liquids
- **Label** 3

· **Packing group**

- **DOT, IMDG, IATA** III

· **Environmental hazards:**

- **Marine pollutant:** No

· **Special precautions for user**

Warning: Flammable liquids

- **Hazard identification number (Kemler code):** -
- **EMS Number:** F-E, S-E
- **Stowage Category** A

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **IMDG**

- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 1263 PAINT, 3, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

· **Various regulations**

- SARA

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

(Contd. on page 16)

Product number KGA2
Trade name: PU CLEAR CONV 50SH

(Contd. of page 15)

· **Section 313 (Specific toxic chemical listings) :**

1330-20-7	xylene	10-12.49%
100-41-4	ethylbenzene	2.5-4.99%
108-88-3	toluene	1-2.49%
108-10-1	4-methylpentan-2-one	0.5-1%
67-63-0	propan-2-ol	<0.5%

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene
108-88-3	toluene
108-10-1	4-methylpentan-2-one

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene	*	2.5-4.99%
108-10-1	4-methylpentan-2-one	*	0.5-1%

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene	1-2.49%
64-17-5	ethanol	0.5-1%
108-10-1	4-methylpentan-2-one	0.5-1%

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I	10-12.49%
100-41-4	ethylbenzene	D	2.5-4.99%
108-88-3	toluene	II	1-2.49%
78-93-3	butanone	I	0.5-1%
108-10-1	4-methylpentan-2-one	I	0.5-1%

· **TLV (Threshold Limit Value)**

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
108-88-3	toluene	A4
64-17-5	ethanol	A3
108-94-1	cyclohexanone	A3
67-63-0	propan-2-ol	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

(Contd. on page 17)

Product number KGA2**Trade name: PU CLEAR CONV 50SH**

(Contd. of page 16)

- **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl

- **Contact:** See emergency phone

- **Date of preparation / last revision** 08/30/2021 / 75

- **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids . Category 2

Flam. Liq. 3: Flammable liquids . Category 3

Acute Tox. 4: Acute toxicity . Category 4

Skin Irrit. 2: Skin corrosion/irritation . Category 2

Eye Dam. 1: Serious eye damage/eye irritation . Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation . Category 2A

Carc. 1A: Carcinogenicity . Category 1A

Carc. 2: Carcinogenicity . Category 2

Repr. 2: Reproductive toxicity . Category 2

STOT SE 3: Specific target organ toxicity (single exposure) . Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) . Category 2

Asp. Tox. 1: Aspiration hazard . Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

- **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

- *** Data compared to the previous version altered.**