

1 Identification

- **Product identifier**
 - *Product number* KGA406
 - *Trade name:* **NEUTRAL ACRYLIC SELF S 30SH**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**
 - Flam. Liq. 2 H225 Highly flammable liquid and vapor.
 - Eye Irrit. 2A H319 Causes serious eye irritation.
 - Skin Sens. 1 H317 May cause an allergic skin reaction.
 - Carc. 2 H351 Suspected of causing cancer.
 - Repr. 2 H361 Suspected of damaging fertility or the unborn child.
 - STOT SE 3 H336 May cause drowsiness or dizziness.
 - STOT RE 2 H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

n-butyl acetate
xylene
toluene
ethylbenzene
methyl methacrylate

· Hazard statements

H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.

(Contd. on page 2)

Product number KGA406

Trade name: NEUTRAL ACRYLIC SELF S 30SH

(Contd. of page 1)

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 2

Fire = 3

Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = *2

Fire = 3

Reactivity = 0

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture: consisting of the following components.









Dangerous components:

123-86-4	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	50-74.99%
110-19-0	isobutyl acetate Flam. Liq. 2, H225 STOT SE 3, H336	5-9.99%
1330-20-7	xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	5-9.99%
67-63-0	propan-2-ol Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336	1-2.49%
108-88-3	toluene Flam. Liq. 2, H225 Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H336 Aquatic Chronic 3, H412	1-2.49%
78-83-1	2-methylpropan-1-ol Flam. Liq. 3, H226 Eye Dam. 1, H318 Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-2.49%

(Contd. on page 3)

Product number KGA406

Trade name: NEUTRAL ACRYLIC SELF S 30SH

		(Contd. of page 2)
100-41-4	ethylbenzene  Flam. Liq. 2, H225  Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304  Acute Tox. 4, H332 Aquatic Chronic 3, H412	1-2.49%
80-62-6	methyl methacrylate  Flam. Liq. 2, H225  Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-<0.5%
131-56-6	2,4-dihydroxybenzophenone  Repr. 2, H361  Aquatic Chronic 2, H411  Eye Irrit. 2A, H319 Aquatic Acute 2, H401	≥0.1-<0.25%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Do not induce vomiting; immediately call for medical help.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed

Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

(Contd. on page 4)

Product number KGA406
Trade name: NEUTRAL ACRYLIC SELF S 30SH

(Contd. of page 3)

· **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

123-86-4	n-butyl acetate	5 ppm
110-19-0	isobutyl acetate	450 ppm
1330-20-7	xylene	130 ppm
67-63-0	propan-2-ol	400 ppm
108-88-3	toluene	67 ppm
78-83-1	2-methylpropan-1-ol	150 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m
100-41-4	ethylbenzene	33 ppm
9002-88-4	Polyethylene low density	16 mg/m
80-62-6	methyl methacrylate	17 ppm

· **PAC-2:**

123-86-4	n-butyl acetate	200 ppm
110-19-0	isobutyl acetate	1300* ppm
1330-20-7	xylene	920* ppm
67-63-0	propan-2-ol	2000* ppm
108-88-3	toluene	560 ppm
78-83-1	2-methylpropan-1-ol	1,300 ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m
100-41-4	ethylbenzene	1100* ppm
9002-88-4	Polyethylene low density	170 mg/m
80-62-6	methyl methacrylate	120 ppm

· **PAC-3:**

123-86-4	n-butyl acetate	3000* ppm
110-19-0	isobutyl acetate	7500** ppm
1330-20-7	xylene	2500* ppm

(Contd. on page 5)

Product number KGA406

Trade name: NEUTRAL ACRYLIC SELF S 30SH

(Contd. of page 4)

67-63-0	propan-2-ol	12000** ppm
108-88-3	toluene	3700* ppm
78-83-1	2-methylpropan-1-ol	8000* ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m
100-41-4	ethylbenzene	1800* ppm
9002-88-4	Polyethylene low density	1,000 mg/m
80-62-6	methyl methacrylate	570 ppm

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Protect against electrostatic charges.

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

(Contd. on page 6)

Product number KGA406

Trade name: NEUTRAL ACRYLIC SELF S 30SH

(Contd. of page 5)

REL Short-term value: 950 mg/m , 200 ppm
Long-term value: 710 mg/m , 150 ppm

TLV Short-term value: 150 ppm
Long-term value: 50 ppm

110-19-0 isobutyl acetate

PEL Long-term value: 700 mg/m , 150 ppm

REL Long-term value: 700 mg/m , 150 ppm

TLV Short-term value: 150 ppm
Long-term value: 50 ppm

1330-20-7 xylene

PEL Long-term value: 435 mg/m , 100 ppm

REL Short-term value: 655 mg/m , 150 ppm
Long-term value: 435 mg/m , 100 ppm

TLV Short-term value: (150) ppm
Long-term value: (100) NIC-20 ppm
BEI, A4

67-63-0 propan-2-ol

PEL Long-term value: 980 mg/m , 400 ppm

REL Short-term value: 1225 mg/m , 500 ppm
Long-term value: 980 mg/m , 400 ppm

TLV Short-term value: 400 ppm
Long-term value: 200 ppm
BEI, A4

108-88-3 toluene

PEL Long-term value: 200 ppm
Ceiling limit value: 300; 500* ppm
*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m , 150 ppm
Long-term value: 375 mg/m , 100 ppm

TLV Long-term value: 20 ppm
BEI, OTO, A4

78-83-1 2-methylpropan-1-ol

PEL Long-term value: 300 mg/m , 100 ppm

REL Long-term value: 150 mg/m , 50 ppm

TLV Long-term value: 50 ppm

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m , 100 ppm

REL Short-term value: 545 mg/m , 125 ppm
Long-term value: 435 mg/m , 100 ppm

TLV Long-term value: 20 NIC-20 ppm
BEI, A3, NIC: OTO, BEI, A3

80-62-6 methyl methacrylate

PEL Long-term value: 410 mg/m , 100 ppm

REL Long-term value: 410 mg/m , 100 ppm

TLV Short-term value: 100 ppm
Long-term value: 50 ppm
DSEN, A4

(Contd. on page 7)

Product number KGA406

Trade name: NEUTRAL ACRYLIC SELF S 30SH

(Contd. of page 6)

Ingredients with biological limit values:

1330-20-7 xylene

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

67-63-0 propan-2-ol

BEI 40 mg/L
Medium: urine
Time: end of shift at end of workweek
Parameter: Acetone (background, nonspecific)

108-88-3 toluene

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine
Medium: urine
Time: end of shift at end of workweek
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.
- Pregnant women should strictly avoid inhalation or skin contact.

Breathing equipment:

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

(Contd. on page 8)

Product number KGA406

Trade name: NEUTRAL ACRYLIC SELF S 30SH

(Contd. of page 7)

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:**

Fluid

· **Color:**

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Mixture is non-polar/aprotic.

· **Change in condition**

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

82 °C (179.6 °F)

· **Flash point:**

4 °C (39.2 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

>370 °C (>698 °F)

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not selfigniting.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

· **Lower:**

1 Vol %

· **Upper:**

12 Vol %

· **Vapor pressure at 20 °C (68 °F):**

43 hPa (32.3 mm Hg)

(Contd. on page 9)

Product number KGA406

Trade name: NEUTRAL ACRYLIC SELF S 30SH

(Contd. of page 8)

· Density (+/- 0,03) at 20 °C (68 °F):		1 g/cm (8.345 lbs/gal)
· Relative density		Not determined.
· Vapor density		Not determined.
· Evaporation rate		Not determined.
· Solubility in / Miscibility with		
· Water:		Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water): Not determined.		
· Viscosity:		
· Dynamic:		Not determined.
· Kinematic at 20 °C (68 °F):		55 s (ISO 6 mm)
· Oxidising properties:		N.A.
· Solvent content:		
· VOC content:		73.67 % 736.7 g/l / 6.15 lb/gal
· Solids content:		26.3 %
· Other information (HAPS)		
1330-20-7	xylene	5-9.99%
108-88-3	toluene	1-2.49%
100-41-4	ethylbenzene	1-2.49%
80-62-6	methyl methacrylate	≥0.1-<0.5%
· Other information		No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Reacts with oxidizing agents.
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)		
Dermal	LD50	19,342 mg/kg (rabbit)
Inhalative	LC50/4 h	168 mg/l (mouse)
123-86-4 n-butyl acetate		
Oral	LD50	10,760 mg/kg (mouse)

(Contd. on page 10)

Product number KGA406

Trade name: NEUTRAL ACRYLIC SELF S 30SH

(Contd. of page 9)

Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.1 mg/l (mouse)
110-19-0 isobutyl acetate		
Oral	LD50	13,400 mg/kg (mouse)
Dermal	LD50	17,401 mg/kg (rabbit)
Inhalative	LC50/4 h	31 mg/l (mouse)
1330-20-7 xylene		
Oral	LD50.	3,523 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rabbit) (ATE value)
	LD50.	12,126 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (mouse) (ATE value)
	LC50/4h.	27.571 mg/l (mouse)
67-63-0 propan-2-ol		
Oral	LD50	4,710 mg/kg (mouse)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	72.6 mg/l (mouse)
108-88-3 toluene		
Oral	LD50	5,000 mg/kg (mouse)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	25.7 mg/l (mouse)
78-83-1 2-methylpropan-1-ol		
Oral	LD50	2,460 mg/kg (mouse)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4h.	19.2 mg/l (mouse)
100-41-4 ethylbenzene		
Oral	LD50	3,500 mg/kg (mouse)
Dermal	LD50	15,486 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/l (mouse)
80-62-6 methyl methacrylate		
Oral	LD50	7,872 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	78 mg/l (mouse)
131-56-6 2,4-dihydroxybenzophenone		
Oral	LD50	7,220 mg/kg (mouse)

· **Primary irritant effect:**

· *on the skin:* No irritant effect.

· *on the eye:* Irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

· **Additional toxicological information:**

Irritant

Causes serious eye irritation.

May cause drowsiness or dizziness.

Contains methyl methacrylate. May produce an allergic reaction.

· **Carcinogenic categories**

Ethylbenzene

From IARC MONOGRAPHS VOLUME 77/2000

Human carcinogenicity data

(Contd. on page 11)

Product number KGA406

Trade name: NEUTRAL ACRYLIC SELF S 30SH

(Contd. of page 10)

Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

Evaluation

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

· **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

100-41-4 ethylbenzene

2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

123-86-4 n-butyl acetate

EC50 397 mg/l (algae) (72 h)
44 mg/l (daphnia) (48 h)
LC50 (96h) 18 mg/l (Fish)

110-19-0 isobutyl acetate

EC50 370 mg/l (algae) (72 h)
25 mg/l (daphnia)
LC50 (96h) 17 mg/l (Fish)

1330-20-7 xylene

EC50 2.2 mg/l (algae) (72h)
LC50 48h 1 mg/l (daphnia)
LC50 (96h) 2.6 mg/l (Fish)

67-63-0 propan-2-ol

EC50 1,001 mg/l (algae) (72 h)
10,000 mg/l (daphnia) (24 h)
LC50 (96h) 9,640 mg/l (Fish)

108-88-3 toluene

EC50 134 mg/l (algae) (96 h)
3.78 mg/l (daphnia) (48 h)
LC50 (96h) 5.5 mg/l (Fish)

78-83-1 2-methylpropan-1-ol

EC50 1,799 mg/l (algae) (72 h)
1,100 mg/l (daphnia) (48 h)
LC50 (96h) 1,430 mg/l (Fish)

(Contd. on page 12)

Product number KGA406

Trade name: NEUTRAL ACRYLIC SELF S 30SH

(Contd. of page 11)

100-41-4 ethylbenzene

EC50	438 mg/l (algae) (72h)
	1.8 mg/l (daphnia) (48 h)
LC50 (96h)	12.1 mg/l (Fish)

80-62-6 methyl methacrylate

EC50	170 mg/l (algae) (72 h)
LC50 (96h)	191 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

· **Substances Easily biodegradable**

123-86-4	n-butyl acetate	.
110-19-0	isobutyl acetate	.
1330-20-7	xylene	.
67-63-0	propan-2-ol	.
108-88-3	toluene	.
78-83-1	2-methylpropan-1-ol	.
100-41-4	ethylbenzene	.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· DOT, IMDG, IATA

UN1263

· **Note**

Check the viscosity at section 9

· **UN proper shipping name**

· DOT

Paint

· IMDG, IATA

PAINT

(Contd. on page 13)

Printing date 08/30/2021

Version number 1

Reviewed on 08/30/2021

Product number KGA406

Trade name: NEUTRAL ACRYLIC SELF S 30SH

(Contd. of page 12)

· **Transport hazard class(es)**

· **DOT**



- **Class** 3 Flammable liquids
- **Label** 3
- **Class** 3 Flammable liquids
- **Label** 3

· **IMDG, IATA**



- **Class** 3 Flammable liquids
- **Label** 3

· **Packing group**

- **DOT, IMDG, IATA** III

· **Environmental hazards:**

- **Marine pollutant:** No

· **Special precautions for user**

Warning: Flammable liquids

- **Hazard identification number (Kemler code):** -
- **EMS Number:** F-E, S-E
- **Stowage Category** A

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **IMDG**

- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 1263 PAINT, 3, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Various regulations**
- **SARA**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

(Contd. on page 14)

Product number KGA406
Trade name: NEUTRAL ACRYLIC SELF S 30SH

(Contd. of page 13)

· **Section 313 (Specific toxic chemical listings) :**

1330-20-7	xylene	5-9.99%
67-63-0	propan-2-ol	1-2.49%
108-88-3	toluene	1-2.49%
100-41-4	ethylbenzene	1-2.49%
80-62-6	methyl methacrylate	≥0.1-<0.5%
110-82-7	cyclohexane	<0.025%

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

1330-20-7	xylene
108-88-3	toluene
100-41-4	ethylbenzene
80-62-6	methyl methacrylate

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene	*	1-2.49%
----------	--------------	---	---------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene	1-2.49%
----------	---------	---------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I	5-9.99%
108-88-3	toluene	II	1-2.49%
100-41-4	ethylbenzene	D	1-2.49%
80-62-6	methyl methacrylate	E, NL	≥0.1-<0.5%
110-82-7	cyclohexane	I	<0.025%

· **TLV (Threshold Limit Value)**

1330-20-7	xylene	A4
67-63-0	propan-2-ol	A4
108-88-3	toluene	A4
100-41-4	ethylbenzene	A3
80-62-6	methyl methacrylate	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 15)

Product number KGA406**Trade name: NEUTRAL ACRYLIC SELF S 30SH**

(Contd. of page 14)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** IVM Chemicals Srl

· **Contact:** See emergency phone

· **Date of preparation / last revision** 08/30/2021 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids . Category 2

Flam. Liq. 3: Flammable liquids . Category 3

Acute Tox. 4: Acute toxicity . Category 4

Skin Irrit. 2: Skin corrosion/irritation . Category 2

Eye Dam. 1: Serious eye damage/eye irritation . Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation . Category 2A

Skin Sens. 1: Skin sensitisation . Category 1

Carc. 2: Carcinogenicity . Category 2

Repr. 2: Reproductive toxicity . Category 2

STOT SE 3: Specific target organ toxicity (single exposure) . Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) . Category 2

Asp. Tox. 1: Aspiration hazard . Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard . Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard . Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

· **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

· *** Data compared to the previous version altered.**