

1 Identification

- **Product identifier**
 - Product number LBR1
 - Trade name: **NEUTRAL PU PRIMER**
 - Application of the substance / the mixture For professional use
- **Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
 - **Information department:**
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - **Emergency telephone number:**
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Flam. Liq. 2	H225 Highly flammable liquid and vapor.
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2A	H319 Causes serious eye irritation.
Carc. 1A	H350 May cause cancer.
Repr. 2	H361 Suspected of damaging fertility or the unborn child.
STOT SE 3	H335 May cause respiratory irritation.
STOT RE 2	H373 May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

xylene
ethylbenzene
4-hydroxy-4-methylpentan-2-one
Quartz (SiO₂)

- **Hazard statements**

H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H350 May cause cancer.
H361 Suspected of damaging fertility or the unborn child.
H335 May cause respiratory irritation.
H373 May cause damage to the hearing organs through prolonged or repeated exposure.
Route of exposure: Oral, Inhalation.
H412 Harmful to aquatic life with long lasting effects.

Product number LBR1
Trade name: NEUTRAL PU PRIMER

(Contd. of page 1)

Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



3 Composition/information on ingredients

Chemical characterization: Mixtures


· Description: Mixture: consisting of the following components.

Dangerous components:

1330-20-7	xylene <ul style="list-style-type: none"> ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335 Aquatic Chronic 3, H412 	20-24.99%
100-41-4	ethylbenzene <ul style="list-style-type: none"> ⚠ Flam. Liq. 2, H225 ⚠ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H332 Aquatic Chronic 3, H412 	5-9.99%
110-19-0	isobutyl acetate <ul style="list-style-type: none"> ⚠ Flam. Liq. 2, H225 ⚠ STOT SE 3, H336 	5-9.99%
123-42-2	4-hydroxy-4-methylpentan-2-one <ul style="list-style-type: none"> ⚠ Repr. 2, H361 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H335 Flam. Liq. 4, H227 	2.5-4.99%
141-78-6	ethyl acetate <ul style="list-style-type: none"> ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336 	0.5-1%
67-56-1	methanol <ul style="list-style-type: none"> ⚠ Flam. Liq. 2, H225 ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 ⚠ STOT SE 1, H370 	<0.5%

(Contd. on page 3)

Product number LBR1
Trade name: NEUTRAL PU PRIMER

14808-60-7 Quartz (SiO₂)
 Carc. 1A, H350

(Contd. of page 2)

≥0.1-<0.5%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary).

Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Do not induce vomiting; immediately call for medical help.

· Information for doctor:

- Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by substances, refer to Section 11.

- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

US

(Contd. on page 4)

Product number LBR1
Trade name: NEUTRAL PU PRIMER

(Contd. of page 3)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-1:**

1330-20-7	xylene	130 ppm
471-34-1	calcium carbonate	45 mg/m
100-41-4	ethylbenzene	33 ppm
110-19-0	isobutyl acetate	450 ppm
123-42-2	4-hydroxy-4-methylpentan-2-one	150 ppm
141-78-6	ethyl acetate	1,200 ppm
67-56-1	methanol	530 ppm
14808-60-7	Quartz (SiO ₂)	0.075 mg/m

- **PAC-2:**

1330-20-7	xylene	920* ppm
471-34-1	calcium carbonate	210 mg/m
100-41-4	ethylbenzene	1100* ppm
110-19-0	isobutyl acetate	1300* ppm
123-42-2	4-hydroxy-4-methylpentan-2-one	350 ppm
141-78-6	ethyl acetate	1,700 ppm
67-56-1	methanol	2,100 ppm
14808-60-7	Quartz (SiO ₂)	33 mg/m

- **PAC-3:**

1330-20-7	xylene	2500* ppm
471-34-1	calcium carbonate	1,300 mg/m
100-41-4	ethylbenzene	1800* ppm
110-19-0	isobutyl acetate	7500** ppm
123-42-2	4-hydroxy-4-methylpentan-2-one	2100* ppm
141-78-6	ethyl acetate	10000** ppm
67-56-1	methanol	7200* ppm

(Contd. on page 5)

Product number LBR1
Trade name: NEUTRAL PU PRIMER

(Contd. of page 4)

14808-60-7 Quartz (SiO₂)

200 mg/m

7 Handling and storage

· Handling:

· Precautions for safe handling

- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Prevent formation of aerosols.
- Protect against electrostatic charges.
- Keep respiratory protective device available.
- Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

- Store in a cool, well-ventilated area, away from heat and sources of ignition
- Provide solvent resistant, sealed floor.
- Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.
- In cases where there is no reported expiration date, it means that the product must be used within 8 months.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions:

- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

1330-20-7 xylene

PEL	Long-term value: 435 mg/m , 100 ppm
REL	Short-term value: 655 mg/m , 150 ppm Long-term value: 435 mg/m , 100 ppm
TLV	Short-term value: (150) ppm Long-term value: (100) NIC-20 ppm BEI, A4

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m , 100 ppm
REL	Short-term value: 545 mg/m , 125 ppm Long-term value: 435 mg/m , 100 ppm
TLV	Long-term value: 20 NIC-20 ppm BEI, A3, NIC: OTO, BEI, A3

(Contd. on page 6)

Product number LBR1
Trade name: NEUTRAL PU PRIMER

(Contd. of page 5)

110-19-0 isobutyl acetate

PEL Long-term value: 700 mg/m³ , 150 ppm
 REL Long-term value: 700 mg/m³ , 150 ppm
 TLV Short-term value: 150 ppm
 Long-term value: 50 ppm

123-42-2 4-hydroxy-4-methylpentan-2-one

PEL Long-term value: 240 mg/m³ , 50 ppm
 REL Long-term value: 240 mg/m³ , 50 ppm
 TLV Long-term value: 50 ppm

141-78-6 ethyl acetate

PEL Long-term value: 1400 mg/m³ , 400 ppm
 REL Long-term value: 1400 mg/m³ , 400 ppm
 TLV Long-term value: 400 ppm

67-56-1 methanol

PEL Long-term value: 260 mg/m³ , 200 ppm
 REL Short-term value: 325 mg/m³ , 250 ppm
 Long-term value: 260 mg/m³ , 200 ppm
 Skin
 TLV Short-term value: 250 ppm
 Long-term value: 200 ppm
 Skin; BEI

14808-60-7 Quartz (SiO₂)

PEL Long-term value: 0.05* mg/m³
 *resp. dust; 30mg/m³/%SiO₂+2
 REL Long-term value: 0.05* mg/m³
 *respirable dust; See Pocket Guide App. A
 TLV Long-term value: 0.025* mg/m³
 *respirable particulate matter, A2

· Ingredients with biological limit values:**1330-20-7 xylene**

BEI 1.5 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

67-56-1 methanol

BEI 15 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Methanol (background, nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 7)

Product number LBR1
Trade name: NEUTRAL PU PRIMER

(Contd. of page 6)

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.
- Pregnant women should strictly avoid inhalation or skin contact.

· Breathing equipment:

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

- Form:** Fluid
- Color:** According to product specification
- Odor:** Characteristic
- Odor threshold:** Not determined.

· pH-value: Mixture is non-polar/aprotic.

· Change in condition

· Melting point/Melting range: Undetermined.

(Contd. on page 8)

Product number LBR1
Trade name: NEUTRAL PU PRIMER

(Contd. of page 7)

· Boiling point/Boiling range:	77 °C (170.6 °F)	
· Flash point:	-4 °C (24.8 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	460 °C (860 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· Explosion limits:		
· Lower:	1 Vol %	
· Upper:	30 Vol %	
· Vapor pressure at 20 °C (68 °F):	97 hPa (72.8 mm Hg)	
· Density (+/- 0,03) at 20 °C (68 °F):	1.186 g/cm (9.897 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water):	Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	38 s (ISO 6 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· VOC content:	40.33 % 478.3 g/l / 3.99 lb/gal	
· Solids content:	59.7 %	
· Other information (HAPS)		
1330-20-7	xylene	20-24.99%
100-41-4	ethylbenzene	5-9.99%
67-56-1	methanol	<0.5%
· Other information	No further relevant information available.	

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions**
Reacts with oxidizing agents.
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents

(Contd. on page 9)

US

Product number LBR1
Trade name: NEUTRAL PU PRIMER

(Contd. of page 8)

- **Hazardous decomposition products:**
 in case of possible formation of combustion:
 Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
 · **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	791,244 mg/kg
Dermal	LD50	4,489 mg/kg (rabbit)
Inhalative	LC50/4 h	38.9 mg/l (mouse)

1330-20-7 xylene

Oral	LD50.	3,523 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rabbit) (ATE value)
	LD50.	12,126 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (mouse) (ATE value)
	LC50/4h.	27.571 mg/l (mouse)

100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (mouse)
Dermal	LD50	15,486 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/l (mouse)

110-19-0 isobutyl acetate

Oral	LD50	13,400 mg/kg (mouse)
Dermal	LD50	17,401 mg/kg (rabbit)
Inhalative	LC50/4 h	31 mg/l (mouse)

123-42-2 4-hydroxy-4-methylpentan-2-one

Oral	LD50	3,002 mg/kg (mouse)
Dermal	LD50	13,630 mg/kg (rab)

141-78-6 ethyl acetate

Oral	LD50	4,934 mg/kg (rabbit)
Dermal	LD50	20,001 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (mouse)
	LC0	22.6 ppm (mouse)

67-56-1 methanol

Oral	LD50	1,187 mg/kg (mouse)
Dermal	LD50	17,000 mg/kg (rabbit)
Inhalative	LC50/4 h	128.2 mg/l (mouse)

- **Primary irritant effect:**
 - **on the skin:**
 Irritant to skin and mucous membranes.
 Causes skin irritation.
 - **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.

(Contd. on page 10)

Product number LBR1
Trade name: NEUTRAL PU PRIMER

(Contd. of page 9)

· **Additional toxicological information:**

Irritant

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause respiratory irritation.

May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

· **Carcinogenic categories**

Quartz

No significant exposure to quartz is thought to occur during the use of products in which quartz is bound to other materials, such as resin, and for quantities present in the formula

Ethylbenzene

From IARC MONOGRAPHS VOLUME 77/2000

Human carcinogenicity data

Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

Evaluation

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

· **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

100-41-4	ethylbenzene	2B
14808-60-7	Quartz (SiO ₂)	1

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	≥0.1-<0.5%
------------	----------------------------	------------

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.		
------------------------------------	--	--

12 Ecological information

· **Toxicity** Harmful to aquatic life with long lasting effects.

· **Aquatic toxicity:**

1330-20-7 xylene

EC50 2.2 mg/l (algae) (72h)

LC50 48h 1 mg/l (daphnia)

LC50 (96h) 2.6 mg/l (Fish)

100-41-4 ethylbenzene

EC50 438 mg/l (algae) (72h)

1.8 mg/l (daphnia) (48 h)

LC50 (96h) 12.1 mg/l (Fish)

110-19-0 isobutyl acetate

EC50 370 mg/l (algae) (72 h)

25 mg/l (daphnia)

LC50 (96h) 17 mg/l (Fish)

(Contd. on page 11)

Product number LBR1
Trade name: NEUTRAL PU PRIMER

(Contd. of page 10)

123-42-2 4-hydroxy-4-methylpentan-2-one

EC50	1,001 mg/l (algae) (72 h)
	1,000 mg/l (daphnia) (48 h)
LC50 (96h)	101 mg/l (Fish)

141-78-6 ethyl acetate

EC50	165 mg/l (daphnia) (48 h)
LC50 (96h)	230 mg/l (Fish)

67-56-1 methanol

EC50	8,000 mg/l (algae) (72 h)
	24,500 mg/l (daphnia) (48 h)
LC50 (96h)	15,400 mg/l (Fish)

- **Persistence and degradability** No further relevant information available.

· **Substances Easily biodegradable**

1330-20-7	xylene	.
100-41-4	ethylbenzene	.
110-19-0	isobutyl acetate	.
123-42-2	4-hydroxy-4-methylpentan-2-one	.
141-78-6	ethyl acetate	.

- **Behavior in environmental systems:**
 - *Bioaccumulative potential* No further relevant information available.
 - *Mobility in soil* No further relevant information available.
- **Ecotoxicological effects:**
 - *Remark:* Harmful to fish
- **Additional ecological information:**
 - *General notes:*
 - Water hazard class 2 (Self-assessment): hazardous for water
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.
 - Harmful to aquatic organisms
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 - *Recommendation:*
 - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 - Hand over to hazardous waste disposers.
 - Dispose of contents and container in accordance with local state and federal regulations.
- **Uncleaned packagings:**
 - *Recommendation:* Disposal must be made according to official regulations.



14 Transport information

- **UN-Number**
- *DOT, IMDG, IATA* UN1263

(Contd. on page 12)

Product number LBR1
Trade name: NEUTRAL PU PRIMER

(Contd. of page 11)

· <i>Note</i>	Check the viscosity at section 9
· UN proper shipping name	
· <i>DOT</i>	Paint
· <i>IMDG, IATA</i>	PAINT
· Transport hazard class(es)	
· <i>DOT</i>	
	
· <i>Class</i>	3 Flammable liquids
· <i>Label</i>	3
· <i>Class</i>	3 Flammable liquids
· <i>Label</i>	3
· <i>IMDG, IATA</i>	
	
· <i>Class</i>	3 Flammable liquids
· <i>Label</i>	3
· Packing group	
· <i>DOT, IMDG, IATA</i>	II
· Environmental hazards:	
· <i>Marine pollutant:</i>	No
· Special precautions for user	Warning: Flammable liquids
· <i>Hazard identification number (Kemler code):</i>	33
· <i>EMS Number:</i>	F-E, S-E
· <i>Stowage Category</i>	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· <i>IMDG</i>	
· <i>Limited quantities (LQ)</i>	5L
· <i>Excepted quantities (EQ)</i>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
Requirements of Federal Register

(Contd. on page 13)

Product number LBR1
Trade name: NEUTRAL PU PRIMER

(Contd. of page 12)

- Various regulations
- SARA

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

1330-20-7	xylene	20-24.99%
100-41-4	ethylbenzene	5-9.99%
67-56-1	methanol	<0.5%

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene
67-56-1	methanol

· **Proposition 65**

- **Chemicals known to cause cancer:**
 Quartz (SiO₂) only in bound form

100-41-4	ethylbenzene	*	5-9.99%
14808-60-7	Quartz (SiO ₂)	*	≥0.1-<0.5%

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

67-56-1	methanol	<0.5%
---------	----------	-------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I	20-24.99%
100-41-4	ethylbenzene	D	5-9.99%

· **TLV (Threshold Limit Value)**

1330-20-7	xylene	A4
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
100-41-4	ethylbenzene	A3
14808-60-7	Quartz (SiO ₂)	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7	Quartz (SiO ₂)	≥0.1-<0.5%
------------	----------------------------	------------

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 14)

Product number LBR1
Trade name: NEUTRAL PU PRIMER

(Contd. of page 13)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
 - **Date of preparation / last revision** 08/30/2021 / 70
 - **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - NIOSH: National Institute for Occupational Safety
 - OSHA: Occupational Safety & Health
 - TLV: Threshold Limit Value
 - PEL: Permissible Exposure Limit
 - REL: Recommended Exposure Limit
 - BEI: Biological Exposure Limit
 - Flam. Liq. 2: Flammable liquids . Category 2
 - Flam. Liq. 3: Flammable liquids . Category 3
 - Flam. Liq. 4: Flammable liquids . Category 4
 - Acute Tox. 3: Acute toxicity . Category 3
 - Acute Tox. 4: Acute toxicity . Category 4
 - Skin Irrit. 2: Skin corrosion/irritation . Category 2
 - Eye Irrit. 2A: Serious eye damage/eye irritation . Category 2A
 - Carc. 1A: Carcinogenicity . Category 1A
 - Carc. 2: Carcinogenicity . Category 2
 - Repr. 2: Reproductive toxicity . Category 2
 - STOT SE 1: Specific target organ toxicity (single exposure) . Category 1
 - STOT SE 3: Specific target organ toxicity (single exposure) . Category 3
 - STOT RE 2: Specific target organ toxicity (repeated exposure) . Category 2
 - Asp. Tox. 1: Aspiration hazard . Category 1
 - Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3
- **Sources**
 - REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments
 - Agency ECHA web site
 - INRS Fiche Toxicologique
 - IARC International agency for research on cancer
- *** Data compared to the previous version altered.**