

Printing date 10/17/2013

Reviewed on 10/17/2013

#### 1 Identification

- · Product identifier
  - · Product number LBR102
  - · Trade name: FONDO PU BIANCO HQ
    - · Application of the substance / the mixture Professional uses
- · Details of the supplier of the safety data sheet
  - · Manufacturer/Supplier:

IVM Chemicals srl

Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/MSDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

#### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

- · Label elements
  - · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

· Precautionary statements

P303+P361+P353 IF ON SKIN: Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · Classification system:
  - · NFPA ratings (scale 0 4)



Health = 0 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0Fire = 3

Reactivity = 0



Printing date 10/17/2013 Reviewed on 10/17/2013

**Product number LBR102** 

Trade name: FONDO PU BIANCO HQ

(Contd. of page 1)

## 3 Composition/information on ingredients

#### · Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangerou	· Dangerous components:			
110-19-0	isobutyl acetate  Flam. Liq. 2, H225	10-12.49%		
108-65-6	2-methoxy-1-methylethyl acetate  Flam. Liq. 3, H226	5-9.99%		
1330-20-7	xylene Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2.5-4.99%		
141-78-6	ethyl acetate  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336	2.5-4.99%		
100-41-4	ethylbenzene  Flam. Liq. 2, H225 Carc. 2, H351 Acute Tox. 4, H332	0.5-<1%		
64742-95-6	Solvent naphtha (petroleum), light arom.  Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336	0.1-<0.5%		

### 4 First-aid measures

- · Description of first aid measures
  - · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
  - · Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.
  - · For safety reasons unsuitable extinguishing agents:
    - Do not use a jet water stream as it may scatter and spread fire.
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 3)



Printing date 10/17/2013 Reviewed on 10/17/2013

**Product number LBR102** 

Trade name: FONDO PU BIANCO HQ

(Contd. of page 2)

#### · Advice for firefighters

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
  - · Storage:
    - · Requirements to be met by storerooms and receptacles:

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

#### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)



Printing date 10/17/2013 Reviewed on 10/17/2013

**Product number LBR102** 

Trade name: FONDO PU BIANCO HQ

(Contd. of page 3)

· Control parameters					
· Compa	· Components with limit values that require monitoring at the workplace:				
110-19-0	110-19-0 isobutyl acetate				
PEL ()	Long-term value: 700 mg/m³, 150 ppm				
REL ()	Long-term value: 700 mg/m³, 150 ppm				
TLV ()	Long-term value: 713 mg/m³, 150 ppm				
108-65-6	2-methoxy-1-methylethyl acetate				
WEEL ()	Long-term value: 50 ppm				
1330-20-	7 xylene				
PEL ()	Long-term value: 435 mg/m³, 100 ppm				
REL ()	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm				
TLV ()	Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI				
141-78-6	ethyl acetate				
PEL ()	Long-term value: 1400 mg/m³, 400 ppm				
REL ()	Long-term value: 1400 mg/m³, 400 ppm				
TLV ()	Long-term value: 1440 mg/m³, 400 ppm				
	Ingredients with biological limit values:				
1330-20-	7 xylene				
BEI () 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids					

· Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

- · Personal protective equipment:
  - · General protective and hygienic measures: Wash hands before breaks and at the end of work.
  - · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)



Printing date 10/17/2013 Reviewed on 10/17/2013

**Product number LBR102** 

Trade name: FONDO PU BIANCO HQ

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

Physical and chemical prope	
Information on basic physical and	chemical properties
· General Information	
· Appearance: · Form:	Fluid
· Color:	According to product specification
· Odor:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	77 °C (171 °F)
· Flash point:	-4 °C (25 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	315 °C (599 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosivair/vapor mixtures are possible.
· Explosion limits:	
· Lower:	1.1 Vol %
· Upper:	11.5 Vol %
· Vapor pressure at 20 °C (68 °F):	97 hPa (73 mm Hg)
· Density at 20 °C (68 °F):	1.351 g/cm³ (11.274 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic at 20 °C (68 °F):	101 s (ISO 6 mm)
· Solvent content:	
· Water:	0.1 %
· VOC content:	28.2 %
	381.6 g/l / 3.18 lb/gl
· Solids content:	71.7 %



Printing date 10/17/2013 Reviewed on 10/17/2013

**Product number LBR102** 

Trade name: FONDO PU BIANCO HQ

(Contd. of page 5)

· Other information (HAPS)		
1330-20-7	xylene	2,5-4,99%
100-41-4	ethylbenzene	0.5-<1%

### 10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
  - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions

Reacts with oxidizing agents.

Vapours may form explosive mixtures with air

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products:

in case of possible formation of combustion:

Carbon monoxide and carbon dioxide

### 11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

110-19-0 isobutyl acetate			
Oral	LD50	13400 mg/kg (rat/szczur/mouse/souris/Maus/ratón)	
Dermal	LD50	17401 mg/kg (Con)	
Inhalative	LC50/4 h	31 mg/l (rat/szczur/mouse/souris/Maus/ratón)	
108-65-6	2-methoxy	r-1-methylethyl acetate	
Oral	LD50	8532 mg/kg (rat/szczur/mouse/souris/Maus/ratón)	
Inhalative	LC50/4 h	35.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)	
1330-20-7	xylene		
Oral	LD50	4300 mg/kg (rat/szczur/mouse/souris/Maus/ratón)	
Dermal	LD50	2000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)	
141-78-6	ethyl aceta	ate	
Oral	LD50	4934 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)	
Dermal	LD50	>20000 mg/kg (Con)	
Inhalative	LC0/6 h	>22.5 ppm (mouse)	
	LC50/4 h	1600 mg/l (rat/szczur/mouse/souris/Maus/ratón)	
100-41-4	ethylbenze	ene	
Oral	LD50	3500 mg/kg (rat/szczur/mouse/souris/Maus/ratón)	
Dermal	LD50	17800 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)	
64742-95-	6 Solvent	naphtha (petroleum), light arom.	
Oral	LD50	>6800 mg/kg (rat/szczur/mouse/souris/Maus/ratón)	
Dermal	LD50	>3400 mg/kg (rab)	



Printing date 10/17/2013 Reviewed on 10/17/2013

**Product number LBR102** 

Trade name: FONDO PU BIANCO HQ

(Contd. of page 6)

Inhalative LC50/4 h >10.2 mg/l (rat/szczur/mouse/souris/Maus/ratón)

- · Primary irritant effect:
  - · on the skin: No irritant effect.
  - on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
  - · Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
100-41-4	ethylbenzene	2B
1330-20-7	xylene	3
· N	TP (National Toxicology Program)	
None of the ingredients, in dangerous form, is listed.		

### 12 Ecological information

- · Toxicity
  - · Aquatic toxicity:

#### 110-19-0 isobutyl acetate

EC50 25 mg/l (daphnia)

1330-20-7 xylene

EC50 1 mg/l (daphnia)

141-78-6 ethyl acetate

EC50 164 mg/l (daphnia)

- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
  - $\cdot \textit{Additional ecological information:}$ 
    - · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

· Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
  - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
  - Recommendation: Disposal must be made according to official regulations.

HEA



Printing date 10/17/2013 Reviewed on 10/17/2013

**Product number LBR102** 

Trade name: FONDO PU BIANCO HQ

(Contd. of page 7)

### 14 Transport information · UN-Number · DOT, IMDG, IATA UN1263 · UN proper shipping name $\cdot DOT$ Paint **PAINT** · IMDG, IATA · Transport hazard class(es) $\cdot DOT$ · Class 3 Flammable liquids. · Label 3 Flammable liquids · Class · Label · IMDG, IATA 3 Flammable liquids. · Class · Label Packing group · DOT, IMDG, IATA III· Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Flammable liquids · Danger code (Kemler): 33 F-E,S-E · EMS Number: · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · UN "Model Regulation": UN1263, Paint, special provision 640H, 3, III

### 15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients, in dangerous form, is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

100-41-4 ethylbenzene

(Contd. on page 9)



Printing date 10/17/2013 Reviewed on 10/17/2013

**Product number LBR102** 

Trade name: FONDO PU BIANCO HQ

(Contd. of page 8)

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
  - · Chemicals known to cause cancer:

100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients, in dangerous form, is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients, in dangerous form, is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients, in dangerous form, is listed.

· Carcinogenic categories

· I	EPA (Environmental Protection Agency)		
1330-20-7	xylene	1	
100-41-4	ethylbenzene	D	
· TLV (Threshold Limit Value established by ACGIH)			

· TLV (Threshold Limit Value established by ACGIH)			
100-41-4	ethylbenzene	A3	
1330-20-7	xylene	A4	

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients, in dangerous form, is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients, in dangerous form, is listed.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: IVM Chemicals Srl
- · Contact: See emergency phone
  - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

· Sources

Directive 1999/45/EC and following amendments

Directive 67/548/EEC and following amendments and adjustments

Agency ECHA web site

INRS Fiche Toxicologique

(Contd. on page 10)

Page 10/10



## **Safety Data Sheet** 29 CFR Parts 1910 1915 1926

Printing date 10/17/2013 Reviewed on 10/17/2013

**Product number LBR102** 

Trade name: FONDO PU BIANCO HQ

(Contd. of page 9)

IARC International agency for research on cancer

\* Data compared to the previous version altered.

USA -