SIO4 ADHESIVE CLEANER/REMOVER







As part of our Cleaners range, S104 is suitable for use on most surfaces.

PRODUCT DESCRIPTION

TensorGrip S104 is an adhesive cleaner/remover designed to safely and powerfully remove adhesives and other tough substances.

ADVANTAGES

- Exceptional cleaning/degreasing power
- Non-corrosive
- Compatible with most plastics
- Biodegradable

- Cleans hoses, spray guns and other adhesive equipment
- Decal residue removal safe for powder-coated surfaces

DIRECTIONS FOR USE

- TensorGrip S104 can be sprayed on and wiped off.
 Wash off any remaining residue with water.
- The product will not be damaged by freezing. Warm up to room temperature for use.



SIO4 ADHESIVE CLEANER/REMOVER

CHEMICAL TECHNICAL DATA

TYPICAL PROPERTIES

Total SolidsVOC Content

Color

System Flammability Flammable propellant
Solvent System Acetone, Mineral Spirits

Dry time 1-3 mins dependent on temp & humidity
Shelf Life 18 months from date of manufacture

0%

350 g/L

Clear

PACKAGING

• 650ml Aerosol Cans

STORAGE

HANDLING & STORAGE

- Consult Material Safety Data Sheet prior to use.
- Do not store at temperatures over 120°F/50°C.
- · Avoid exposure to direct sunlight.
- Do not store directly on concrete floor.
- Always store above 60°F/15°C
- When connected, keep valve open and hose pressurized at all times
- Always test our adhesives to determine suitability for your particular application prior to use in production

DISCLAIMER OF WARRANTY: Quin Global makes neither warranty of merchantability or fitness for any use nor any other warranty, express or implied, in the sales of its products. Buyer assumes all risk and liability for the results obtained by the use of its products, whether used singly or in combination with other products.







SAFETY DATA SHEET Tensorgrip S104 Adhesive Remover/Cleaner Canister SDS

1. Identification

Product identifier

Product name Tensorgrip S104 Adhesive Remover/Cleaner Canister SDS

Product number USA

Recommended use of the chemical and restrictions on use

Application Aerosol Cleaning Solvent

Details of the supplier of the safety data sheet

Supplier Quin Global US, Inc.

5710 F St

Omaha NE 68117 (402) 731 3636 (402) 731 1473

marketing.us@quin-global.com

Emergency telephone number

Emergency telephone Chemtrec: 1 800 424 9300

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Flam. Aerosol 2 - H223 Press. Gas, Compressed - H280 Flam. Liq. 2 - H225

Health hazards Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 STOT SE 3 -

H336 Asp. Tox. 1 - H304

Environmental hazards Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Human health The liquid may be irritating to eyes, respiratory system and skin. Symptoms following

overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

Label elements

Hazard symbols







Signal word

Danger

Revision date: 9/19/2019 Revision: 9 Supersedes date: 11/30/2017

Tensorgrip S104 Adhesive Remover/Cleaner Canister SDS

Hazard statements H223 Flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H225 Highly flammable liquid and vapor.

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways. H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301+P312 If swallowed: Call a poison center/ doctor if you feel unwell.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/ shower.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Contains Odorless Mineral Spirits, Cyclohexane

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

Odorless Mineral Spirits	60-100%
CAS number: 64742-47-8	
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	

Cyclohexane 20-30%

CAS number: 110-82-7

M factor (Acute) = 1 M factor (Chronic) = 1

Classification

Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

Revision date: 9/19/2019 Revision: 9 Supersedes date: 11/30/2017

Tensorgrip S104 Adhesive Remover/Cleaner Canister SDS

General information Remove affected person from source of contamination. Place unconscious person on their

side in the recovery position and ensure breathing can take place. Get medical attention if any

discomfort continues.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. When breathing is difficult, properly trained personnel may assist affected person

by administering oxygen. Get medical attention.

Ingestion Get medical attention immediately. Never give anything by mouth to an unconscious person.

Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a

position comfortable for breathing.

Skin Contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the

person is conscious, coherent and they can remove them themselves If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get

medical attention promptly. Show this Safety Data Sheet to the medical personnel.

Most important symptoms and effects, both acute and delayed

Inhalation May cause coughing and difficulties in breathing. May cause eye and respiratory system

irritation. Overexposure may depress the central nervous system, causing dizziness and

intoxication.

Ingestion Aspiration hazard if swallowed. May be fatal if swallowed and enters airways. Ingestion may

cause severe irritation of the mouth, the esophagus and the gastrointestinal tract. May Cause the following effects: Gastrointestinal symptoms, including upset stomach. Central nervous system depression. Nausea, vomiting. Entry into the lungs following ingestion or vomiting may

cause chemical pneumonitis.

Skin contact May be absorbed through the skin. Product has a defatting effect on skin. The liquid is

irritating to eyes and skin. A single exposure may cause the following adverse effects:

Dryness and/or cracking.

Eye contact Causes serious eye irritation. Burns can occur. A single exposure may cause the following

adverse effects: Pain. Conjunctivitis, irritation, tearing. Prolonged or repeated exposure may cause the following adverse effects: Irritation of eyes and mucous membranes. Prolonged

contact causes serious eye and tissue damage.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards Pressurized container: Must not be exposed to temperatures above 50°C/120°F Containers

can burst violently or explode when heated, due to excessive pressure build-up. Vapors are heavier than air and may spread near ground and travel a considerable distance to a source

of ignition and flash back.

Advice for firefighters

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. No smoking, sparks, flames or other sources of

ignition near spillage.

Environmental precautions

Environmental precautions Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-

combustible material.

Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames

or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and

place into containers. Wash thoroughly after dealing with a spillage.

7. Handling and storage

Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide

adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use. Use explosion proof electric equipment. Avoid discharge into drains or watercourses or onto the

ground.

Advice on general occupational hygiene

Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the

original container. Pressurized container: Must not be exposed to temperatures above

50°C/120°F

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits

Odorless Mineral Spirits

Long-term exposure limit (8-hour TWA): ACGIH 200 mg/m³

Long-term exposure limit (8-hour TWA): OSHA 500 ppm 2000 mg/m³

Cyclohexane

Long-term exposure limit (8-hour TWA): ACGIH 100 ppm

ACGIH = American Conference of Governmental Industrial Hygienists.

OSHA = Occupational Safety and Health Administration.

Exposure controls

Protective equipment





Revision date: 9/19/2019 Revision: 9 Supersedes date: 11/30/2017

Tensorgrip S104 Adhesive Remover/Cleaner Canister SDS

Appropriate engineering

controls

This product must not be handled in a confined space without adequate ventilation. Avoid inhalation of vapors and spray/mists. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust,

fumes, gas, vapor or mist.

Eye/face protection Wear chemical splash goggles.

Hand protection Use protective gloves.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapor contact.

Hygiene measures DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating,

smoking and using the toilet. Wash promptly with soap and water if skin becomes

contaminated. Promptly remove any clothing that becomes contaminated. When using do not

eat, drink or smoke.

filter for short term low level exposures. For long term or high level exposures, a supplied air

respirator should be used.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance Aerosol.

Color Clear

Odor Sweetish.

Initial boiling point and range 81°C/177.8°F

Flash point -18°C/0°F Closed cup.

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: .6% Upper flammable/explosive limit: 8.3%

Relative density 0.765

Volatile organic compound This product contains a maximum VOC content of 466.97 g/l.

10. Stability and reactivity

Stability Stable at normal ambient temperatures and when used as recommended.

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:

Oxidizing agents. Reducing agents.

Hazardous decomposition

products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

Hydrogen chloride (HCI). Nitrous gases (NOx).

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 793.65

Acute toxicity - dermal

ATE dermal (mg/kg) 1,746.03

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 17.46

Toxicological information on ingredients.

Odorless Mineral Spirits

Acute toxicity - oral

Acute toxicity oral (LD50

5,000.0

mg/kg)

Species Rat

ATE oral (mg/kg) 500.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,000.0

mg/kg)

Species Rabbit

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

Acute toxicity inhalation

(LC₅₀ vapours mg/l)

5.0

11.0

Species Rat

ATE inhalation (vapours

mg/l)

Skin corrosion/irritation

Animal data Irritating.

Serious eye damage/irritation

Serious eye

Slightly irritating.

damage/irritation

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

Specific target organ toxicity - single exposure

STOT - single exposure High concentrations may cause: Central nervous system depression. Continued

inhalation may result in: Unconsciousness and/or death.

Specific target organ toxicity - repeated exposure

Target organs Kidneys

Route of exposure Skin absorption Skin and/or eye contact Inhalation Ingestion

Cyclohexane

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

12,705.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,000.0

mg/kg)

Species Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation

34,000.0

(LC₅₀ vapours mg/l)

Species Rat

Serious eye damage/irritation

Serious eye

Slightly irritating.

damage/irritation

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways.

.

Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Vapours may cause

drowsiness and dizziness.

Ingestion May be harmful if swallowed. Aspiration hazard if swallowed.

Skin Contact May be absorbed through the skin. Causes skin irritation.

Eye contact Causes eye irritation.

12. Ecological information

13. Disposal considerations

Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

14. Transport information

Air transport notes Cargo aircraft only. <75kg

UN Number

UN No. (TDG) 3501

UN No. (IMDG) 3501

UN No. (ICAO) 3501

UN No. (DOT) 3501

UN proper shipping name

Proper shipping name (TDG) Chemical Under Pressure, Flammable, N.O.S. (Odorless Mineral Spirits, Cyclohexane)

Proper shipping name (IMDG) Chemical Under Pressure, Flammable, N.O.S. (Odorless Mineral Spirits, Cyclohexane)

Proper shipping name (ICAO) Chemical Under Pressure, Flammable, N.O.S. (Odorless Mineral Spirits, Cyclohexane)

Proper shipping name (DOT) Chemical Under Pressure, Flammable, N.O.S. (Odorless Mineral Spirits, Cyclohexane)

Transport hazard class(es)

DOT hazard class 2.1

Transport labels



Packing group

Packing group (International) Not applicable.

15. Regulatory information

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009

No. 716).

Guidance CHIP for everyone HSG228.

Workplace Exposure Limits EH40.

Safety Data Sheets for Substances and Preparations.

Approved Classification and Labelling Guide (Sixth edition) L131.

US Federal Regulations

SARA (311/312) Hazard Categories

Present.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

Present.

Massachusetts "Right To Know" List

Present.

New Jersey "Right To Know" List

Present.

Pennsylvania "Right To Know" List

Present.

Inventories

Canada - DSL/NDSL

Present. DSL

US - TSCA

Present.

16. Other information

Revision date 9/19/2019

Revision 9

Supersedes date 11/30/2017

SDS No. 23114

Hazard statements in full H223 Flammable aerosol.

H225 Highly flammable liquid and vapor.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation. H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

ACA HMIS Health rating. Moderate hazard. (2)

ACA HMIS Flammability

rating.

Extremely flammable. (4)

ACA HMIS Physical hazard

rating.

Normally stable. (0)

ACA HMIS Personal

В

protection rating.

DIRECTIONS FOR USE

PRODUCT LOGO

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the usage of this product is fit for a particular purpose and suitable for the user's method of use or application. It is essential that the user, not the manufacturer, evaluates this product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.