

4375 | WIDE BELT SANDERS

I've been running the 20HP 3ph version for 5+ years now. As expected, it is a workhorse that will far outlive me. Jeff Roltgen, Roltgen Woodworks, Rapid City, South Dakota



The 43x75 wide belt sanders are welded at our factory in Minnesota with domestic steel.

75" abrasive belts in this machine are 25% longer than the belts on the 37X60. This increases capacity, reduces heat and provides more consistent results.



Optional Power Lift Table

An adjustable platen allows for finer sanding with finish sanding abrasives

Configure your Safety Speed on your application, use and your shop requirements.

4375 Wide Belt Sander

Motor Configurations	10 Hp, 1~, 220 Volt 20 Hp, 3~, 208 / 230 Volt 30 Hp, 3~, 208 / 230 Volt
Max. Working Length	Unlimited
Min. Working Length	12" / 305mm
Max. Working Width	42" / 1070mm
Max. Working Thickness	7.25" / 184mm
Min. Working Thickness	1/8" / 3mm
Machine Dimensions	53"D x 70"H x 56"W
Vacuum Requirement	1000 CFM
Conveyor Speed	0-18 FPM
Durometer of Contact Roller	60
Sanding Belt Size	43" x 75"
Shipping Weight	1946lbs/883KG

Features

- 5.25" Diameter Contact Roller
- Rubber-Covered Pinch Rollers (2)
- 1" diameter jackscrews (4)
- Photo electric belt tracking.
- Platen 2.5" and adjustable.
- Emergency stops (5).
- Pneumatic belt tensioning.
- 6" internal dust chute.
- Conveyor Motor (3/4 Hp)
- 3 year warranty.

Optional Equipment

- Digital Readout (DRO)
- Power Lift Table
- Hour Meter
- 460 Voltage Configuration
- Abrasive Sanding belts