



## FormFill Color Matched Caulk, 5.5 Fl.oz Tube

## GENERAL SPECIFICATIONS

## PRODUCT IDENTIFICATION

Product Name:	FormFill Color Matched Caulk
Other Names:	Silicized Latex Caulk
Product Classification	Caulking Compound

## COMPOSITION

Single or Mixture:	Mixture	Weight %	ACGIH TLV	PEL	STEL
Chemical Name	CAS Number				
Calcium Carbonate	471-34-1	35%-65%	10 mg/m <sup>3</sup>	5mg/m <sup>3</sup>	
Vinyl acetate/acrylic copolymer	Proprietary	10%-20%			
Phthalate plasticizer	Proprietary	5%-10%			
Acrylic resin	Proprietary	4%-10%			
Distillates (petroleum), hydrotreated middle	64742-46-7	<5.0%	5mg/m <sup>3</sup>	5mg/m <sup>3</sup>	10mg/m <sup>3</sup>
Ethylene Glycol	107-21-1	<1.0%	50mg/m	40 ppm	40 ppm

## HAZARDS IDENTIFICATION

Health Hazards	The principle volatile component is water. Minor volatile components from the emulsion may cause headache and nausea. Prolonged and repeated skin contact can cause irritation. Treatment of overexposure should be directed at the control of symptoms and clinical condition.
Eye Contact	Direct contact may cause moderate irritation.
Skin contact	No significant effects expected from a single short term exposure.
Inhalation	Trace component and residual monomer may cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.
Ingestion	No significant effects expected from a single short term exposure
Existing Conditions Aggravated by Exposure	No known applicable information
Symptoms of Overexposure	No known applicable information
Note	The above listed potential effects are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to section 11 for detailed toxicology information.

## FIRST AID MEASURES

Eye Contact	Immediately flush with large amounts of water. If irritation occurs, seek medical attention.
Skin Contact	Wash affected area with soap and water.
Inhalation	Remove to fresh air. If symptoms persist, obtain appropriate attention.
Ingestion	No first aid should be needed.

## FIRE FIGHTING MEASURES

Flash Point	Not determined
Extinguishing Media	Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog
Special Fire Fighting Procedures	Non-flammable (aqueous emulsion). After ware evaporates, remaining material will burn. Breathing apparatus required when fighting fire in enclosed areas.
Unusual Fire or Explosion Hazards	Product will not burn, but may splatter if temperature exceeds boiling point of water. Dried solids can burn, giving off oxides of carbon.

## ACCIDENTAL RELEASE MEASURES

Steps to be taken in case of spill or release	Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment recommendations described in Sections 5 and 8. For large spills, providing diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. For small spills, wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled material, even in small quantities, may present a slip hazard. Final cleaning may require the use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and item employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.
---	---

## HANDLING AND STORAGE

Handling	Avoid breathing vapors in top of shipping container. Keep container closed. Use with adequate ventilation. Avoid contact with skin and clothing. Wash thoroughly after handling.
Storage	Store in a cool dry place. Protect from freezing and excessive heat.

## EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls	
Local Ventilation:	Recommended
General Ventilation:	Recommended
Eye Protection	Chemical goggles if liquid contact is likely, or safety glasses with side shields
Skin Protection	Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended
Respiratory Protection	Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within guidelines. Industrial Hygiene Personnel can assist in judging the adequacy of existing engineering controls.
Suitable Respirator	General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits as determined by air sampling or are unknown, appropriate respiratory protection should be worn. Follow OSHA Respirator Regulations (29CFR 1910.134) and use NIOSH/MSHS approved respirators.
Ventilation	Local exhaust ventilation is recommended to maintain vapor level below TLV.
Note	These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions. For further information regarding aerosol inhalation toxicity, please refer to the guidance document regarding the use of silicone-based materials in aerosol applications that has been developed by silicone industry ( <a href="http://www.SEHSC.com">www.SEHSC.com</a> )

## PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Paste
Specific Gravity	1.64
Color/Appearance	White
Odor	Slight
Boiling/Cond. Point	100° C
Melting/Freezing Point	0° C
Solubility	Dilutable in wet stage
Evaporation Rate	Slower than n-Butyl acetate
VOC%	0.67% (by weight) 11g/l
Percent Volatile	18%
Vapor Density	Lighter than air
Vapor Pressure	Not Determined
CARB Method 310: VOC Content	11 grams/liter
Note	The above information is not intended for use in preparing product specifications. Contact FormFill Products before writing specifications.



Manufacturer:  
FormFill Products  
305 Industrial Blvd  
Clarksville, TX 75426  
Tel: 903 427 0267  
Fax: 903 427 0261

Office:  
O'BH Associates LLC  
609 Cheek Sparger, Ste 120  
Colleyville, Texas 76034  
Tel: 800 536 0041  
Fax: 817 428 0333

Emergency Response Center:  
InfoTrac  
200 North Palmetto Street  
Leesburg, Florida 34748  
Tel. United States: 1 800 535 5053  
Tel. International: 1 352 323 3500

The information given is based on data considered accurate as of the date indicated. However no representation, guarantee or warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. FormFill Products assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.

**STABILITY AND REACTIVITY**

Chemical Stability	Stable
Hazardous Polymerization	Will not occur
Materials to Avoid/Incompatibility	None Known

**TOXICOLOGICAL INFORMATION**

Special Hazard Information on Components	No known applicable information
Component Toxicology Information	No known applicable information

**ECOLOGICAL INFORMATION**

Environmental Effects	Complete information is not yet available
Environmental Fate and Distribution	Complete information is not yet available.
Fate and Effects in Waste Water Treatment Plants	Complete information is not yet available.

**DISPOSAL CONSIDERATION**

Waste Disposal Method	We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state or federal laws. It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes. This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after careful evaluation and in compliance with all federal, local and state laws.
-----------------------	---

**TRANSPORTATION INFORMATION**

US DOT & CANADA TDG SURFACE Transport by sea IMDG-Code	Valuation: Not regulated for transport
Air transport ICAO-TI/IATA-DGR	Valuation: Not regulated for transport

**REGULATORY INFORMATION**

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910. 1200.	
TSCA Status	All chemical substances found in this product comply with the Toxic Substance Control Act inventory reporting requirements
SARA Title III Section 302 Extremely Hazardous Substances	None
SARA Title III Section 304 CERCLA Hazardous Substances	None
SARA Title III Section 312 Hazard Class	
Acute:	Yes
Chronic:	No
Fire:	No
Pressure:	No
Reactive:	No
SARA Title III Section 313 Toxic Chemicals	None present or none present in regulated quantities.
California Proposition 65	This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: None known

**OTHER INFORMATION**

HMIS III Rating	Health: 0	HMIS uses a numbering scale ranging from 0 to 4 to indicate the degree of hazard. Value of zero means that the substance possesses essentially no hazard; a rating of four indicates high hazard	Flammability: 0	Physical hazard: 0
-----------------	-----------	--	-----------------	--------------------

**FOR INDUSTRIAL USE ONLY**

This material safety data sheet is offered solely for your information, consideration and investigation. The data described in this MSDS consist of data on literature, our acquisitioned data and analogical inference by data of similar chemical substance or product. FormFill Products provides no warranties; either expressed or implied, and assumes no responsibility for the accuracy or completeness of the data contained herein.



Manufacturer:  
FormFill Products  
305 Industrial Blvd  
Clarksville, TX 75426  
Tel: 903 427 0267  
Fax: 903 427 0261

Office:  
O'BH Associates LLC  
609 Cheek Sparger, Ste 120  
Colleyville, Texas 76034  
Tel: 800 536 0041  
Fax: 817 428 0333

Emergency Response Center:  
InfoTrac  
200 North Palmetto Street  
Leesburg, Florida 34748  
Tel. United States: 1 800 535 5053  
Tel. International: 1 352 323 3500

*The information given is based on data considered accurate as of the date indicated. However no representation, guarantee or warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. FormFill Products assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.*