

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



FILL & FINISH - ALDER 16OZ

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2024
2.0	06/30/2025	5376770-00007	Date of first issue: 01/16/2020

SECTION 1. IDENTIFICATION

Product name : FILL & FINISH - ALDER 16OZ

Product code : 0890303511

Manufacturer or supplier's details

Company name of supplier : Wurth USA Inc.

Address : 93 Grant St.
Ramsey, NJ 07446

Telephone : (201) 825-2710

Telefax : (201) 825-1643

Emergency telephone : +1 800 255 3924

E-mail address : prodsafe@wuerth.com

Recommended use of the chemical and restrictions on use

Recommended use : Body filler/stopper

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization : Category 1

Other hazards

None known.

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

Precautionary Statements : **Prevention:**
P261 Avoid breathing vapors.
P272 Contaminated work clothing must not be allowed out of the workplace.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



FILL & FINISH - ALDER 16OZ

Version 2.0 Revision Date: 06/30/2025 SDS Number: 5376770-00007 Date of last issue: 06/18/2024
Date of first issue: 01/16/2020

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P321 Specific treatment (see supplemental first aid instructions on this label).

P333 + P313 If skin irritation or rash occurs: Get medical attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Limestone	1317-65-3*	>= 65 - <= 85	TSC
Quartz	14808-60-7*	>= 0.5 - <= 1.5	TSC
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9*	<= 0.1	TSC
2-Methyl-2H-isothiazol-3-one	2682-20-4*	<= 0.1	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

Alternative CAS Numbers for some ingredients

Chemical name	Alternative CAS Number(s)
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	2682-20-4, 26172-55-4

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



FILL & FINISH - ALDER 16OZ

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2024
2.0	06/30/2025	5376770-00007	Date of first issue: 01/16/2020

- of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Not applicable
Will not burn
- Unsuitable extinguishing media : Not applicable
Will not burn
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



FILL & FINISH - ALDER 16OZ

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2024
2.0	06/30/2025	5376770-00007	Date of first issue: 01/16/2020

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8). |
| Environmental precautions | : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for containment and cleaning up | : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. |

SECTION 7. HANDLING AND STORAGE

- | | |
|-----------------------------|--|
| Technical measures | : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : Use only with adequate ventilation. |
| Advice on safe handling | : Do not get on skin or clothing.
Avoid breathing vapors.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment. |
| Conditions for safe storage | : Keep in properly labeled containers.
Store in accordance with the particular national regulations. |
| Materials to avoid | : No special restrictions on storage with other products. |

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



FILL & FINISH - ALDER 16OZ

Version 2.0 Revision Date: 06/30/2025 SDS Number: 5376770-00007 Date of last issue: 06/18/2024
Date of first issue: 01/16/2020

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Limestone	1317-65-3	TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (Respirable)	5 mg/m ³ (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m ³ (Calcium carbonate)	NIOSH REL
Quartz	14808-60-7	TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m ³ (Silica)	NIOSH REL
		PEL (respirable)	0.05 mg/m ³	OSHA CARC

Engineering measures : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0.38 mm
Protective index : Class 6

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



FILL & FINISH - ALDER 16OZ

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2024
2.0	06/30/2025	5376770-00007	Date of first issue: 01/16/2020

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous

Color : colored

Odor : pleasant

Odor Threshold : No data available

pH : 7

Melting point/freezing point : 32 °F / 0 °C

Initial boiling point and boiling range : No data available

Flash point : does not flash

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Will not burn

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



FILL & FINISH - ALDER 16OZ

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2024
2.0	06/30/2025	5376770-00007	Date of first issue: 01/16/2020

Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	1.85
Density	:	1.85 g/cm ³
Solubility(ies) Water solubility	:	Decomposes in contact with water.
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	None known.
Conditions to avoid	:	None known.
Incompatible materials	:	None.
Hazardous decomposition products	:	No hazardous decomposition products are known.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



FILL & FINISH - ALDER 16OZ

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2024
2.0	06/30/2025	5376770-00007	Date of first issue: 01/16/2020

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Limestone:

Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 420 Assessment: The substance or mixture has no acute oral toxicity Remarks: Based on data from similar materials
Acute inhalation toxicity	: LC50 (Rat): > 3 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity Remarks: Based on data from similar materials

Quartz:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
---------------------	-----------------------------

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Acute oral toxicity	: LD50 (Rat): 64 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 0.171 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: Corrosive to the respiratory tract.
Acute dermal toxicity	: LD50 (Rabbit): 87.12 mg/kg

2-Methyl-2H-isothiazol-3-one:

Acute oral toxicity	: LD50 (Rat): 120 mg/kg
---------------------	-------------------------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



FILL & FINISH - ALDER 16OZ

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2024
2.0	06/30/2025	5376770-00007	Date of first issue: 01/16/2020

Acute inhalation toxicity : LC50 (Rat): 0.11 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rat): 242 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Components:

Limestone:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Quartz:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 1 to 4 hours of exposure

2-Methyl-2H-isothiazol-3-one:

Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Limestone:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Quartz:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



FILL & FINISH - ALDER 16OZ

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2024
2.0	06/30/2025	5376770-00007	Date of first issue: 01/16/2020

Remarks : Based on data from similar materials

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Result : Irreversible effects on the eye

Remarks : Based on skin corrosivity.

2-Methyl-2H-isothiazol-3-one:

Result : Irreversible effects on the eye

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Limestone:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative
Remarks	: Based on data from similar materials

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Test Type : Buehler Test

Routes of exposure : Skin contact

Species : Guinea pig

Result : positive

Assessment : Probability or evidence of high skin sensitization rate in humans

2-Methyl-2H-isothiazol-3-one:

Routes of exposure : Skin contact

Result : positive

Assessment : Probability or evidence of high skin sensitization rate in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Limestone:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



FILL & FINISH - ALDER 16OZ

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2024
2.0	06/30/2025	5376770-00007	Date of first issue: 01/16/2020

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

2-Methyl-2H-isothiazol-3-one:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with
mammalian liver cells in vivo
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 486
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Quartz:

Species	:	Humans
Application Route	:	inhalation (dust/mist/fume)
Result	:	positive
Remarks	:	This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

IARC	Group 1: Carcinogenic to humans	
	Quartz	14808-60-7
	(Silica dust, crystalline)	

OSHA	OSHA specifically regulated carcinogen	
	Quartz	14808-60-7
	(crystalline silica)	

NTP	Known to be human carcinogen	
	Quartz	14808-60-7
	(Silica, Crystalline (Respirable Size))	

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



FILL & FINISH - ALDER 16OZ

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2024
2.0	06/30/2025	5376770-00007	Date of first issue: 01/16/2020

Reproductive toxicity

Not classified based on available information.

Components:

Limestone:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

2-Methyl-2H-isothiazol-3-one:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Limestone:

Species : Rat
NOAEL : > 300 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Method : OECD Test Guideline 422
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



FILL & FINISH - ALDER 16OZ

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2024
2.0	06/30/2025	5376770-00007	Date of first issue: 01/16/2020

Quartz:

Species	:	Rat
LOAEL	:	0.002 mg/l
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	13 Weeks
Remarks	:	This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Limestone:

Toxicity to fish	:	LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	LL50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	:	EL50 (Desmodesmus subspicatus (green algae)): > 14 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 Remarks: No toxicity at the limit of solubility. Based on data from similar materials EL10 (Desmodesmus subspicatus (green algae)): > 14 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 Remarks: No toxicity at the limit of solubility. Based on data from similar materials
Toxicity to microorganisms	:	EC50: > 100 mg/l Exposure time: 3 h Method: OECD Test Guideline 209 Remarks: Based on data from similar materials

Quartz:

Toxicity to fish	:	LL50 (Danio rerio (zebra fish)): > 10,000 mg/l Exposure time: 96 h
------------------	---	---

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



FILL & FINISH - ALDER 16OZ

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2024
2.0	06/30/2025	5376770-00007	Date of first issue: 01/16/2020

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 0.19 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 0.16 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	ErC50 (Skeletonema costatum (marine diatom)): 0.0052 mg/l Exposure time: 48 h NOEC (Skeletonema costatum (marine diatom)): 0.00049 mg/l Exposure time: 48 h
Toxicity to fish (Chronic toxicity)	:	NOEC (Pimephales promelas (fathead minnow)): 0.02 mg/l Exposure time: 36 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 0.10 mg/l Exposure time: 21 d

2-Methyl-2H-isothiazol-3-one:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 4.77 - 6 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 0.93 - 1.9 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	ErC50 (Skeletonema costatum (marine diatom)): 0.1 mg/l Exposure time: 72 h ErC50 (Skeletonema costatum (marine diatom)): 0.0695 mg/l Exposure time: 24 h EC10 (Pseudokirchneriella subcapitata (green algae)): 0.024 mg/l Exposure time: 24 h
Toxicity to fish (Chronic toxicity)	:	NOEC (Pimephales promelas (fathead minnow)): 2.1 mg/l Exposure time: 33 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 0.04 mg/l Exposure time: 21 d

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



FILL & FINISH - ALDER 16OZ

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2024
2.0	06/30/2025	5376770-00007	Date of first issue: 01/16/2020

Persistence and degradability

Components:

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 62 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

2-Methyl-2H-isothiazol-3-one:

Biodegradability : Result: Not readily biodegradable.

Bioaccumulative potential

Components:

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Partition coefficient: n- : log Pow: < 1
octanol/water

2-Methyl-2H-isothiazol-3-one:

Partition coefficient: n- : log Pow: -0.34
octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



FILL & FINISH - ALDER 16OZ

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2024
2.0	06/30/2025	5376770-00007	Date of first issue: 01/16/2020

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Volatile organic compounds (VOC) content 40 CFR Part 59 National VOC Emission Standard For Consumer Products, Subpart C
VOC content: 0 %

US State Regulations

Pennsylvania Right To Know

Limestone	1317-65-3
Water	7732-18-5
Quartz	14808-60-7

California Prop. 65

WARNING: This product can expose you to chemicals including Quartz, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Permissible Exposure Limits for Chemical Contaminants

Limestone	1317-65-3
Quartz	14808-60-7

California Regulated Carcinogens

Quartz	14808-60-7
--------	------------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



FILL & FINISH - ALDER 16OZ

Version 2.0 Revision Date: 06/30/2025 SDS Number: 5376770-00007 Date of last issue: 06/18/2024
Date of first issue: 01/16/2020


The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	1	2
FLAMMABILITY	0	
PHYSICAL HAZARD	0	

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits
OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA : 8-hour, time-weighted average
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



FILL & FINISH - ALDER 16OZ

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2024
2.0	06/30/2025	5376770-00007	Date of first issue: 01/16/2020

International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 06/30/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8