according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

SECTION 1. IDENTIFICATION

Product name : HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Product code : 0890303513

Manufacturer or supplier's details

Company name of supplier : Wurth USA Inc.

Address : 93 Grant St.

Ramsey, NJ 07446

Telephone : (201) 825-2710

Telefax : (201) 825-1643

Emergency telephone : +1 800 255 3924

E-mail address : prodsafe@wuerth.com

Recommended use of the chemical and restrictions on use

Recommended use : Body filler/stopper

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization : Category 1

GHS label elements

Hazard pictograms



Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

Precautionary Statements : Prevention:

P261 Avoid breathing vapors.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves.

Response:

according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P321 Specific treatment (see supplemental first aid instructions

on this label).

P333 + P313 If skin irritation or rash occurs: Get medical atten-

tion.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 70 - < 90
Quartz	14808-60-7	>= 1 - < 5
Diiron trioxide	1309-37-1	>= 1 - < 5
Reaction mass of: 5-chloro-2-methyl-	55965-84-9	>= 0.0015 - < 0.06
4-isothiazolin-3-one and 2-methyl-2H-		
isothiazol-3-one (3:1)		
2-Methyl-2H-isothiazol-3-one	2682-20-4	>= 0.0015 - < 0.1

Actual concentration is withheld as a trade secret

Alternative CAS Numbers for some regions

Alternative CAS Number(s)
2682-20-4, 26172-55-4

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.

according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

May cause an allergic skin reaction.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Not applicable

Will not burn

Unsuitable extinguishing

media

Not applicable Will not burn

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Carbon oxides Metal oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.

Avoid breathing vapors.

Do not swallow.

Avoid contact with eyes.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Limestone	1317-65-3	TWA (total dust)	15 mg/m³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m³	OSHA Z-1
		TWA (Respirable)	5 mg/m³ (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m³ (Calcium car-	NIOSH REL

according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

			bonate)	
Quartz	14808-60-7	TWA (Res-	0.05 mg/m ³	OSHA Z-1
		pirable dust)		
		TWA (respir-	10 mg/m3	OSHA Z-3
		able)	/ %SiO2+2	
		TWA (respir-	250 mppcf	OSHA Z-3
		able)	/ %SiO2+5	
		TWA (Res-	0.025 mg/m ³	ACGIH
		pirable par-	(Silica)	
		ticulate mat-		
		ter)		
		TWA (Res-	0.05 mg/m ³	NIOSH REL
		pirable dust)	(Silica)	
		PEL (respir-	0.05 mg/m ³	OSHA CARC
		able)		
Diiron trioxide	1309-37-1	TWA (Res-	5 mg/m³	ACGIH
		pirable par-		
		ticulate mat-		
		ter)		
		TWA (dust	5 mg/m³	NIOSH REL
		and fume)	(Iron)	
		TWA	10 mg/m ³	OSHA Z-1
		(Fumes)		
		TWA (total	15 mg/m ³	OSHA Z-1
		dust)		
		TWA (respir-	5 mg/m³	OSHA Z-1
		able fraction)		

Engineering measures : Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where

concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance

where air purifying respirators may not provide adequate

protection.

Hand protection

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0.38 mm
Protective index : Class 6

according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of

workday.

Eye protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke.

Contaminated work clothing should not be allowed out of the

workplace.

Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous

Color : colored

Odor : pleasant

Odor Threshold : No data available

pH : 7

Melting point/freezing point : 32 °F / 0 °C

Initial boiling point and boiling :

range

No data available

Flash point : does not flash

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Will not burn

according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : 1.85

Density : 1.85 g/cm³

Solubility(ies)

Water solubility : Decomposes in contact with water.

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

None known.

Conditions to avoid : None known.

Incompatible materials : None.

Hazardous decomposition

products

No hazardous decomposition products are known.

according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

Limestone:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 420

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Diiron trioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Acute oral toxicity : LD50 (Rat): 64 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.171 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rabbit): 87.12 mg/kg

according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

2-Methyl-2H-isothiazol-3-one:

Acute oral toxicity : LD50 (Rat): 120 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.11 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rat): 242 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Components:

Limestone:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Quartz:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Diiron trioxide:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Species : Rabbit

Method : OECD Test Guideline 404

Result : Corrosive after 1 to 4 hours of exposure

2-Methyl-2H-isothiazol-3-one:

Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Limestone:

Species : Rabbit

according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Quartz:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Diiron trioxide:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Result : Irreversible effects on the eye Remarks : Based on skin corrosivity.

2-Methyl-2H-isothiazol-3-one:

Result : Irreversible effects on the eye

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Limestone:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Remarks : Based on data from similar materials

Diiron trioxide:

Routes of exposure : Skin contact Species : Guinea pig Result : negative

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Test Type : Buehler Test

according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

Routes of exposure : Skin contact Species : Guinea pig Result : positive

Assessment : Probability or evidence of high skin sensitization rate in hu-

mans

2-Methyl-2H-isothiazol-3-one:

Routes of exposure : Skin contact Result : positive

Assessment : Probability or evidence of high skin sensitization rate in hu-

mans

Germ cell mutagenicity

Not classified based on available information.

Components:

Limestone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Diiron trioxide:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

2-Methyl-2H-isothiazol-3-one:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with

mammalian liver cells in vivo

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 486

Result: negative

according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

Carcinogenicity

Not classified based on available information.

Components:

Quartz:

Species : Humans

Application Route : inhalation (dust/mist/fume)

Result : positive

Remarks : This substance(s) is not bioavailable and therefore does not

contribute to a dust inhalation hazard.

Diiron trioxide:

Species : Rat

Application Route : Intraperitoneal injection

Exposure time : 790 - 914 days Result : negative

IARC Group 1: Carcinogenic to humans

Quartz 14808-60-7

(Silica dust, crystalline)

OSHA specifically regulated carcinogen

Quartz 14808-60-7

(crystalline silica)

NTP Known to be human carcinogen

Quartz 14808-60-7

(Silica, Crystalline (Respirable Size))

Reproductive toxicity

Not classified based on available information.

Components:

Limestone:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

2-Methyl-2H-isothiazol-3-one:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Limestone:

Species : Rat

NOAEL : > 300 mg/kg
Application Route : Ingestion
Exposure time : 28 Days

Method : OECD Test Guideline 422

Remarks : Based on data from similar materials

Quartz:

Species : Rat LOAEL : 0.002 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 13 Weeks

Remarks : This substance(s) is not bioavailable and therefore does not

contribute to a dust inhalation hazard.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Limestone:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

LL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EL50 (Desmodesmus subspicatus (green algae)): > 14 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility.

Based on data from similar materials

EL10 (Desmodesmus subspicatus (green algae)): > 14 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility.

Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Quartz:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 10,000 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Diiron trioxide:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 50,000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to microorganisms : EC50: > 10,000 mg/l

Exposure time: 3 h

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.19 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.16 mg/l

Exposure time: 48 h

according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

Toxicity to algae/aquatic

plants

ErC50 (Skeletonema costatum (marine diatom)): 0.0052 mg/l

Exposure time: 48 h

NOEC (Skeletonema costatum (marine diatom)): 0.00049 mg/l

Exposure time: 48 h

Toxicity to fish (Chronic tox-

icity)

NOEC (Pimephales promelas (fathead minnow)): 0.02 mg/l

Exposure time: 36 d

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.10 mg/l

Exposure time: 21 d

2-Methyl-2H-isothiazol-3-one:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.77 - 6 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.93 - 1.9 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

ErC50 (Skeletonema costatum (marine diatom)): 0.1 mg/l

Exposure time: 72 h

ErC50 (Skeletonema costatum (marine diatom)): 0.0695 mg/l

Exposure time: 24 h

EC10 (Pseudokirchneriella subcapitata (green algae)): 0.024

mg/l

Exposure time: 24 h

Toxicity to fish (Chronic tox-

icity)

NOEC (Pimephales promelas (fathead minnow)): 2.1 mg/l

Exposure time: 33 d

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.04 mg/l

Exposure time: 21 d

Persistence and degradability

Components:

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 62 % Exposure time: 28 d

Method: OECD Test Guideline 301B

2-Methyl-2H-isothiazol-3-one:

Biodegradability : Result: Not readily biodegradable.

according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

Bioaccumulative potential

Components:

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Partition coefficient: n-

octanol/water

log Pow: < 1

2-Methyl-2H-isothiazol-3-one:

Partition coefficient: n-

octanol/water

log Pow: -0.34

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Volatile organic compounds

(VOC) content

40 CFR Part 59 National VOC Emission Standard For Con-

sumer Products, Subpart C

VOC content: 0 %

US State Regulations

Pennsylvania Right To Know

 Limestone
 1317-65-3

 Water
 7732-18-5

 Quartz
 14808-60-7

 Diiron trioxide
 1309-37-1

California Prop. 65

WARNING: This product can expose you to chemicals including Quartz, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Diiron trioxide 1309-37-1

California Permissible Exposure Limits for Chemical Contaminants

 Limestone
 1317-65-3

 Quartz
 14808-60-7

 Diiron trioxide
 1309-37-1

California Regulated Carcinogens

Quartz 14808-60-7

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

SECTION 16. OTHER INFORMATION

Further information


according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Oth-

according to the OSHA Hazard Communication Standard



HVY BODY FILL & FINISH ROSEWOOD 3.9LB

Version Revision Date: SDS Number: Date of last issue: 11/13/2022 1.5 06/18/2024 5376685-00006 Date of first issue: 01/16/2020

erwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 06/18/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8