

ACETONE

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/24/2019 5207637-00001 Date of first issue: 10/24/2019

SECTION 1. IDENTIFICATION

Product name : ACETONE

Product code : 0893460006

Manufacturer or supplier's details

Company name of supplier : Wurth USA Inc.

Address : 93 Grant St.

Ramsey, NJ 07446

Telephone : (201) 825-2710

Telefax : (201) 825-1643

Emergency telephone : +1 800 255 3924

E-mail address : prodsafe@wuerth.com

Recommended use of the chemical and restrictions on use

Recommended use : Solvent

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 2

Eye irritation : Category 2A

Specific target organ toxicity

- single exposure

Category 3

GHS label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Precautionary Statements : Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P233 Keep container tightly closed.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equip-



ACETONE

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/24/2019 5207637-00001 Date of first issue: 10/24/2019

ment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist or vapors. P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Repeated exposure may cause skin dryness or cracking.

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Substance name : Acetone

CAS-No. : 67-64-1

Components

Chemical name	CAS-No.	Concentration (% w/w)
Acetone	67-64-1	>= 90 - <= 100

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.



ACETONE

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/24/2019 5207637-00001 Date of first issue: 10/24/2019

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.

If vomiting occurs have person lean forward.

Call a physician or poison control center immediately.

Rinse mouth thoroughly with water.

Never give anything by mouth to an unconscious person.

Most important symptoms

and effects, both acute and

delayed

Causes serious eye irritation.

May cause drowsiness or dizziness.

Prolonged or repeated contact may dry skin and cause irrita-

tion.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not use a solid water stream as it may scatter and spread

fire.

Flash back possible over considerable distance. Vapors may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Carbon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.
Use water spray to cool unopened containers.

Description of the property of

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.



ACETONE

Version **Revision Date:** SDS Number: Date of last issue: -

10/24/2019 5207637-00001 Date of first issue: 10/24/2019 1.0

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Remove all sources of ignition.

Ventilate the area.

Use personal protective equipment.

Follow safe handling advice and personal protective

equipment recommendations.

Discharge into the environment must be avoided. Environmental precautions

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapors/mists with a water spray

For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation If sufficient ventilation is unavailable, use with local exhaust

ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventila-

tion.

Advice on safe handling Do not get on skin or clothing.

Do not breathe vapors or spray mist.

Do not swallow. Do not get in eyes.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment



ACETONE

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/24/2019 5207637-00001 Date of first issue: 10/24/2019

Non-sparking tools should be used. Keep container tightly closed.

Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store locked up. Keep tightly closed.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents Organic peroxides Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures which in contact with water emit

flammable gases

Explosives Gases

Recommended storage tem: :

perature

59 - 68 °F / 15 - 20 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	1,000 ppm 2,400 mg/m ³	OSHA Z-1
		TWA	250 ppm 590 mg/m³	NIOSH REL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentration	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure	25 mg/l	ACGIH BEI



ACETONE

Version Revision Date: 1.0 10/24/2019

SDS Number: 5207637-00001

Date of last issue: -

Date of first issue: 10/24/2019

ceases)

Engineering measures

: Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust

ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust venti-

lation.

Personal protective equipment

Respiratory protection

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate

protection.

Hand protection

Material : butyl-rubber

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the pro-

duct. Change gloves often!

Eye protection : Wear the following personal protective equipment:

Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Wear the following personal protective equipment:

If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic

protective clothing.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.



ACETONE

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/24/2019 5207637-00001 Date of first issue: 10/24/2019

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : colorless

Odor : aromatic, sweet, fruity

Odor Threshold : 306 - 653 ppm

pH : 7

Concentration: 10 g/l

Melting point/freezing point : -139 °F / -95 °C

Initial boiling point and boiling

range

133 °F / 56 °C

Flash point : 1 °F / -17 °C

Method: closed cup

Evaporation rate : 6

(Butyl Acetate=1.0)

2

(Diethylether=1.0)

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper

flammability limit

12.8 %(V)

Lower explosion limit / Lower

flammability limit

2 %(V)

Vapor pressure : 247 hPa (68 °F / 20 °C)

828 hPa (122 °F / 50 °C)

Relative vapor density : 2 (68 °F / 20 °C)

Relative density : 0.79

Density : 786 kg/m³

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : soluble



ACETONE

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/24/2019 5207637-00001 Date of first issue: 10/24/2019

Solvent: Ethanol

soluble

Solvent: Ether

soluble

Solvent: Dimethylformamide

soluble

Solvent: Chloroform

soluble

Solvent: Mineral oils

soluble

Solvent: Hydrocarbons

Partition coefficient: n-

octanol/water

log Pow: -0.24

Autoignition temperature : 869 °F / 465 °C

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : 0.32 mPa.s (68 °F / 20 °C)

Viscosity, kinematic : 0.417 mm²/s (104 °F / 40 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Minimum ignition energy : 1.15 mJ

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Highly flammable liquid and vapor.

Vapors may form explosive mixture with air.

Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.



ACETONE

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/24/2019 5207637-00001 Date of first issue: 10/24/2019

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

Acetone:

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l

Exposure time: 4 h Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): 7,426 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Acetone:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Acetone:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Acetone:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig



ACETONE

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/24/2019 5207637-00001 Date of first issue: 10/24/2019

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Acetone:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Acetone:

Species : Mouse
Application Route : Skin contact
Exposure time : 424 days
Result : negative

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Acetone:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative



ACETONE

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/24/2019 5207637-00001 Date of first issue: 10/24/2019

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: inhalation (vapor)

Result: negative

STOT-single exposure

May cause drowsiness or dizziness.

Components:

Acetone:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Acetone:

Species : Rat

NOAEL : 900 mg/kg LOAEL : 1,700 mg/kg Application Route : Ingestion Exposure time : 90 Days

Species : Rat NOAEL : 45 mg/l

Application Route : inhalation (vapor)

Exposure time : 8 Weeks

Aspiration toxicity

Not classified based on available information.

Components:

Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Acetone:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia pulex (Water flea)): 8,800 mg/l

Exposure time: 48 h



ACETONE

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/24/2019 5207637-00001 Date of first issue: 10/24/2019

Toxicity to algae/aquatic

plants

: NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000

mg/l

Exposure time: 96 h

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): >= 79 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: 61,150 mg/l

Exposure time: 30 min Method: ISO 8192

Persistence and degradability

Components:

Acetone:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 91 % Exposure time: 28 d

Bioaccumulative potential

Components:

Acetone:

Partition coefficient: n-

octanol/water

log Pow: -0.27 - -0.23

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations



ACETONE

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/24/2019 5207637-00001 Date of first issue: 10/24/2019

UNRTDG

UN number : UN 1090 Proper shipping name : ACETONE

Class : 3
Packing group : II
Labels : 3

IATA-DGR

UN/ID No. : UN 1090
Proper shipping name : Acetone
Class : 3
Packing group : II

Labels : Flammable Liquids

Packing instruction (cargo : 364

aircraft)

Packing instruction (passen: 353

ger aircraft)

IMDG-Code

UN number : UN 1090 Proper shipping name : ACETONE

Class : 3
Packing group : II
Labels : 3
EmS Code : F-

EmS Code : F-E, S-D Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1090 Proper shipping name : Acetone

Class : 3 Packing group : II

Labels : FLAMMABLE LIQUID

ERG Code : 127 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)



ACETONE

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/24/2019 5207637-00001 Date of first issue: 10/24/2019

Acetone | 67-64-1 | 5000 | 5000

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Volatile organic compounds

(VOC) content

40 CFR Part 59 National VOC Emission Standard For Con-

sumer Products, Subpart C

VOC content: 0 %

US State Regulations

Pennsylvania Right To Know

Acetone 67-64-1

California List of Hazardous Substances

Acetone 67-64-1

California Permissible Exposure Limits for Chemical Contaminants

Acetone 67-64-1

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory



ACETONE


Version Revision Date: SDS Number: Date of last issue: -

1.0 10/24/2019 5207637-00001 Date of first issue: 10/24/2019

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials: bw - Body weight: CERCLA - Comprehensive Environmental Response. Compensation. and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NTP - National Toxicology Program: NZIoC - New Zealand Inventory of



ACETONE

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/24/2019 5207637-00001 Date of first issue: 10/24/2019

Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 10/24/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8