

# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

#### **SECTION 1. IDENTIFICATION**

Product name : DENATURED ALCOHOL

Product code : 0890997341

Manufacturer or supplier's details

Company name of supplier : Wurth USA Inc.

Address : 93 Grant St.

Ramsey, NJ 07446

Telephone : (201) 825-2710

Telefax : (201) 825-1643

Emergency telephone : +1 800 255 3924

E-mail address : prodsafe@wuerth.com

Recommended use of the chemical and restrictions on use

Recommended use : Solvent

#### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 2

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 3

Acute toxicity (Dermal) : Category 3

Eye irritation : Category 2A

Specific target organ toxicity

- single exposure

: Category 1 (Eye, Central nervous system)

**GHS** label elements

Hazard pictograms :









Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.

H302 Harmful if swallowed.

H311 + H331 Toxic in contact with skin or if inhaled.





Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

H319 Causes serious eye irritation.

H370 Causes damage to organs (Eye, Central nervous system).

Precautionary Statements : Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P233 Keep container tightly closed.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equip-

ment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe mist or vapors.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON

CENTER/doctor if you feel unwell. Rinse mouth.

P302 + P352 + P312 IF ON SKIN: Wash with plenty of wa-

ter.Call a POISON CENTER/doctor if you feel unwell.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water/shower. P304 + P340 + P311 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Call a POISON

CENTER/doctor.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water

for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P307 + P311 IF exposed: Call a POISON CENTER or doctor/

physician.

P337 + P313 If eye irritation persists: Get medical advice/ atten-

tion.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

Vapors may form explosive mixture with air.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS** 

Substance / Mixture : Mixture

Chemical nature : Alcohol

Components



# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

Chemical name	CAS-No.	Concentration (% w/w)
Ethanol	64-17-5	>= 50 - < 70
Methanol	67-56-1	>= 30 - < 50
Propan-2-ol	67-63-0	>= 1 - < 5
Propyl acetate	109-60-4	>= 1 - < 5

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting unless directed to do

so by medical personnel. Get medical attention.

Rinse mouth thoroughly with water.

Never give anything by mouth to an unconscious person.

Most important symptoms

and effects, both acute and delayed

Harmful if swallowed.

Toxic in contact with skin or if inhaled.

Causes serious eye irritation. Causes damage to organs.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)



# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during fire

fighting

Do not use a solid water stream as it may scatter and spread

tire

Flash back possible over considerable distance. Vapors may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Carbon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

# **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

Remove all sources of ignition.

Ventilate the area.

Use personal protective equipment.

Follow safe handling advice and personal protective

equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapors/mists with a water spray

jet.

For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding



# **DENATURED ALCOHOL**

Version **Revision Date:** SDS Number: Date of last issue: -

12/10/2019 5349034-00001 Date of first issue: 12/10/2019 1.0

certain local or national requirements.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation If sufficient ventilation is unavailable, use with local exhaust

ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventila-

tion.

Advice on safe handling Do not get on skin or clothing.

Do not breathe vapors or spray mist.

Do not swallow. Do not get in eyes.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Non-sparking tools should be used. Keep container tightly closed.

Keep away from heat and sources of ignition.

Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the

environment.

Keep in properly labeled containers. Conditions for safe storage

> Store locked up. Keep tightly closed.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Keep away from heat and sources of ignition.

Materials to avoid Do not store with the following product types:

Strong oxidizing agents Organic peroxides Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures which in contact with water emit

flammable gases **Explosives** Gases

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### Ingredients with workplace control parameters

_				
Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	



# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

Ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m <sup>3</sup>	NIOSH REL
		STEL	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m³	OSHA Z-1
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m <sup>3</sup>	NIOSH REL
		ST	250 ppm 325 mg/m³	NIOSH REL
		TWA	200 ppm 260 mg/m <sup>3</sup>	OSHA Z-1
Propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m <sup>3</sup>	NIOSH REL
		ST	500 ppm 1,225 mg/m <sup>3</sup>	NIOSH REL
		TWA	400 ppm 980 mg/m³	OSHA Z-1
Propyl acetate	109-60-4	TWA	200 ppm 840 mg/m³	NIOSH REL
		ST	250 ppm 1,050 mg/m³	NIOSH REL
		TWA	200 ppm 840 mg/m³	OSHA Z-1
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH

# **Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentration	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work- week	40 mg/l	ACGIH BEI

**Engineering measures** 

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust venti-

lation.



# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

#### Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate

protection.

Hand protection

Material : Nitrile rubber

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the pro-

duct. Change gloves often!

Eye protection : Wear the following personal protective equipment:

Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Wear the following personal protective equipment:

If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic

protective clothing.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : colorless



# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

Odor : sweet, solvent

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : -128.99 °F / -89.44 °C

Initial boiling point and boiling

range

167.99 °F / 75.55 °C

Flash point : 54.00 °F / 12.22 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper

flammability limit

20 %(V)

Lower explosion limit / Lower

flammability limit

4 %(V)

Vapor pressure : 42.663 hPa

Relative vapor density : No data available

Relative density : 0.8

Solubility(ies)

Water solubility : completely soluble

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature : 797 °F / 425 °C

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable



# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Highly flammable liquid and vapor.

Vapors may form explosive mixture with air. Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

## Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

#### **Acute toxicity**

Harmful if swallowed.

Toxic in contact with skin or if inhaled.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: 909.09 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 9.01 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 909.09 mg/kg

Method: Calculation method

**Components:** 

**Ethanol:** 

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 124.7 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Methanol:

Acute oral toxicity : Acute toxicity estimate (Humans): 300 mg/kg



# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

Method: Expert judgment

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Expert judgment

Remarks: Based on harmonised classification in EU regulation

1272/2008, Annex VI

Acute dermal toxicity : Acute toxicity estimate (Humans): 300 mg/kg

Method: Expert judgment

Propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25 mg/l

Exposure time: 6 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Propyl acetate:

Acute oral toxicity : LD50 (Rat): 8,700 mg/kg

Acute inhalation toxicity : LC50 (Rat): 32 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 17,800 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.

#### **Components:**

**Ethanol:** 

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Methanol:

Species : Rabbit

Result : No skin irritation

Propan-2-ol:

Species : Rabbit

Result : No skin irritation

Propyl acetate:

Species : Rabbit

Result : No skin irritation



# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

Assessment : Repeated exposure may cause skin dryness or cracking.

## Serious eye damage/eye irritation

Causes serious eye irritation.

**Components:** 

**Ethanol:** 

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Method : OECD Test Guideline 405

Methanol:

Species : Rabbit

Result : No eye irritation

Propan-2-ol:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Propyl acetate:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

# Respiratory or skin sensitization

# Skin sensitization

Not classified based on available information.

# Respiratory sensitization

Not classified based on available information.

#### **Components:**

**Ethanol:** 

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact Species : Mouse Result : negative

Methanol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Propan-2-ol:

Test Type : Buehler Test Routes of exposure : Skin contact Species : Guinea pig



# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

Method : OECD Test Guideline 406

Result : negative

Propyl acetate:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

**Components:** 

**Ethanol:** 

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Mouse

Application Route: Ingestion

Result: equivocal

Methanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Propan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse



# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

Application Route: Intraperitoneal injection

Result: negative

Propyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on data from similar materials

# Carcinogenicity

Not classified based on available information.

#### Components:

#### Methanol:

Species : Mouse

Application Route : inhalation (vapor)
Exposure time : 18 Months
Result : negative

# Propan-2-ol:

Species : Rat

Application Route : inhalation (vapor) Exposure time : 104 weeks

Method : OECD Test Guideline 451

Result : negative

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

#### Reproductive toxicity

Not classified based on available information.

#### **Components:**

## **Ethanol:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Mouse

Application Route: Ingestion

Result: negative

#### Methanol:



# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

Effects on fertility : Test Type: Fertility/early embryonic development

Species: Mouse

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Mouse

Application Route: Ingestion

Result: positive

Remarks: The effects were seen only at maternally toxic dos-

es.

Propan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

**Application Route: Ingestion** 

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Propyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapor) Method: OECD Test Guideline 416

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: inhalation (vapor)

Result: negative

Remarks: Based on data from similar materials

STOT-single exposure

Causes damage to organs (Eye, Central nervous system).

**Components:** 

Methanol:

Target Organs : Eye, Central nervous system Assessment : Causes damage to organs.

Propan-2-ol:

Assessment : May cause drowsiness or dizziness.

Propyl acetate:

Assessment : May cause drowsiness or dizziness.



# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

#### STOT-repeated exposure

Not classified based on available information.

### Repeated dose toxicity

#### Components:

**Ethanol:** 

Species : Rat

NOAEL : 1,280 mg/kg LOAEL : 3,156 mg/kg Application Route : Ingestion Exposure time : 90 Days

Methanol:

Species : Rat NOAEL : 1.06 mg/l

Application Route : inhalation (vapor)

Exposure time : 90 Days

Propan-2-ol:

Species : Rat NOAEL : 12.5 mg/l

Application Route : inhalation (vapor) Exposure time : 104 Weeks

Propyl acetate:

Species : Rat

NOAEL : > 6.48 mg/l
Application Route : inhalation (vapor)

Exposure time : 90 Days

Method : OECD Test Guideline 413

#### **Aspiration toxicity**

Not classified based on available information.

# **SECTION 12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

#### **Components:**

**Ethanol:** 

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Ceriodaphnia (water flea)): > 1,000 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

ErC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l

plants

Exposure time: 72 h



# **DENATURED ALCOHOL**

Version **Revision Date:** SDS Number: Date of last issue: -

5349034-00001 Date of first issue: 12/10/2019 1.0 12/10/2019

EC10 (Chlorella vulgaris (Fresh water algae)): 11.5 mg/l

Exposure time: 72 h

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 9.6 mg/l Exposure time: 9 d

Toxicity to microorganisms EC50 (Pseudomonas putida): 6,500 mg/l

Exposure time: 16 h

Methanol:

Toxicity to fish LC50 (Lepomis macrochirus (Bluegill sunfish)): 15,400 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 22,000

Exposure time: 96 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC (Oryzias latipes (Orange-red killifish)): 15,800 mg/l

Exposure time: 200 h

Toxicity to microorganisms IC50: > 1,000 mg/l

Exposure time: 3 h

Propan-2-ol:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 24 h

EC50 (Pseudomonas putida): > 1,050 mg/l Toxicity to microorganisms

Exposure time: 16 h

Propyl acetate:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): 60 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 91.5 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 672

ma/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 83.2

mg/l



# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : IC50: > 1,000 mg/l

Exposure time: 16 h

Persistence and degradability

**Components:** 

Ethanol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 84 % Exposure time: 20 d

Methanol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 95 % Exposure time: 20 d

Propan-2-ol:

Biodegradability : Result: rapidly degradable

BOD/COD : BOD: 1.19 (BOD5)COD: 2.23BOD/COD: 53 %

Propyl acetate:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 62 % Exposure time: 20 d

Bioaccumulative potential

Components:

Ethanol:

Partition coefficient: n-

octanol/water

log Pow: -0.35

Methanol:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)

Bioconcentration factor (BCF): < 10

Partition coefficient: n-

octanol/water

log Pow: -0.77

Propan-2-ol:

Partition coefficient: n-

octanol/water

log Pow: 0.05

Propyl acetate:



# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

Partition coefficient: n-

octanol/water

log Pow: 1.4

Mobility in soil

No data available

Other adverse effects

No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

### **SECTION 14. TRANSPORT INFORMATION**

### **International Regulations**

**UNRTDG** 

UN number : UN 1986

Proper shipping name : ALCOHOLS, FLAMMABLE, TOXIC, N.O.S.

(Ethanol, Methanol)

Class : 3
Subsidiary risk : 6.1
Packing group : II
Labels : 3 (6.1)

**IATA-DGR** 

UN/ID No. : UN 1986

Proper shipping name : Alcohols, flammable, toxic, n.o.s.

(Ethanol, Methanol)

Class : 3 Subsidiary risk : 6.1 Packing group : II

Labels : Flammable Liquids, Toxic

Packing instruction (cargo : 364

aircraft)

Packing instruction (passen-

: 352

ger aircraft)

**IMDG-Code** 

UN number : UN 1986

Proper shipping name : ALCOHOLS, FLAMMABLE, TOXIC, N.O.S.

(Ethanol, Methanol)

Class : 3 Subsidiary risk : 6.1



# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

Packing group : II
Labels : 3 (6.1)
EmS Code : F-E, S-D
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **Domestic regulation**

**49 CFR** 

UN/ID/NA number : UN 1986

Proper shipping name : Alcohols, flammable, toxic n.o.s.

(Ethanol, Methanol)

Class : 3
Subsidiary risk : 6.1
Packing group : II

Labels : FLAMMABLE LIQUID, TOXIC

ERG Code : 131 Marine pollutant : no

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

# **EPCRA - Emergency Planning and Community Right-to-Know**

#### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Methanol	67-56-1	5000	15151

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

# SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure) Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Methanol 67-56-1 >= 30 - < 50 %

Propan-2-ol 67-63-0 >= 1 - < 5 %

Volatile organic compounds

(VOC) content

40 CFR Part 59 National VOC Emission Standard For Con-

sumer Products, Subpart C



# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

VOC content: 100 %

#### **US State Regulations**

### Pennsylvania Right To Know

Ethanol	64-17-5
Methanol	67-56-1
Propyl acetate	109-60-4
Propan-2-ol	67-63-0

#### California Prop. 65

WARNING: This product can expose you to chemicals including Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

#### **California List of Hazardous Substances**

Ethanol	64-17-5
Methanol	67-56-1
Propyl acetate	109-60-4
Propan-2-ol	67-63-0

## **California Permissible Exposure Limits for Chemical Contaminants**

 Ethanol
 64-17-5

 Methanol
 67-56-1

 Propyl acetate
 109-60-4

 Propan-2-ol
 67-63-0


#### The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA 704:



Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations



# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG -United Nations Recommendations on the Transport of Dangerous Goods: vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

**Data Sheet** 

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 12/10/2019



# **DENATURED ALCOHOL**

Version Revision Date: SDS Number: Date of last issue: -

1.0 12/10/2019 5349034-00001 Date of first issue: 12/10/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8