

**PRO BOND PREMIUM ADHESIVE - NATURAL
COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.6	11/11/2022	10699484-00006	Date of first issue: 10/11/2017

SECTION 1. IDENTIFICATION

Product name : PRO BOND PREMIUM ADHESIVE - NATURAL COLOR
Product code : 0893100890

Manufacturer or supplier's details

Company name of supplier : Wurth USA Inc.
Address : 93 Grant St.
Ramsey, NJ 07446
Telephone : (201) 825-2710
Telefax : (201) 825-1643
Emergency telephone : +1 800 255 3924
E-mail address : prodsafe@wurth.com

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives

Restrictions on use : This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Flammable aerosols : Category 1
Gases under pressure : Liquefied gas
Skin irritation : Category 2
Eye irritation : Category 2A
Carcinogenicity : Category 2
Specific target organ toxicity : Category 3
- single exposure

GHS label elements

**PRO BOND PREMIUM ADHESIVE - NATURAL
COLOR**

Version 2.6 Revision Date: 11/11/2022 SDS Number: 10699484-00006 Date of last issue: 05/20/2022
Date of first issue: 10/11/2017

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.

Precautionary Statements

: **Prevention:**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical attention.
P332 + P313 If skin irritation occurs: Get medical attention.
P337 + P313 If eye irritation persists: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

**PRO BOND PREMIUM ADHESIVE - NATURAL
COLOR**

Version 2.6 Revision Date: 11/11/2022 SDS Number: 10699484-00006 Date of last issue: 05/20/2022
Date of first issue: 10/11/2017

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Dichloromethane	75-09-2	>= 50 - < 70
Petroleum gases, liquefied, sweetened	68476-86-8	>= 30 - < 50

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of causing cancer.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

**PRO BOND PREMIUM ADHESIVE - NATURAL
COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.6	11/11/2022	10699484-00006	Date of first issue: 10/11/2017

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides
Chlorine compounds
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
-

**PRO BOND PREMIUM ADHESIVE - NATURAL
COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.6	11/11/2022	10699484-00006	Date of first issue: 10/11/2017

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Avoid breathing spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.

Do not breathe decomposition products.
- Conditions for safe storage : Store locked up.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.
- Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases

PRO BOND PREMIUM ADHESIVE - NATURAL COLOR

Version 2.6 Revision Date: 11/11/2022 SDS Number: 10699484-00006 Date of last issue: 05/20/2022
Date of first issue: 10/11/2017

Recommended storage temperature : < 104 °F / < 40 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Dichloromethane	75-09-2	TWA	50 ppm	ACGIH
		PEL	25 ppm	OSHA CARC
		STEL	125 ppm	OSHA CARC
Petroleum gases, liquefied, sweetened	68476-86-8	TWA	800 ppm 1,900 mg/m ³	NIOSH REL
		STEL	1,000 ppm	ACGIH

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen chloride	7647-01-0	C	2 ppm	ACGIH
		C	5 ppm 7 mg/m ³	NIOSH REL
		C	5 ppm 7 mg/m ³	OSHA Z-1
Phosgene	75-44-5	C	0.2 ppm 0.8 mg/m ³	NIOSH REL
		TWA	0.1 ppm 0.4 mg/m ³	NIOSH REL
		TWA	0.1 ppm 0.4 mg/m ³	OSHA Z-1
Carbon monoxide	630-08-0	C	0.02 ppm	ACGIH
		TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m ³	NIOSH REL
Chlorine	7782-50-5	C	200 ppm 229 mg/m ³	NIOSH REL
		TWA	50 ppm 55 mg/m ³	OSHA Z-1
		TWA	0.1 ppm	ACGIH
		STEL	0.4 ppm	ACGIH
		C	0.5 ppm 1.45 mg/m ³	NIOSH REL
		C	1 ppm 3 mg/m ³	OSHA Z-1

**PRO BOND PREMIUM ADHESIVE - NATURAL
COLOR**

Version 2.6 Revision Date: 11/11/2022 SDS Number: 10699484-00006 Date of last issue: 05/20/2022
Date of first issue: 10/11/2017

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Dichloromethane	75-09-2	Dichlorome-thane	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/l	ACGIH BEI

Engineering measures : Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure

**PRO BOND PREMIUM ADHESIVE - NATURAL
COLOR**

Version 2.6	Revision Date: 11/11/2022	SDS Number: 10699484-00006	Date of last issue: 05/20/2022 Date of first issue: 10/11/2017
----------------	------------------------------	-------------------------------	---

potential.

Wear the following personal protective equipment:

If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.

Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Propellant	: Petroleum gases, liquefied, sweetened
Color	: colored
Odor	: sweet, pungent
Odor Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: Not applicable
Flash point	: Not applicable
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: Not applicable
Relative vapor density	: Not applicable

**PRO BOND PREMIUM ADHESIVE - NATURAL
COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.6	11/11/2022	10699484-00006	Date of first issue: 10/11/2017

Relative density	:	No data available
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n- octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reac- tions	:	Extremely flammable aerosol. Vapors may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents

Hazardous decomposition products

Thermal decomposition	:	Hydrogen chloride Phosgene Carbon monoxide Chlorine
-----------------------	---	--

**PRO BOND PREMIUM ADHESIVE - NATURAL
COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.6	11/11/2022	10699484-00006	Date of first issue: 10/11/2017

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:**Dichloromethane:**

Acute oral toxicity : LD50 (Rat): $\geq 2,000$ mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Mouse): 49 mg/l
Exposure time: 7 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rat): $\geq 2,000$ mg/kg
Method: OECD Test Guideline 402

Petroleum gases, liquefied, sweetened:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm
Exposure time: 15 min
Test atmosphere: gas
Remarks: Based on data from similar materials

Skin corrosion/irritation

Causes skin irritation.

Components:**Dichloromethane:**

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Dichloromethane:**

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

**PRO BOND PREMIUM ADHESIVE - NATURAL
COLOR**

Version 2.6 Revision Date: 11/11/2022 SDS Number: 10699484-00006 Date of last issue: 05/20/2022
Date of first issue: 10/11/2017

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Dichloromethane:**

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Dichloromethane:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: positive

Test Type: Bacterial reverse mutation assay (AMES)
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

Petroleum gases, liquefied, sweetened:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

**PRO BOND PREMIUM ADHESIVE - NATURAL
COLOR**

Version 2.6 Revision Date: 11/11/2022 SDS Number: 10699484-00006 Date of last issue: 05/20/2022
Date of first issue: 10/11/2017

Carcinogenicity

Suspected of causing cancer.

Components:**Dichloromethane:**

Species : Mouse
Application Route : inhalation (vapor)
Exposure time : 102 weeks
Result : positive

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

IARC	Group 2A: Probably carcinogenic to humans Dichloromethane	75-09-2
OSHA	OSHA specifically regulated carcinogen Dichloromethane	75-09-2
NTP	Reasonably anticipated to be a human carcinogen Dichloromethane	75-09-2

Reproductive toxicity

Not classified based on available information.

Components:**Dichloromethane:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: inhalation (vapor)
Result: negative

Petroleum gases, liquefied, sweetened:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat

**PRO BOND PREMIUM ADHESIVE - NATURAL
COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.6	11/11/2022	10699484-00006	Date of first issue: 10/11/2017

Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

May cause drowsiness or dizziness.

Components:**Dichloromethane:**

Assessment : May cause drowsiness or dizziness.

Petroleum gases, liquefied, sweetened:

Assessment : May cause drowsiness or dizziness.
Remarks : Based on data from similar materials

STOT-repeated exposure

Not classified based on available information.

Components:**Dichloromethane:**

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Repeated dose toxicity**Components:****Dichloromethane:**

Species : Rat
NOAEL : 6 mg/kg
Application Route : Ingestion
Exposure time : 104 Weeks

Species : Rat
NOAEL : 694 mg/l
LOAEL : 1,736 mg/l
Application Route : inhalation (vapor)
Exposure time : 2 y

Petroleum gases, liquefied, sweetened:

Species : Rat
NOAEL : >=10000 ppm
Application Route : inhalation (gas)
Exposure time : 13 Weeks
Method : OECD Test Guideline 413
Remarks : Based on data from similar materials

**PRO BOND PREMIUM ADHESIVE - NATURAL
COLOR**

Version 2.6 Revision Date: 11/11/2022 SDS Number: 10699484-00006 Date of last issue: 05/20/2022
Date of first issue: 10/11/2017

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Dichloromethane:**

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 193 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 27 mg/l
aquatic invertebrates Exposure time: 48 h
- Toxicity to fish (Chronic tox- : NOEC (Pimephales promelas (fathead minnow)): 83 mg/l
icity) Exposure time: 28 d
- Toxicity to microorganisms : EC50: 2,590 mg/l
Exposure time: 40 min
Method: OECD Test Guideline 209

Persistence and degradability**Components:****Dichloromethane:**

- Biodegradability : Result: Readily biodegradable.
Biodegradation: 68 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Petroleum gases, liquefied, sweetened:

- Biodegradability : Result: Readily biodegradable.
Remarks: Based on data from similar materials

Bioaccumulative potential**Components:****Dichloromethane:**

- Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 40
Method: OECD Test Guideline 305

- Partition coefficient: n- : log Pow: 1.25
octanol/water

Petroleum gases, liquefied, sweetened:

- Partition coefficient: n- : log Pow: <= 2.8

**PRO BOND PREMIUM ADHESIVE - NATURAL
COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.6	11/11/2022	10699484-00006	Date of first issue: 10/11/2017

octanol/water

Mobility in soil

No data available

Other adverse effectsNo data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

- Waste from residues : Dispose of in accordance with local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)
-

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

- UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1

IATA-DGR

- UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

- UN number : UN 1950
Proper shipping name : AEROSOLS
- Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
-

PRO BOND PREMIUM ADHESIVE - NATURAL COLOR

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.6	11/11/2022	10699484-00006	Date of first issue: 10/11/2017

EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1950
Proper shipping name : Aerosols

Class : 2.1
Packing group : Not assigned by regulation
Labels : FLAMMABLE GAS
ERG Code : 126
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Dichloromethane	75-09-2	1000	1492

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Gases under pressure
Skin corrosion or irritation
Serious eye damage or eye irritation
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Dichloromethane 75-09-2 >= 50 - < 70 %

Volatile organic compounds (VOC) content 40 CFR Part 59 National VOC Emission Standard For Consumer Products, Subpart C
VOC content: 34.89 % / 295.64 g/l
Category: Adhesives - aerosols

PRO BOND PREMIUM ADHESIVE - NATURAL COLOR

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.6	11/11/2022	10699484-00006	Date of first issue: 10/11/2017

US State Regulations

Pennsylvania Right To Know

Dichloromethane	75-09-2
Petroleum gases, liquefied, sweetened	68476-86-8

California Prop. 65

WARNING: This product can expose you to chemicals including Dichloromethane, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Dichloromethane	75-09-2
-----------------	---------

California Permissible Exposure Limits for Chemical Contaminants

Dichloromethane	75-09-2
Petroleum gases, liquefied, sweetened	68476-86-8

California Regulated Carcinogens

Dichloromethane	75-09-2
-----------------	---------

The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

TSCA list

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.


SECTION 16. OTHER INFORMATION

Further information

PRO BOND PREMIUM ADHESIVE - NATURAL COLOR

Version 2.6 Revision Date: 11/11/2022 SDS Number: 10699484-00006 Date of last issue: 05/20/2022
Date of first issue: 10/11/2017

NFPA 704:



HMIS® IV:

HEALTH	*	2
FLAMMABILITY		4
PHYSICAL HAZARD		3

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA CARC	:	OSHA Specifically Regulated Chemicals/Carcinogens
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA CARC / PEL	:	Permissible exposure limit (PEL)
OSHA CARC / STEL	:	Excursion limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-1 / C	:	Ceiling

AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EC_x - Concentration associated with x% response; EHS - Extremely Hazardous Substance; EL_x - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErC_x - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC₅₀ - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemi-

**PRO BOND PREMIUM ADHESIVE - NATURAL
COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.6	11/11/2022	10699484-00006	Date of first issue: 10/11/2017

icals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/11/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8