

**PRO BOND CAL COMPLIANT ADHESIVE -
NATURAL COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.4	11/11/2022	10699493-00005	Date of first issue: 10/11/2017

SECTION 1. IDENTIFICATION

Product name : PRO BOND CAL COMPLIANT ADHESIVE - NATURAL COLOR

Product code : 0893100885

Manufacturer or supplier's details

Company name of supplier : Wurth USA Inc.

Address : 93 Grant St.
Ramsey, NJ 07446

Telephone : (201) 825-2710

Telefax : (201) 825-1643

Emergency telephone : +1 800 255 3924

E-mail address : prodsafe@wurth.com

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Flammable aerosols : Category 1

Gases under pressure : Liquefied gas

Eye irritation : Category 2B

Specific target organ toxicity : Category 3
- single exposure

GHS label elements

Hazard pictograms :



Signal Word : Danger

**PRO BOND CAL COMPLIANT ADHESIVE -
NATURAL COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.4	11/11/2022	10699493-00005	Date of first issue: 10/11/2017

Hazard Statements : H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H320 Causes eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary Statements : **Prevention:**
P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical attention.

Storage:

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Repeated exposure may cause skin dryness or cracking.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Methyl acetate	79-20-9	>= 50 - < 70
Petroleum gases, liquefied, sweetened	68476-86-8	>= 20 - < 30

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.

**PRO BOND CAL COMPLIANT ADHESIVE -
NATURAL COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.4	11/11/2022	10699493-00005	Date of first issue: 10/11/2017

When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Get medical attention if symptoms occur.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water
for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

Most important symptoms
and effects, both acute and
delayed : Causes eye irritation.
May cause drowsiness or dizziness.
Prolonged or repeated contact may dry skin and cause irrita-
tion.

Protection of first-aiders : First Aid responders should pay attention to self-protection,
and use the recommended personal protective equipment
when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing
media : None known.

Specific hazards during fire
fighting : Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting
due to the high vapor pressure.

Hazardous combustion prod-
ucts : Carbon oxides

Specific extinguishing meth-
ods : Use extinguishing measures that are appropriate to local cir-
cumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do
so.

**PRO BOND CAL COMPLIANT ADHESIVE -
NATURAL COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.4	11/11/2022	10699493-00005	Date of first issue: 10/11/2017

Evacuate area.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.
for fire-fighters Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : Remove all sources of ignition.
tive equipment and emer- Use personal protective equipment.
gency procedures Follow safe handling advice (see section 7) and personal pro-
tective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or
oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages
cannot be contained.

Methods and materials for : Non-sparking tools should be used.
containment and cleaning up Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray
jet.
For large spills, provide diking or other appropriate contain-
ment to keep material from spreading. If diked material can be
pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absor-
bent.
Local or national regulations may apply to releases and dispo-
sal of this material, as well as those materials and items em-
ployed in the cleanup of releases. You will need to determine
which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding
certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE
CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust
ventilation.
If advised by assessment of the local exposure potential, use
only in an area equipped with explosion-proof exhaust ventila-
tion.

Advice on safe handling : Do not get on skin or clothing.
Avoid breathing spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.

PRO BOND CAL COMPLIANT ADHESIVE - NATURAL COLOR

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.4	11/11/2022	10699493-00005	Date of first issue: 10/11/2017

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the environment.

Do not spray on an open flame or other ignition source.

Conditions for safe storage : Store locked up.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases

Recommended storage temperature : < 104 °F / < 40 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methyl acetate	79-20-9	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 610 mg/m ³	NIOSH REL
		ST	250 ppm 760 mg/m ³	NIOSH REL
		TWA	200 ppm 610 mg/m ³	OSHA Z-1
Petroleum gases, liquefied, sweetened	68476-86-8	TWA	800 ppm 1,900 mg/m ³	NIOSH REL
		STEL	1,000 ppm	ACGIH

Engineering measures : Minimize workplace exposure concentrations.

**PRO BOND CAL COMPLIANT ADHESIVE -
NATURAL COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.4	11/11/2022	10699493-00005	Date of first issue: 10/11/2017

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

**PRO BOND CAL COMPLIANT ADHESIVE -
NATURAL COLOR**

Version 2.4	Revision Date: 11/11/2022	SDS Number: 10699493-00005	Date of last issue: 05/20/2022 Date of first issue: 10/11/2017
----------------	------------------------------	-------------------------------	---

Propellant	:	Petroleum gases, liquefied, sweetened
Color	:	colored
Odor	:	solvent
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	Not applicable
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Relative density	:	No data available
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

**PRO BOND CAL COMPLIANT ADHESIVE -
NATURAL COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.4	11/11/2022	10699493-00005	Date of first issue: 10/11/2017

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Extremely flammable aerosol. Vapors may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:**Methyl acetate:**

Acute oral toxicity	: LD50 (Rat): 6,482 mg/kg
Acute inhalation toxicity	: LC50 (Rabbit): > 49.2 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

Petroleum gases, liquefied, sweetened:

Acute inhalation toxicity	: LC50 (Rat): > 800000 ppm Exposure time: 15 min Test atmosphere: gas Remarks: Based on data from similar materials
---------------------------	--

**PRO BOND CAL COMPLIANT ADHESIVE -
NATURAL COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.4	11/11/2022	10699493-00005	Date of first issue: 10/11/2017

Skin corrosion/irritation

Not classified based on available information.

Components:**Methyl acetate:**

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation

Assessment	:	Repeated exposure may cause skin dryness or cracking.
------------	---	---

Serious eye damage/eye irritation

Causes eye irritation.

Components:**Methyl acetate:**

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 7 days
Method	:	OECD Test Guideline 405

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Components:**Methyl acetate:**

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
-----------------------	---	---

	:	Test Type: In vitro mammalian cell gene mutation test Result: negative Remarks: Based on data from similar materials
--	---	--

Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: Inhalation Method: OECD Test Guideline 474 Result: negative
----------------------	---	--

Petroleum gases, liquefied, sweetened:

**PRO BOND CAL COMPLIANT ADHESIVE -
NATURAL COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.4	11/11/2022	10699493-00005	Date of first issue: 10/11/2017

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:**Methyl acetate:**

Species : Rat
Application Route : Inhalation
Exposure time : 18 Months
Result : negative
Remarks : Based on data from similar materials

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:**Petroleum gases, liquefied, sweetened:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

**PRO BOND CAL COMPLIANT ADHESIVE -
NATURAL COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.4	11/11/2022	10699493-00005	Date of first issue: 10/11/2017

reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

May cause drowsiness or dizziness.

Components:**Methyl acetate:**

Assessment : May cause drowsiness or dizziness.

Petroleum gases, liquefied, sweetened:

Assessment : May cause drowsiness or dizziness.
Remarks : Based on data from similar materials

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity**Components:****Methyl acetate:**

Species : Rat
NOAEL : 1.057 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 28 Days
Method : OECD Test Guideline 412

Petroleum gases, liquefied, sweetened:

Species : Rat
NOAEL : ≥ 10000 ppm
Application Route : inhalation (gas)
Exposure time : 13 Weeks
Method : OECD Test Guideline 413
Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Methyl acetate:**

**PRO BOND CAL COMPLIANT ADHESIVE -
NATURAL COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.4	11/11/2022	10699493-00005	Date of first issue: 10/11/2017

Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): 250 - 350 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,026.7 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	ErC50 (Desmodesmus subspicatus (green algae)): > 120 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 EC10 (Desmodesmus subspicatus (green algae)): > 120 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to microorganisms	:	EC10 (Pseudomonas putida): 1,830 mg/l Exposure time: 16 h

Persistence and degradability**Components:****Methyl acetate:**

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 70 % Exposure time: 28 d Method: OECD Test Guideline 301D
------------------	---	---

Petroleum gases, liquefied, sweetened:

Biodegradability	:	Result: Readily biodegradable. Remarks: Based on data from similar materials
------------------	---	---

Bioaccumulative potential**Components:****Methyl acetate:**

Partition coefficient: n-octanol/water	:	log Pow: 0.18
--	---	---------------

Petroleum gases, liquefied, sweetened:

Partition coefficient: n-octanol/water	:	log Pow: <= 2.8
--	---	-----------------

Mobility in soil

No data available

Other adverse effects

No data available

**PRO BOND CAL COMPLIANT ADHESIVE -
NATURAL COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.4	11/11/2022	10699493-00005	Date of first issue: 10/11/2017

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

- Waste from residues : Dispose of in accordance with local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

- UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1

IATA-DGR

- UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

- UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

**PRO BOND CAL COMPLIANT ADHESIVE -
NATURAL COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.4	11/11/2022	10699493-00005	Date of first issue: 10/11/2017

UN/ID/NA number	: UN 1950
Proper shipping name	: Aerosols
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: FLAMMABLE GAS
ERG Code	: 126
Marine pollutant	: no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	: Flammable (gases, aerosols, liquids, or solids) Gases under pressure Serious eye damage or eye irritation Specific target organ toxicity (single or repeated exposure)
-----------------------------	---

SARA 313	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
-----------------	---

Volatile organic compounds (VOC) content	40 CFR Part 59 National VOC Emission Standard For Consumer Products, Subpart C VOC content: 25 % Category: Adhesives - aerosols
---	---

US State Regulations**Pennsylvania Right To Know**

Methyl acetate	79-20-9
Non Hazardous Component	Not Assigned
Petroleum gases, liquefied, sweetened	68476-86-8

California List of Hazardous Substances

Methyl acetate	79-20-9
----------------	---------

California Permissible Exposure Limits for Chemical Contaminants

Methyl acetate	79-20-9
Petroleum gases, liquefied, sweetened	68476-86-8

PRO BOND CAL COMPLIANT ADHESIVE - NATURAL COLOR

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.4	11/11/2022	10699493-00005	Date of first issue: 10/11/2017


The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	/	1
FLAMMABILITY		4
PHYSICAL HAZARD		3

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	: 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -

**PRO BOND CAL COMPLIANT ADHESIVE -
NATURAL COLOR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/20/2022
2.4	11/11/2022	10699493-00005	Date of first issue: 10/11/2017

International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/11/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8