

PRODUCT DATA SHEET

PRODUCT NAME:

PRO BOND DRY LUBRICANT

PRODUCT NUMBER:

WUR-DRYLUBE-AA

Typical Physical Properties:

Pattern:	Fine mist
Solvents:	Isoparaffinic / Hydrocarbon propellant
Color:	Hazy liquid
VOC:	60.2%
VOC:	373.3 g/L
Shelf Life:	1 Year in Unopened Container

Properties:

- Spray application
- Protection against rust
- Fast drying

Suitable for:

Maintaining and reducing friction on saw tables, drill presses, planers, band saws, lathes, and all hand tools. Dry Lubricant will eliminate hang-ups on sliding surfaces.

Features:

It protects from rust and is fast drying, non-staining, and will not attract dirt or dust. Dry Lubricant is slicker than paste wax and is easier and faster to apply than paste wax.

Directions:

Clean saw or tool with a degreaser. Spray a light even coat over surface. Allow a few seconds to dry. Wipe with a clean cloth, wait 3-4 minutes and then buff to a shine. Apply a second coat if needed.

These instructions are only recommendations, which are based on our experience. We advise preliminary testing before use. For further details see product information

Not For Retail Sale.

Handling and Application:

Use only in well ventilated areas. Do not use near ignition sources.

Storage Conditions:

Store between 60° F and 90° F for best performance. Do not expose to direct sunlight. Diminished performance may occur below 60° F. If so, warm canister to room temperature. Remove directly from concrete floor in cold temps. Do not freeze.

Attention: Empty container remains hazardous until all vapors, which may explode upon ignition, are gone from residue and container. Observe all labeled hazard precautions. Do not cut, puncture, or weld while hazard exists. Do not reuse empty container. Recycle, or dispose of, according to all federal, state, and local regulations.

Please refer to the Safety Data sheet for further information.