

## METHYL ETHYL KETONE

Version 1.0      Revision Date: 10/24/2019      SDS Number: 5207657-00001      Date of last issue: -  
Date of first issue: 10/24/2019

---

**SECTION 1. IDENTIFICATION**

Product name : METHYL ETHYL KETONE

Product code : 082344055

**Manufacturer or supplier's details**

Company name of supplier : Wurth USA Inc.

Address : 93 Grant St.  
Ramsey, NJ 07446

Telephone : (201) 825-2710

Telefax : (201) 825-1643

Emergency telephone : +1 800 255 3924

E-mail address : prodsafe@wuerth.com

**Recommended use of the chemical and restrictions on use**

Recommended use : Coatings and paints, thinners, paint removers

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Flammable liquids : Category 2

Eye irritation : Category 2A

Specific target organ toxicity : Category 3  
- single exposure

**GHS label elements**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Precautionary Statements : **Prevention:**  
P210 Keep away from heat/sparks/open flames/hot surfaces.  
No smoking.  
P233 Keep container tightly closed.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equip-

---

**METHYL ETHYL KETONE**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/24/2019	5207657-00001	Date of first issue: 10/24/2019

---

ment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist or vapors.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

Repeated exposure may cause skin dryness or cracking.

Vapors may form explosive mixture with air.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Substance

Substance name : Butanone

CAS-No. : 78-93-3

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Butanone	78-93-3	>= 90 - <= 100

Actual concentration is withheld as a trade secret

---

**SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.

**METHYL ETHYL KETONE**

Version 1.0      Revision Date: 10/24/2019      SDS Number: 5207657-00001      Date of last issue: -  
Date of first issue: 10/24/2019

---

- Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting. If vomiting occurs have person lean forward. Call a physician or poison control center immediately. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : Causes serious eye irritation. May cause drowsiness or dizziness. Prolonged or repeated contact may dry skin and cause irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
- 

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire. Flash back possible over considerable distance. Vapors may form explosive mixtures with air. Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

## METHYL ETHYL KETONE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/24/2019	5207657-00001	Date of first issue: 10/24/2019

---

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Ventilate the area.  
Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
- 

**SECTION 7. HANDLING AND STORAGE**

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Do not breathe vapors or spray mist.  
Do not swallow.  
Do not get in eyes.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
-

**METHYL ETHYL KETONE**

Version 1.0      Revision Date: 10/24/2019      SDS Number: 5207657-00001      Date of last issue: -  
 Date of first issue: 10/24/2019

Non-sparking tools should be used.  
 Keep container tightly closed.  
 Keep away from heat and sources of ignition.  
 Take precautionary measures against static discharges.  
 Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.  
 Store locked up.  
 Keep tightly closed.  
 Keep in a cool, well-ventilated place.  
 Store in accordance with the particular national regulations.  
 Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:  
 Strong oxidizing agents  
 Organic peroxides  
 Flammable solids  
 Pyrophoric liquids  
 Pyrophoric solids  
 Self-heating substances and mixtures  
 Substances and mixtures which in contact with water emit flammable gases  
 Explosives  
 Gases

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Butanone	78-93-3	TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
		TWA	200 ppm 590 mg/m <sup>3</sup>	OSHA Z-1
		TWA	200 ppm 590 mg/m <sup>3</sup>	NIOSH REL
		ST	300 ppm 885 mg/m <sup>3</sup>	NIOSH REL

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI

## METHYL ETHYL KETONE

Version 1.0      Revision Date: 10/24/2019      SDS Number: 5207657-00001      Date of last issue: -  
Date of first issue: 10/24/2019

---

**Engineering measures** : Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

**Personal protective equipment**

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

**Hand protection**  
**Material** : butyl-rubber

**Remarks** : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

**Eye protection** : Wear the following personal protective equipment:  
Safety goggles

**Skin and body protection** : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

**Hygiene measures** : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

## METHYL ETHYL KETONE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/24/2019	5207657-00001	Date of first issue: 10/24/2019

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	:	liquid
Color	:	clear
Odor	:	characteristic
Odor Threshold	:	2 - 85 ppm
pH	:	No data available
Melting point/freezing point	:	-123 °F / -86 °C (1,013 hPa)
Initial boiling point and boiling range	:	175.3 °F / 79.6 °C (1,013 hPa)
Flash point	:	16 °F / -9 °C
Evaporation rate	:	6 (Butyl Acetate=1.0)  2.7 (Diethylether=1.0)
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	12 %(V)
Lower explosion limit / Lower flammability limit	:	1.5 %(V)
Vapor pressure	:	126 hPa (68 °F / 20 °C)  370 hPa (122 °F / 50 °C)
Relative vapor density	:	2.4 (68 °F / 20 °C)
Relative density	:	0.81 (68 °F / 20 °C)
Density	:	810 kg/m <sup>3</sup> (68 °F / 20 °C)
Solubility(ies) Water solubility	:	soluble
Partition coefficient: n-octanol/water	:	log Pow: 0.3 (104 °F / 40 °C) Method: OECD Test Guideline 117

## METHYL ETHYL KETONE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/24/2019	5207657-00001	Date of first issue: 10/24/2019

---

Autoignition temperature : 959 °F / 515 °C

Decomposition temperature : No data available

Viscosity

    Viscosity, dynamic : 0.4 mPa.s (77 °F / 25 °C)

    Viscosity, kinematic : < 14 mm<sup>2</sup>/s (104 °F / 40 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Minimum ignition energy : 0.53 mJ

Particle size : Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Highly flammable liquid and vapor.  
Vapors may form explosive mixture with air.  
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Product:**

Acute oral toxicity : Acute toxicity estimate: 2,500 mg/kg  
Method: Calculation method

**Components:**

**Butanone:**



## METHYL ETHYL KETONE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/24/2019	5207657-00001	Date of first issue: 10/24/2019

---

Acute oral toxicity : LD50 (Rat): > 2,000 - 5,000 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 25.5 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 436  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Components:****Butanone:**

Assessment : Repeated exposure may cause skin dryness or cracking.

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Components:****Butanone:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days  
Method : OECD Test Guideline 405

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Components:****Butanone:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

**Germ cell mutagenicity**

Not classified based on available information.

**METHYL ETHYL KETONE**

Version 1.0      Revision Date: 10/24/2019      SDS Number: 5207657-00001      Date of last issue: -  
Date of first issue: 10/24/2019

---

**Components:****Butanone:**

- Genotoxicity in vitro      :    Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative
- Test Type: In vitro mammalian cell gene mutation test  
Result: negative
- Test Type: Chromosome aberration test in vitro  
Result: negative
- Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative
- Test Type: Saccharomyces cerevisiae, gene mutation assay (in vitro)  
Result: negative
- Genotoxicity in vivo      :    Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

**Carcinogenicity**

Not classified based on available information.

**IARC**      No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**      No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**      No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**Components:****Butanone:**

- Effects on fertility      :    Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials
- Effects on fetal development      :    Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Inhalation  
Method: OECD Test Guideline 414  
Result: negative

## METHYL ETHYL KETONE

Version 1.0      Revision Date: 10/24/2019      SDS Number: 5207657-00001      Date of last issue: -  
Date of first issue: 10/24/2019

---

**STOT-single exposure**

May cause drowsiness or dizziness.

**Components:****Butanone:**

Assessment : May cause drowsiness or dizziness.

**STOT-repeated exposure**

Not classified based on available information.

**Repeated dose toxicity****Components:****Butanone:**

Species : Rat  
NOAEL : 14.84 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 90 Days  
Method : OECD Test Guideline 413

**Aspiration toxicity**

Not classified based on available information.

**Components:****Butanone:**

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Butanone:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,993 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 308 mg/l  
aquatic invertebrates : Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): 2,029  
plants : mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 1,240

**METHYL ETHYL KETONE**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/24/2019	5207657-00001	Date of first issue: 10/24/2019

---

mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

**Persistence and degradability****Components:****Butanone:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 98 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

**Bioaccumulative potential****Components:****Butanone:**

Partition coefficient: n- : log Pow: 0.3  
octanol/water

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 1193  
Proper shipping name : METHYL ETHYL KETONE  
Class : 3  
Packing group : II  
Labels : 3

**IATA-DGR**

**METHYL ETHYL KETONE**

Version      Revision Date:      SDS Number:      Date of last issue: -  
 1.0            10/24/2019            5207657-00001      Date of first issue: 10/24/2019

UN/ID No.                    : UN 1193  
 Proper shipping name      : Ethyl methyl ketone  
 Class                        : 3  
 Packing group              : II  
 Labels                      : Flammable Liquids  
 Packing instruction (cargo : 364  
 aircraft)  
 Packing instruction (passen- : 353  
 ger aircraft)

**IMDG-Code**

UN number                    : UN 1193  
 Proper shipping name      : ETHYL METHYL KETONE  
  
 Class                        : 3  
 Packing group              : II  
 Labels                      : 3  
 EmS Code                    : F-E, S-D  
 Marine pollutant            : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

UN/ID/NA number            : UN 1193  
 Proper shipping name      : Ethyl methyl ketone  
  
 Class                        : 3  
 Packing group              : II  
 Labels                      : FLAMMABLE LIQUID  
 ERG Code                    : 127  
 Marine pollutant            : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Butanone	78-93-3	5000	5000

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards**            : Flammable (gases, aerosols, liquids, or solids)

**METHYL ETHYL KETONE**

Version 1.0      Revision Date: 10/24/2019      SDS Number: 5207657-00001      Date of last issue: -  
Date of first issue: 10/24/2019

Serious eye damage or eye irritation  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Volatile organic compounds (VOC) content** 40 CFR Part 59 National VOC Emission Standard For Consumer Products, Subpart C  
VOC content: 100 %

**US State Regulations**
**Pennsylvania Right To Know**

Butanone 78-93-3

**California List of Hazardous Substances**


Butanone 78-93-3

**California Permissible Exposure Limits for Chemical Contaminants**

Butanone 78-93-3

**The ingredients of this product are reported in the following inventories:**

TSCA : All substances listed as active on the TSCA inventory

**SECTION 16. OTHER INFORMATION**
**Further information**
**NFPA 704:**

**HMIS® IV:**

<b>HEALTH</b>	/	<b>2</b>
<b>FLAMMABILITY</b>	<b>3</b>	
<b>PHYSICAL HAZARD</b>	<b>0</b>	

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
NIOSH REL : USA. NIOSH Recommended Exposure Limits  
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

**METHYL ETHYL KETONE**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/24/2019	5207657-00001	Date of first issue: 10/24/2019

---

ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/24/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text.

**METHYL ETHYL KETONE**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/24/2019	5207657-00001	Date of first issue: 10/24/2019

---

Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8